

CIS Distribution Independent Linux

v2.0.0 - 07-16-2019

Terms of Use

Please see the below link for our current terms of use:

https://www.cisecurity.org/cis-securesuite/cis-securesuite-membership-terms-of-use/

Table of Contents

Intended Audience	1
Consensus Guidance Typographical Conventions	. 12
Typographical Conventions Scoring Information Profile Definitions Acknowledgements 1 Initial Setup 1.1 Filesystem Configuration 1.1.1 Disable unused filesystems 1.1.1.2 Ensure mounting of cramfs filesystems is disabled (Scored) 1.1.3 Ensure mounting of jffs2 filesystems is disabled (Scored) 1.1.4 Ensure mounting of hfs filesystems is disabled (Scored) 1.1.5 Ensure mounting of hfsplus filesystems is disabled (Scored) 1.1.6 Ensure mounting of squashfs filesystems is disabled (Scored) 1.1.1.7 Ensure mounting of udf filesystems is disabled (Scored) 1.1.1.8 Ensure mounting of FAT filesystems is limited (Not Scored) 1.1.1.5 Ensure rounting of FAT filesystems is limited (Not Scored) 1.1.1.5 Ensure nodev option set on /tmp partition (Scored) 1.1.5 Ensure nosuid option set on /tmp partition (Scored) 1.1.5 Ensure noexec option set on /tmp partition (Scored) 1.1.6 Ensure separate partition exists for /var (Scored) 1.1.7 Ensure separate partition exists for /var/tmp (Scored) 1.1.8 Ensure nodev option set on /var/tmp partition (Scored)	. 12
Profile Definitions Acknowledgements Recommendations 1 Initial Setup	. 12
Profile Definitions	. 14
Acknowledgements Recommendations	. 14
1 Initial Setup	. 15
1.1 Filesystem Configuration 1.1.1 Disable unused filesystems 1.1.1.1 Ensure mounting of cramfs filesystems is disabled (Scored) 1.1.1.2 Ensure mounting of freevxfs filesystems is disabled (Scored) 1.1.1.3 Ensure mounting of jffs2 filesystems is disabled (Scored) 1.1.1.4 Ensure mounting of hfs filesystems is disabled (Scored) 1.1.1.5 Ensure mounting of hfsplus filesystems is disabled (Scored) 1.1.1.6 Ensure mounting of squashfs filesystems is disabled (Scored) 1.1.1.7 Ensure mounting of udf filesystems is disabled (Scored) 1.1.1.8 Ensure mounting of FAT filesystems is limited (Not Scored) 1.1.1 Ensure /tmp is configured (Scored) 1.1.2 Ensure nodev option set on /tmp partition (Scored) 1.1.5 Ensure noexec option set on /tmp partition (Scored) 1.1.6 Ensure separate partition exists for /var (Scored) 1.1.7 Ensure separate partition exists for /var/tmp (Scored) 1.1.8 Ensure nodev option set on /var/tmp partition (Scored)	. 16
1.1 Disable unused filesystems	. 18
1.1.1 Disable unused filesystems	. 18
1.1.1.1 Ensure mounting of cramfs filesystems is disabled (Scored)	. 19
1.1.1.2 Ensure mounting of freevxfs filesystems is disabled (Scored)	. 20
1.1.1.3 Ensure mounting of jffs2 filesystems is disabled (Scored)	. 21
1.1.1.4 Ensure mounting of hfs filesystems is disabled (Scored)	. 23
1.1.1.5 Ensure mounting of hfsplus filesystems is disabled (Scored)	. 25
1.1.1.6 Ensure mounting of squashfs filesystems is disabled (Scored)	. 27
1.1.1.7 Ensure mounting of udf filesystems is disabled (Scored)	. 29
1.1.1.8 Ensure mounting of FAT filesystems is limited (Not Scored) 1.1.2 Ensure /tmp is configured (Scored) 1.1.3 Ensure nodev option set on /tmp partition (Scored) 1.1.4 Ensure nosuid option set on /tmp partition (Scored) 1.1.5 Ensure noexec option set on /tmp partition (Scored) 1.1.6 Ensure separate partition exists for /var (Scored) 1.1.7 Ensure separate partition exists for /var/tmp (Scored) 1.1.8 Ensure nodev option set on /var/tmp partition (Scored)	. 31
1.1.2 Ensure /tmp is configured (Scored)	. 33
1.1.3 Ensure nodev option set on /tmp partition (Scored)	. 35
1.1.4 Ensure nosuid option set on /tmp partition (Scored)	. 37
1.1.5 Ensure noexec option set on /tmp partition (Scored)	. 40
1.1.6 Ensure separate partition exists for /var (Scored)	. 42
1.1.7 Ensure separate partition exists for /var/tmp (Scored)	. 44
1.1.8 Ensure nodev option set on /var/tmp partition (Scored)	. 46
	. 48
4407	. 50
1.1.9 Ensure nosuid option set on /var/tmp partition (Scored)	. 51
1.1.10 Ensure noexec option set on /var/tmp partition (Scored)	. 52

	1.1.11 Ensure separate partition exists for /var/log (Scored)	53
	1.1.12 Ensure separate partition exists for /var/log/audit (Scored)	55
	1.1.13 Ensure separate partition exists for /home (Scored)	57
	1.1.14 Ensure nodev option set on /home partition (Scored)	59
	1.1.15 Ensure nodev option set on /dev/shm partition (Scored)	61
	1.1.16 Ensure nosuid option set on /dev/shm partition (Scored)	63
	1.1.17 Ensure noexec option set on /dev/shm partition (Scored)	65
	1.1.18 Ensure nodev option set on removable media partitions (Not Scored)	67
	1.1.19 Ensure nosuid option set on removable media partitions (Not Scored)	68
	1.1.20 Ensure noexec option set on removable media partitions (Not Scored)	69
	1.1.21 Ensure sticky bit is set on all world-writable directories (Scored)	70
	1.1.22 Disable Automounting (Scored)	72
	1.1.23 Disable USB Storage (Scored)	74
1.2	Configure Software Updates	76
	1.2.1 Ensure package manager repositories are configured (Not Scored)	77
	1.2.2 Ensure GPG keys are configured (Not Scored)	79
1.3	Filesystem Integrity Checking	81
	1.3.1 Ensure AIDE is installed (Scored)	82
	1.3.2 Ensure filesystem integrity is regularly checked (Scored)	85
1.4	Secure Boot Settings	88
	1.4.1 Ensure permissions on bootloader config are configured (Scored)	89
	1.4.2 Ensure bootloader password is set (Scored)	91
	1.4.3 Ensure authentication required for single user mode (Scored)	94
	1.4.4 Ensure interactive boot is not enabled (Not Scored)	95
1.5	Additional Process Hardening	97
	1.5.1 Ensure core dumps are restricted (Scored)	98
	1.5.2 Ensure XD/NX support is enabled (Scored)	100
	1.5.3 Ensure address space layout randomization (ASLR) is enabled (Scored)	102
	1.5.4 Ensure prelink is disabled (Scored)	104
1 6	Mandatory Access Control	106

1.6.1 Ensure Mandatory Access Control Software is Installed	107
1.6.1.1 Ensure SELinux or AppArmor are installed (Scored)	108
1.6.2 Configure SELinux	110
1.6.2.1 Ensure SELinux is not disabled in bootloader configuration (Scored)	112
1.6.2.2 Ensure the SELinux state is enforcing (Scored)	114
1.6.2.3 Ensure SELinux policy is configured (Scored)	116
1.6.2.4 Ensure SETroubleshoot is not installed (Scored)	118
1.6.2.5 Ensure the MCS Translation Service (mcstrans) is not installed (Score	-
1.6.2.6 Ensure no unconfined daemons exist (Scored)	122
1.6.3 Configure AppArmor	124
1.6.3.1 Ensure AppArmor is not disabled in bootloader configuration (Score	d) 125
1.6.3.2 Ensure all AppArmor Profiles are enforcing (Scored)	127
1.7 Warning Banners	129
1.7.1 Command Line Warning Banners	130
1.7.1.1 Ensure message of the day is configured properly (Scored)	131
1.7.1.2 Ensure local login warning banner is configured properly (Scored)	133
1.7.1.3 Ensure remote login warning banner is configured properly (Scored)	135
1.7.1.4 Ensure permissions on /etc/motd are configured (Scored)	137
1.7.1.5 Ensure permissions on /etc/issue are configured (Scored)	138
1.7.1.6 Ensure permissions on /etc/issue.net are configured (Scored)	139
1.7.2 Ensure GDM login banner is configured (Scored)	140
1.8 Ensure updates, patches, and additional security software are installed (Scored)	
2 Services	144
2.1 inetd Services	145
2.1.1 Ensure chargen services are not enabled (Scored)	146
2.1.2 Ensure daytime services are not enabled (Scored)	148
2.1.3 Ensure discard services are not enabled (Scored)	150
2.1.4 Ensure echo services are not enabled (Scored)	152
2.1.5 Ensure time services are not enabled (Scored)	154

	2.1.6 Ensure rsh server is not enabled (Scored)	156
	2.1.7 Ensure talk server is not enabled (Scored)	158
	2.1.8 Ensure telnet server is not enabled (Scored)	160
	2.1.9 Ensure tftp server is not enabled (Scored)	162
	2.1.10 Ensure xinetd is not enabled (Scored)	164
2.2	Special Purpose Services	166
2	.2.1 Time Synchronization	167
	2.2.1.1 Ensure time synchronization is in use (Not Scored)	168
	2.2.1.2 Ensure ntp is configured (Scored)	170
	2.2.1.3 Ensure chrony is configured (Scored)	173
	2.2.1.4 Ensure systemd-timesyncd is configured (Scored)	175
	2.2.2 Ensure X Window System is not installed (Scored)	178
	2.2.3 Ensure Avahi Server is not enabled (Scored)	180
	2.2.4 Ensure CUPS is not enabled (Scored)	182
	2.2.5 Ensure DHCP Server is not enabled (Scored)	184
	2.2.6 Ensure LDAP server is not enabled (Scored)	186
	2.2.7 Ensure NFS and RPC are not enabled (Scored)	188
	2.2.8 Ensure DNS Server is not enabled (Scored)	191
	2.2.9 Ensure FTP Server is not enabled (Scored)	193
	2.2.10 Ensure HTTP server is not enabled (Scored)	195
	2.2.11 Ensure IMAP and POP3 server is not enabled (Scored)	197
	2.2.12 Ensure Samba is not enabled (Scored)	199
	2.2.13 Ensure HTTP Proxy Server is not enabled (Scored)	201
	2.2.14 Ensure SNMP Server is not enabled (Scored)	203
	2.2.15 Ensure mail transfer agent is configured for local-only mode (Scored).	205
	2.2.16 Ensure rsync service is not enabled (Scored)	207
	2.2.17 Ensure NIS Server is not enabled (Scored)	209
2.3	Service Clients	211
	2.3.1 Ensure NIS Client is not installed (Scored)	212
	2.3.2 Ensure rsh client is not installed (Scored)	214

2.3.3 Ensure talk client is not installed (Scored)	216
2.3.4 Ensure telnet client is not installed (Scored)	218
2.3.5 Ensure LDAP client is not installed (Scored)	220
3 Network Configuration	222
3.1 Network Parameters (Host Only)	223
3.1.1 Ensure IP forwarding is disabled (Scored)	224
3.1.2 Ensure packet redirect sending is disabled (Scored)	226
3.2 Network Parameters (Host and Router)	228
3.2.1 Ensure source routed packets are not accepted (Scored)	229
3.2.2 Ensure ICMP redirects are not accepted (Scored)	232
3.2.3 Ensure secure ICMP redirects are not accepted (Scored)	235
3.2.4 Ensure suspicious packets are logged (Scored)	237
3.2.5 Ensure broadcast ICMP requests are ignored (Scored)	239
3.2.6 Ensure bogus ICMP responses are ignored (Scored)	241
3.2.7 Ensure Reverse Path Filtering is enabled (Scored)	243
3.2.8 Ensure TCP SYN Cookies is enabled (Scored)	245
3.2.9 Ensure IPv6 router advertisements are not accepted (Scored)	247
3.3 TCP Wrappers	249
3.3.1 Ensure TCP Wrappers is installed (Not Scored)	250
3.3.2 Ensure /etc/hosts.allow is configured (Not Scored)	252
3.3.3 Ensure /etc/hosts.deny is configured (Not Scored)	254
3.3.4 Ensure permissions on /etc/hosts.allow are configured (Scored)	256
3.3.5 Ensure permissions on /etc/hosts.deny are configured (Scored)	258
3.4 Uncommon Network Protocols	260
3.4.1 Ensure DCCP is disabled (Scored)	261
3.4.2 Ensure SCTP is disabled (Scored)	263
3.4.3 Ensure RDS is disabled (Scored)	265
3.4.4 Ensure TIPC is disabled (Scored)	267
3.5 Firewall Configuration	269
3.5.1 Configure IPv6 ip6tables	270

3.5.1.1 Ensure IPv6 default deny firewall policy (Scored)	272
3.5.1.2 Ensure IPv6 loopback traffic is configured (Scored)	274
3.5.1.3 Ensure IPv6 outbound and established connections are config Scored)	•
3.5.1.4 Ensure IPv6 firewall rules exist for all open ports (Not Scored	.)279
3.5.2 Configure IPv4 iptables	282
3.5.2.1 Ensure default deny firewall policy (Scored)	284
3.5.2.2 Ensure loopback traffic is configured (Scored)	286
3.5.2.3 Ensure outbound and established connections are configured	•
3.5.2.4 Ensure firewall rules exist for all open ports (Scored)	290
3.5.3 Ensure iptables is installed (Scored)	292
3.6 Ensure wireless interfaces are disabled (Not Scored)	294
3.7 Disable IPv6 (Not Scored)	296
4 Logging and Auditing	298
4.1 Configure System Accounting (auditd)	299
4.1.1 Configure Data Retention	300
4.1.1.1 Ensure audit log storage size is configured (Scored)	301
4.1.1.2 Ensure system is disabled when audit logs are full (Scored)	303
4.1.1.3 Ensure audit logs are not automatically deleted (Scored)	305
4.1.2 Ensure auditd is installed (Scored)	306
4.1.3 Ensure auditd service is enabled (Scored)	308
4.1.4 Ensure auditing for processes that start prior to auditd is enable	
4.1.5 Ensure events that modify date and time information are collecture.	
4.1.6 Ensure events that modify user/group information are collected	-
4.1.7 Ensure events that modify the system's network environment a (Scored)	
4.1.8 Ensure events that modify the system's Mandatory Access Cont collected (Scored)	

4.1.9 Ensure login and logout events are collected (Scored)	324
4.1.10 Ensure session initiation information is collected (Scored)	326
4.1.11 Ensure discretionary access control permission modification events collected (Scored)	
4.1.12 Ensure unsuccessful unauthorized file access attempts are collected (Scored)	333
4.1.13 Ensure use of privileged commands is collected (Scored)	336
4.1.14 Ensure successful file system mounts are collected (Scored)	338
4.1.15 Ensure file deletion events by users are collected (Scored)	341
4.1.16 Ensure changes to system administration scope (sudoers) is collected (Scored)	
4.1.17 Ensure system administrator actions (sudolog) are collected (Scored	.)346
4.1.18 Ensure kernel module loading and unloading is collected (Scored)	348
4.1.19 Ensure the audit configuration is immutable (Scored)	351
4.2 Configure Logging	353
4.2.1 Configure rsyslog	354
4.2.1.1 Ensure rsyslog is installed (Scored)	355
4.2.1.2 Ensure rsyslog Service is enabled (Scored)	357
4.2.1.3 Ensure logging is configured (Not Scored)	359
4.2.1.4 Ensure rsyslog default file permissions configured (Scored)	362
4.2.1.5 Ensure rsyslog is configured to send logs to a remote log host (Score	d).364
4.2.1.6 Ensure remote rsyslog messages are only accepted on designated log hosts. (Not Scored)	_
4.2.2 Configure journald	368
4.2.2.1 Ensure journald is configured to send logs to rsyslog (Scored)	369
4.2.2.2 Ensure journald is configured to compress large log files (Scored)	371
4.2.2.3 Ensure journald is configured to write logfiles to persistent disk (Sco	-
4.2.3 Ensure permissions on all logfiles are configured (Scored)	375
4.3 Ensure logrotate is configured (Not Scored)	377
5 Access, Authentication and Authorization	379
5.1 Configure cron	380

	5.1.1 Ensure cron daemon is enabled (Scored)	.381
	5.1.2 Ensure permissions on /etc/crontab are configured (Scored)	.383
	5.1.3 Ensure permissions on /etc/cron.hourly are configured (Scored)	.385
	5.1.4 Ensure permissions on /etc/cron.daily are configured (Scored)	.387
	5.1.5 Ensure permissions on /etc/cron.weekly are configured (Scored)	.389
	5.1.6 Ensure permissions on /etc/cron.monthly are configured (Scored)	.391
	5.1.7 Ensure permissions on /etc/cron.d are configured (Scored)	.393
	5.1.8 Ensure at/cron is restricted to authorized users (Scored)	.395
5.2	SSH Server Configuration	.397
	5.2.1 Ensure permissions on /etc/ssh/sshd_config are configured (Scored)	.398
	5.2.2 Ensure permissions on SSH private host key files are configured (Scored	-
	5.2.3 Ensure permissions on SSH public host key files are configured (Scored)	
	5.2.4 Ensure SSH Protocol is set to 2 (Scored)	
	5.2.5 Ensure SSH LogLevel is appropriate (Scored)	
	5.2.6 Ensure SSH X11 forwarding is disabled (Scored)	
	5.2.7 Ensure SSH MaxAuthTries is set to 4 or less (Scored)	
	5.2.8 Ensure SSH IgnoreRhosts is enabled (Scored)	
	5.2.9 Ensure SSH HostbasedAuthentication is disabled (Scored)	
	5.2.10 Ensure SSH root login is disabled (Scored)	
	5.2.11 Ensure SSH PermitEmptyPasswords is disabled (Scored)	
	5.2.12 Ensure SSH PermitUserEnvironment is disabled (Scored)	
	5.2.13 Ensure only strong Ciphers are used (Scored)	
	5.2.14 Ensure only strong MAC algorithms are used (Scored)	.426
	5.2.15 Ensure only strong Key Exchange algorithms are used (Scored)	
	5.2.16 Ensure SSH Idle Timeout Interval is configured (Scored)	
	5.2.17 Ensure SSH LoginGraceTime is set to one minute or less (Scored)	.435
	5.2.18 Ensure SSH access is limited (Scored)	
	5.2.19 Ensure SSH warning banner is configured (Scored)	
	5.2.20 Ensure SSH PAM is enabled (Scored)	
	5.2.21 Ensure SSH AllowTcpForwarding is disabled (Scored)	

5.2.22 Ensure SSH MaxStartups is configured (Scored)	446
5.2.23 Ensure SSH MaxSessions is set to 4 or less (Scored)	448
5.3 Configure PAM	450
5.3.1 Ensure password creation requirements are configured (Scored)	451
5.3.2 Ensure lockout for failed password attempts is configured (Not Score	d)454
5.3.3 Ensure password reuse is limited (Not Scored)	456
5.3.4 Ensure password hashing algorithm is SHA-512 (Not Scored)	458
5.4 User Accounts and Environment	460
5.4.1 Set Shadow Password Suite Parameters	461
5.4.1.1 Ensure password expiration is 365 days or less (Scored)	462
5.4.1.2 Ensure minimum days between password changes is 7 or more (Sco	-
5.4.1.3 Ensure password expiration warning days is 7 or more (Scored)	
5.4.1.4 Ensure inactive password lock is 30 days or less (Scored)	468
5.4.1.5 Ensure all users last password change date is in the past (Scored)	470
5.4.2 Ensure system accounts are secured (Scored)	471
5.4.3 Ensure default group for the root account is GID 0 (Scored)	473
5.4.4 Ensure default user umask is 027 or more restrictive (Scored)	474
5.4.5 Ensure default user shell timeout is 900 seconds or less (Scored)	476
5.5 Ensure root login is restricted to system console (Not Scored)	478
5.6 Ensure access to the su command is restricted (Scored)	479
6 System Maintenance	481
6.1 System File Permissions	482
6.1.1 Audit system file permissions (Not Scored)	483
6.1.2 Ensure permissions on /etc/passwd are configured (Scored)	486
6.1.3 Ensure permissions on /etc/shadow are configured (Scored)	487
6.1.4 Ensure permissions on /etc/group are configured (Scored)	489
6.1.5 Ensure permissions on /etc/gshadow are configured (Scored)	490
6.1.6 Ensure permissions on /etc/passwd- are configured (Scored)	492
6.1.7 Ensure permissions on /etc/shadow- are configured (Scored)	494
6.1.8 Ensure permissions on /etc/group- are configured (Scored)	496

6.1.9 Ensure permissions on /etc/gshadow- are configured (Scored)	497
6.1.10 Ensure no world writable files exist (Scored)	499
6.1.11 Ensure no unowned files or directories exist (Scored)	501
6.1.12 Ensure no ungrouped files or directories exist (Scored)	503
6.1.13 Audit SUID executables (Not Scored)	505
6.1.14 Audit SGID executables (Not Scored)	507
6.2 User and Group Settings	509
6.2.1 Ensure password fields are not empty (Scored)	510
6.2.2 Ensure no legacy "+" entries exist in /etc/passwd (Scored)	511
6.2.3 Ensure no legacy "+" entries exist in /etc/shadow (Scored)	512
6.2.4 Ensure no legacy "+" entries exist in /etc/group (Scored)	513
6.2.5 Ensure root is the only UID 0 account (Scored)	514
6.2.6 Ensure root PATH Integrity (Scored)	515
6.2.7 Ensure all users' home directories exist (Scored)	518
6.2.8 Ensure users' home directories permissions are 750 or more restrictive (Scored)	
6.2.9 Ensure users own their home directories (Scored)	522
6.2.10 Ensure users' dot files are not group or world writable (Scored)	524
6.2.11 Ensure no users have .forward files (Scored)	526
6.2.12 Ensure no users have .netrc files (Scored)	528
6.2.13 Ensure users' .netrc Files are not group or world accessible (Scored)	530
6.2.14 Ensure no users have .rhosts files (Scored)	533
6.2.15 Ensure all groups in /etc/passwd exist in /etc/group (Scored)	535
6.2.16 Ensure no duplicate UIDs exist (Scored)	537
6.2.17 Ensure no duplicate GIDs exist (Scored)	539
6.2.18 Ensure no duplicate user names exist (Scored)	541
6.2.19 Ensure no duplicate group names exist (Scored)	543
6.2.20 Ensure shadow group is empty (Scored)	545
Appendix: Summary Table	547
Appendix: Change History	556

Overview

This document provides prescriptive guidance for establishing a secure configuration posture for Linux systems running on x86 and x64 platforms.

Commands and scripts are provided which should work on most distributions however some translation to local styles may be required in places. Where possible Red Hat, Debian, and SUSE derivative styles are provided.

Many lists are included including filesystem types, services, clients, and network protocols. Not all items in these lists are guaranteed to exist on all distributions and additional similar items may exist which should be considered in addition to those explicitly mentioned. The guidance within broadly assumes that operations are being performed as the root user. Operations performed using sudo instead of the root user may produce unexpected results, or fail to make the intended changes to the system. Non-root users may not be able to access certain areas of the system, especially after remediation has been performed. It is advisable to verify root users path integrity and the integrity of any programs being run prior to execution of commands and scripts included in this benchmark.

To obtain the latest version of this guide, please visit http://workbench.cisecurity.org. If you have questions, comments, or have identified ways to improve this guide, please write us at feedback@cisecurity.org.

Intended Audience

This benchmark is intended for system and application administrators, security specialists, auditors, help desk, and platform deployment personnel who plan to develop, deploy, assess, or secure solutions that incorporate Linux on x86 or x64 platform.

Consensus Guidance

This benchmark was created using a consensus review process comprised of subject matter experts. Consensus participants provide perspective from a diverse set of backgrounds including consulting, software development, audit and compliance, security research, operations, government, and legal.

Each CIS benchmark undergoes two phases of consensus review. The first phase occurs during initial benchmark development. During this phase, subject matter experts convene to discuss, create, and test working drafts of the benchmark. This discussion occurs until consensus has been reached on benchmark recommendations. The second phase begins

after the benchmark has been published. During this phase, all feedback provided by the Internet community is reviewed by the consensus team for incorporation in the benchmark. If you are interested in participating in the consensus process, please visit https://workbench.cisecurity.org/.

Typographical Conventions

The following typographical conventions are used throughout this guide:

Convention	Meaning
Stylized Monospace font	Used for blocks of code, command, and script examples. Text should be interpreted exactly as presented.
Monospace font	Used for inline code, commands, or examples. Text should be interpreted exactly as presented.
<italic brackets="" font="" in=""></italic>	Italic texts set in angle brackets denote a variable requiring substitution for a real value.
Italic font	Used to denote the title of a book, article, or other publication.
Note	Additional information or caveats

Scoring Information

A scoring status indicates whether compliance with the given recommendation impacts the assessed target's benchmark score. The following scoring statuses are used in this benchmark:

Scored

Failure to comply with "Scored" recommendations will decrease the final benchmark score. Compliance with "Scored" recommendations will increase the final benchmark score.

Not Scored

Failure to comply with "Not Scored" recommendations will not decrease the final benchmark score. Compliance with "Not Scored" recommendations will not increase the final benchmark score.

Profile Definitions

The following configuration profiles are defined by this Benchmark:

• Level 1 - Server

Items in this profile intend to:

- be practical and prudent;
- o provide a clear security benefit; and
- o not inhibit the utility of the technology beyond acceptable means.

This profile is intended for servers.

• Level 2 - Server

This profile extends the "Level 1 - Server" profile. Items in this profile exhibit one or more of the following characteristics:

- o are intended for environments or use cases where security is paramount.
- o acts as defense in depth measure.
- o may negatively inhibit the utility or performance of the technology.

This profile is intended for servers.

• Level 1 - Workstation

Items in this profile intend to:

- be practical and prudent;
- o provide a clear security benefit; and
- o not inhibit the utility of the technology beyond acceptable means.

This profile is intended for workstations.

• Level 2 - Workstation

This profile extends the "Level 1 - Workstation" profile. Items in this profile exhibit one or more of the following characteristics:

- o are intended for environments or use cases where security is paramount.
- o acts as defense in depth measure.
- o may negatively inhibit the utility or performance of the technology.

This profile is intended for workstations.

Acknowledgements

This benchmark exemplifies the great things a community of users, vendors, and subject matter experts can accomplish through consensus collaboration. The CIS community thanks the entire consensus team with special recognition to the following individuals who contributed greatly to the creation of this guide:

This benchmark is based upon previous Linux benchmarks published and would not be possible without the contributions provided over the history of all of these benchmarks. The CIS community thanks everyone who has contributed to the Linux benchmarks.

Contributor

Rael Daruszka

Ron Colvin, Ron Colvin

Bill Erickson

Dave Billing

Dominic Pace

Elliot Anderson

Ely Pinto

Fredrik Silverskär

Jov Latten

Kirill Antonenko

Koen Laevens

Marcelo Cerri

Mark Birch

Martynas Brijunas

Michel Verbraak

Mike Thompson

Pradeep R B

Rakesh Jain Sr

Robert Thomas

Tom Pietschmann

Vineetha Hari Pai

William E. Triest III

Anurag Pal

Bradley Hieber

Thomas Sjögren

James Trigg

Matthew Woods

Kenneth Karlsson

Editor

Jonathan Lewis Christopherson Eric Pinnell, Center for Internet Security

Recommendations

1 Initial Setup

Items in this section are advised for all systems, but may be difficult or require extensive preparation after the initial setup of the system.

1.1 Filesystem Configuration

Directories that are used for system-wide functions can be further protected by placing them on separate partitions. This provides protection for resource exhaustion and enables the use of mounting options that are applicable to the directory's intended use. Users' data can be stored on separate partitions and have stricter mount options. A user partition is a filesystem that has been established for use by the users and does not contain software for system operations.

The recommendations in this section are easier to perform during initial system installation. If the system is already installed, it is recommended that a full backup be performed before repartitioning the system.

Note: If you are repartitioning a system that has already been installed, make sure the data has been copied over to the new partition, unmount it and then remove the data from the directory that was in the old partition. Otherwise it will still consume space in the old partition that will be masked when the new filesystem is mounted. For example, if a system is in single-user mode with no filesystems mounted and the administrator adds a lot of data to the /tmp directory, this data will still consume space in / once the /tmp filesystem is mounted unless it is removed first.

1.1.1 Disable unused filesystems

A number of uncommon filesystem types are supported under Linux. Removing support for unneeded filesystem types reduces the local attack surface of the system. If a filesystem type is not needed it should be disabled. Native Linux file systems are designed to ensure that built-in security controls function as expected. Non-native filesystems can lead to unexpected consequences to both the security and functionality of the system and should be used with caution. Many filesystems are created for niche use cases and are not maintained and supported as the operating systems are updated and patched. Users of non-native filesystems should ensure that there is attention and ongoing support for them, especially in light of frequent operating system changes.

Standard network connectivity and Internet access to cloud storage may make the use of non-standard filesystem formats to directly attach heterogeneous devices much less attractive.

Note: This should not be considered a comprehensive list of filesystems. You may wish to consider additions to those listed here for your environment.

1.1.1.1 Ensure mounting of cramfs filesystems is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The cramfs filesystem type is a compressed read-only Linux filesystem embedded in small footprint systems. A cramfs image can be used without having to first decompress the image.

Rationale:

Removing support for unneeded filesystem types reduces the local attack surface of the server. If this filesystem type is not needed, disable it.

Audit:

```
# modprobe -n -v cramfs
install /bin/true
# lsmod | grep cramfs
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/cramfs.conf and add the following line:

install cramfs /bin/true

Run the following command to unload the cramfs module:

rmmod cramfs

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.1.2 Ensure mounting of freevxfs filesystems is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The freevxfs filesystem type is a free version of the Veritas type filesystem. This is the primary filesystem type for HP-UX operating systems.

Rationale:

Removing support for unneeded filesystem types reduces the local attack surface of the system. If this filesystem type is not needed, disable it.

Audit:

```
# modprobe -n -v freevxfs
install /bin/true
# lsmod | grep freevxfs
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/freevxfs.conf and add the following line:

install freevxfs /bin/true

Run the following command to unload the freevxfs module:

rmmod freevxfs

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.1.3 Ensure mounting of jffs2 filesystems is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The jffs2 (journaling flash filesystem 2) filesystem type is a log-structured filesystem used in flash memory devices.

Rationale:

Removing support for unneeded filesystem types reduces the local attack surface of the system. If this filesystem type is not needed, disable it.

Audit:

```
# modprobe -n -v jffs2
install /bin/true
# lsmod | grep jffs2
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/jffs2.conf and add the following line:

install jffs2 /bin/true

Run the following command to unload the jffs2 module:

rmmod jffs2

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.1.4 Ensure mounting of hfs filesystems is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The ${\tt hfs}$ filesystem type is a hierarchical filesystem that allows you to mount Mac OS filesystems.

Rationale:

Removing support for unneeded filesystem types reduces the local attack surface of the system. If this filesystem type is not needed, disable it.

Audit:

```
# modprobe -n -v hfs
install /bin/true
# lsmod | grep hfs
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/hfs.conf and add the following line:

install hfs /bin/true

Run the following command to unload the hfs module:

rmmod hfs

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.1.5 Ensure mounting of hfsplus filesystems is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The hfsplus filesystem type is a hierarchical filesystem designed to replace hfs that allows you to mount Mac OS filesystems.

Rationale:

Removing support for unneeded filesystem types reduces the local attack surface of the system. If this filesystem type is not needed, disable it.

Audit:

```
# modprobe -n -v hfsplus
install /bin/true
# lsmod | grep hfsplus
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/hfsplus.conf and add the following line:

install hfsplus /bin/true

Run the following command to unload the hfsplus module:

rmmod hfsplus

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.1.6 Ensure mounting of squashfs filesystems is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The squashfs filesystem type is a compressed read-only Linux filesystem embedded in small footprint systems (similar to cramfs). A squashfs image can be used without having to first decompress the image.

Rationale:

Removing support for unneeded filesystem types reduces the local attack surface of the system. If this filesystem type is not needed, disable it.

Audit:

```
# modprobe -n -v squashfs
install /bin/true
# lsmod | grep squashfs
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/squashfs.conf and add the following line:

install squashfs /bin/true

Run the following command to unload the squashfs module:

rmmod squashfs

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.1.7 Ensure mounting of udf filesystems is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The udf filesystem type is the universal disk format used to implement ISO/IEC 13346 and ECMA-167 specifications. This is an open vendor filesystem type for data storage on a broad range of media. This filesystem type is necessary to support writing DVDs and newer optical disc formats.

Rationale:

Removing support for unneeded filesystem types reduces the local attack surface of the system. If this filesystem type is not needed, disable it.

Audit:

```
# modprobe -n -v udf
install /bin/true
# lsmod | grep udf
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/udf.conf and add the following line:

install udf /bin/true

Run the following command to unload the udf module:

rmmod udf

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.1.8 Ensure mounting of FAT filesystems is limited (Not Scored)

Profile Applicability:

- Level 2 Workstation
- Level 2 Server

Description:

The FAT filesystem format is primarily used on older windows systems and portable USB drives or flash modules. It comes in three types FAT12, FAT16, and FAT32 all of which are supported by the vfat kernel module.

Rationale:

Removing support for unneeded filesystem types reduces the local attack surface of the system. If this filesystem type is not needed, disable it.

Audit:

If utilizing UEFI the FAT filesystem format is required. If this case, ensure that the FAT filesystem is only used where appropriate Run the following command

```
grep -i vfat /etc/fstab
```

And review that any output is approprate for your environment If not utilizing UEFI
Run the following commands and verify the output is as indicated:

modprobe -n -v vfat
install /bin/true
lsmod | grep vfat
<No output>

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/vfat.conf

install vfat /bin/true

Run the following command to unload the vfat module:

rmmod vfat

Impact:

The FAT filesystem format is used by UEFI systems for the EFI boot partition. Disabling the vfat module can prevent boot on UEFI systems.

FAT filesystems are often used on portable USB sticks and other flash media which are commonly used to transfer files between workstations, removing VFAT support may prevent the ability to transfer files in this way.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.2 Ensure /tmp is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The / tmp directory is a world-writable directory used for temporary storage by all users and some applications.

Rationale:

Making /tmp its own file system allows an administrator to set the noexec option on the mount, making /tmp useless for an attacker to install executable code. It would also prevent an attacker from establishing a hardlink to a system setuid program and wait for it to be updated. Once the program was updated, the hardlink would be broken and the attacker would have his own copy of the program. If the program happened to have a security vulnerability, the attacker could continue to exploit the known flaw.

This can be accomplished by either mounting tmpfs to /tmp, or creating a separate partition for /tmp.

Audit:

Run the following command and verify output shows /tmp is mounted:

```
# mount | grep -E '\s/tmp\s'
tmpfs on /tmp type tmpfs (rw,nosuid,nodev,noexec,relatime)
```

Run the following command and verify that tmpfs has been mounted to, or a system partition has been created for / tmp

```
# grep -E '\s/tmp\s' /etc/fstab | grep -E -v '^\s*#'
tmpfs /tmp tmpfs defaults,noexec,nosuid,nodev 0 0
```

OR

```
# systemctl is-enabled tmp.mount
enabled
```

Configure /etc/fstab as appropriate.

```
example:
tmpfs /tmp tmpfs defaults,rw,nosuid,nodev,noexec,relatime 0 0
```

OR

Run the following commands to enable systemd /tmp mounting:

```
systemctl unmask tmp.mount systemctl enable tmp.mount
```

Edit /etc/systemd/system/local-fs.target.wants/tmp.mount to configure the /tmp
mount:

```
[Mount]
What=tmpfs
Where=/tmp
Type=tmpfs
Options=mode=1777,strictatime,noexec,nodev,nosuid
```

Impact:

Since the / tmp directory is intended to be world-writable, there is a risk of resource exhaustion if it is not bound to a separate partition.

Running out of /tmp space is a problem regardless of what kind of filesystem lies under it, but in a default installation a disk-based /tmp will essentially have the whole disk available, as it only creates a single / partition. On the other hand, a RAM-based /tmp as with tmpfs will almost certainly be much smaller, which can lead to applications filling up the filesystem much more easily.

/tmp utalizing tmpfs can be resized using the size={size} parameter on the Options line on the tmp.mount file

References:

- 1. AJ Lewis, "LVM HOWTO", http://tldp.org/HOWTO/LVM-HOWTO/
- 2. https://www.freedesktop.org/wiki/Software/systemd/APIFileSystems/

Notes:

If an entry for /tmp exists in /etc/fstab it will take precedence over entries in the tmp.mount file

CIS Controls:

Version 7

5.1 Establish Secure Configurations

1.1.3 Ensure nodev option set on /tmp partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The nodev mount option specifies that the filesystem cannot contain special devices.

Rationale:

Since the / tmp filesystem is not intended to support devices, set this option to ensure that users cannot attempt to create block or character special devices in / tmp.

Audit:

Verify that the nodev option is set if a /tmp partition exists Run the following command and verify that nothing is returned:

mount | grep -E '\s/tmp\s' | grep -v nodev

Edit the /etc/fstab file and add nodev to the fourth field (mounting options) for the /tmp partition. See the fstab (5) manual page for more information.

Run the following command to remount /tmp:

```
# mount -o remount, nodev /tmp
```

or

Edit /etc/systemd/system/local-fs.target.wants/tmp.mount to add nodev to the /tmp mount options:

[Mount]

Options=mode=1777, strictatime, noexec, nodev, nosuid

Run the following command to remount /tmp:

mount -o remount, nodev /tmp

CIS Controls:

Version 6

13 Data Protection

Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.4 Ensure nosuid option set on /tmp partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The nosuid mount option specifies that the filesystem cannot contain setuid files.

Rationale:

Since the / tmp filesystem is only intended for temporary file storage, set this option to ensure that users cannot create setuid files in / tmp.

Audit:

Verify that the nosuid option is set if a /tmp partition exists Run the following command and verify that nothing is returned:

mount | grep -E '\s/tmp\s' | grep -v nosuid

Edit the /etc/fstab file and add nosuid to the fourth field (mounting options) for the /tmp partition. See the fstab (5) manual page for more information.

Run the following command to remount /tmp:

```
# mount -o remount, nosuid /tmp
```

or

Edit /etc/systemd/system/local-fs.target.wants/tmp.mount to add nosuid to the /tmp mount options:

[Mount]

Options=mode=1777, strictatime, noexec, nodev, nosuid

Run the following command to remount /tmp:

mount -o remount, nosuid /tmp

CIS Controls:

Version 6

13 Data Protection

Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.5 Ensure noexec option set on /tmp partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The noexec mount option specifies that the filesystem cannot contain executable binaries.

Rationale:

Since the / tmp filesystem is only intended for temporary file storage, set this option to ensure that users cannot run executable binaries from / tmp.

Audit:

Verify that the noexec option is set if a /tmp partition exists Run the following command and verify that nothing is returned:

mount | grep -E '\s/tmp\s' | grep -v noexec

Edit the /etc/fstab file and add noexec to the fourth field (mounting options) for the /tmp partition. See the fstab (5) manual page for more information.

Run the following command to remount / tmp:

```
# mount -o remount, noexec /tmp
```

or

Edit /etc/systemd/system/local-fs.target.wants/tmp.mount to add noexec to the /tmp mount options:

[Mount]

Options=mode=1777, strictatime, noexec, nodev, nosuid

Run the following command to remount /tmp:

```
# mount -o remount, noexec /tmp
```

CIS Controls:

Version 6

2 <u>Inventory of Authorized and Unauthorized Software</u> Inventory of Authorized and Unauthorized Software

Version 7

2.6 Address unapproved software

Ensure that unauthorized software is either removed or the inventory is updated in a timely manner

1.1.6 Ensure separate partition exists for /var (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The /var directory is used by daemons and other system services to temporarily store dynamic data. Some directories created by these processes may be world-writable.

Rationale:

Since the /var directory may contain world-writable files and directories, there is a risk of resource exhaustion if it is not bound to a separate partition.

Audit:

Run the following command and verify output shows /var is mounted:

```
# mount | grep -E '\s/var\s'
/dev/xvdg1 on /var type ext4 (rw,relatime,data=ordered)
```

For new installations, during installation create a custom partition setup and specify a separate partition for /var.

For systems that were previously installed, create a new partition and configure /etc/fstab as appropriate.

Impact:

Resizing filesystems is a common activity in cloud-hosted servers. Separate filesystem partitions may prevent successful resizing, or may require the installation of additional tools solely for the purpose of resizing operations. The use of these additional tools may introduce their own security considerations.

References:

1. AJ Lewis, "LVM HOWTO", http://tldp.org/HOWTO/LVM-HOWTO/

Notes:

When modifying /var it is advisable to bring the system to emergency mode (so auditd is not running), rename the existing directory, mount the new file system, and migrate the data over before returning to multiuser mode.

CIS Controls:

Version 6

13 <u>Data Protection</u>
Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.7 Ensure separate partition exists for /var/tmp (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The /var/tmp directory is a world-writable directory used for temporary storage by all users and some applications.

Rationale:

Since the /var/tmp directory is intended to be world-writable, there is a risk of resource exhaustion if it is not bound to a separate partition. In addition, making /var/tmp its own file system allows an administrator to set the noexec option on the mount, making /var/tmp useless for an attacker to install executable code. It would also prevent an attacker from establishing a hardlink to a system setuid program and wait for it to be updated. Once the program was updated, the hardlink would be broken and the attacker would have his own copy of the program. If the program happened to have a security vulnerability, the attacker could continue to exploit the known flaw.

Audit:

Run the following command and verify output shows /var/tmp is mounted:

```
# mount | grep /var/tmp
<device> on /var/tmp type ext4 (rw,nosuid,nodev,noexec,relatime)
```

For new installations, during installation create a custom partition setup and specify a separate partition for $\protect\pro$

For systems that were previously installed, create a new partition and configure /etc/fstab as appropriate.

Impact:

Resizing filesystems is a common activity in cloud-hosted servers. Separate filesystem partitions may prevent successful resizing, or may require the installation of additional tools solely for the purpose of resizing operations. The use of these additional tools may introduce their own security considerations.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.8 Ensure nodev option set on /var/tmp partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The nodev mount option specifies that the filesystem cannot contain special devices.

Rationale:

Since the /var/tmp filesystem is not intended to support devices, set this option to ensure that users cannot attempt to create block or character special devices in /var/tmp.

Audit:

Verify that the nodev option is set if a /var/tmp partition exists. Run the following command and verify that nothing is returned:

```
# mount | grep -E '\s/var/tmp\s' | grep -v nodev
```

Remediation:

Edit the /etc/fstab file and add nodev to the fourth field (mounting options) for the /var/tmp partition. See the fstab (5) manual page for more information. Run the following command to remount /var/tmp:

```
# mount -o remount, nodev /var/tmp
```

CIS Controls:

Version 6

13 Data Protection

Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.9 Ensure nosuid option set on /var/tmp partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The nosuid mount option specifies that the filesystem cannot contain setuid files.

Rationale:

Since the /var/tmp filesystem is only intended for temporary file storage, set this option to ensure that users cannot create setuid files in /var/tmp.

Audit:

Verify that the nosuid option is set if a /var/tmp partition exists. Run the following command and verify that nothing is returned:

```
# mount | grep -E '\s/var/tmp\s' | grep -v nosuid
```

Remediation:

Edit the /etc/fstab file and add nosuid to the fourth field (mounting options) for the /var/tmp partition. See the fstab (5) manual page for more information.

Run the following command to remount /var/tmp:

```
# mount -o remount, nosuid /var/tmp
```

CIS Controls:

Version 6

13 Data Protection

Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.10 Ensure noexec option set on /var/tmp partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The noexec mount option specifies that the filesystem cannot contain executable binaries.

Rationale:

Since the /var/tmp filesystem is only intended for temporary file storage, set this option to ensure that users cannot run executable binaries from /var/tmp.

Audit:

Verify that the noexec option is set if a /var/tmp partition exists. Run the following command and verify that nothing is returned:

```
# mount | grep -E '\s/var/tmp\s' | grep -v noexec
```

Remediation:

Edit the /etc/fstab file and add noexec to the fourth field (mounting options) for the /var/tmp partition. See the fstab (5) manual page for more information.

Run the following command to remount /var/tmp:

```
# mount -o remount, noexec /var/tmp
```

CIS Controls:

Version 6

2 <u>Inventory of Authorized and Unauthorized Software</u> Inventory of Authorized and Unauthorized Software

Version 7

2.6 Address unapproved software

Ensure that unauthorized software is either removed or the inventory is updated in a timely manner

1.1.11 Ensure separate partition exists for /var/log (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The /var/log directory is used by system services to store log data .

Rationale:

There are two important reasons to ensure that system logs are stored on a separate partition: protection against resource exhaustion (since logs can grow quite large) and protection of audit data.

Audit:

Run the following command and verify output shows /var/log is mounted:

```
# mount | grep /var/log
/dev/xvdh1 on /var/log type ext4 (rw,relatime,data=ordered)
```

For new installations, during installation create a custom partition setup and specify a separate partition for $\protect\ensuremath{\text{var/log}}$.

For systems that were previously installed, create a new partition and configure /etc/fstab as appropriate.

Impact:

Resizing filesystems is a common activity in cloud-hosted servers. Separate filesystem partitions may prevent successful resizing, or may require the installation of additional tools solely for the purpose of resizing operations. The use of these additional tools may introduce their own security considerations.

References:

1. AJ Lewis, "LVM HOWTO", http://tldp.org/HOWTO/LVM-HOWTO/

Notes:

When modifying /var/log it is advisable to bring the system to emergency mode (so auditd is not running), rename the existing directory, mount the new file system, and migrate the data over before returning to multiuser mode.

CIS Controls:

Version 6

6.3 Ensure Audit Logging Systems Are Not Subject To Loss (i.e. rotation/archive)
Ensure that all systems that store logs have adequate storage space for the logs
generated on a regular basis, so that log files will not fill up between log rotation intervals.
The logs must be archived and digitally signed on a periodic basis.

Version 7

6.4 Ensure adequate storage for logs

Ensure that all systems that store logs have adequate storage space for the logs generated.

1.1.12 Ensure separate partition exists for /var/log/audit (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The auditing daemon, auditd, stores log data in the /var/log/audit directory.

Rationale:

There are two important reasons to ensure that data gathered by \mathtt{auditd} is stored on a separate partition: protection against resource exhaustion (since the $\mathtt{audit.log}$ file can grow quite large) and protection of audit data. The audit daemon calculates how much free space is left and performs actions based on the results. If other processes (such as \mathtt{syslog}) consume space in the same partition as \mathtt{auditd} , it may not perform as desired.

Audit:

Run the following command and verify output shows /var/log/audit is mounted:

mount | grep /var/log/audit
/dev/xvdi1 on /var/log/audit type ext4 (rw,relatime,data=ordered)

For new installations, during installation create a custom partition setup and specify a separate partition for /var/log/audit.

For systems that were previously installed, create a new partition and configure /etc/fstab as appropriate.

Impact:

Resizing filesystems is a common activity in cloud-hosted servers. Separate filesystem partitions may prevent successful resizing, or may require the installation of additional tools solely for the purpose of resizing operations. The use of these additional tools may introduce their own security considerations.

References:

1. AJ Lewis, "LVM HOWTO", http://tldp.org/HOWTO/LVM-HOWTO/

Notes:

When modifying /var/log/audit it is advisable to bring the system to emergency mode (so auditd is not running), rename the existing directory, mount the new file system, and migrate the data over before returning to multiuser mode.

CIS Controls:

Version 6

6.3 Ensure Audit Logging Systems Are Not Subject To Loss (i.e. rotation/archive)
Ensure that all systems that store logs have adequate storage space for the logs
generated on a regular basis, so that log files will not fill up between log rotation intervals.
The logs must be archived and digitally signed on a periodic basis.

Version 7

6.4 Ensure adequate storage for logs

Ensure that all systems that store logs have adequate storage space for the logs generated.

1.1.13 Ensure separate partition exists for /home (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The /home directory is used to support disk storage needs of local users.

Rationale:

If the system is intended to support local users, create a separate partition for the / home directory to protect against resource exhaustion and restrict the type of files that can be stored under / home.

Audit:

Run the following command and verify output shows $/ {\tt home}$ is mounted:

mount | grep /home
/dev/xvdf1 on /home type ext4 (rw,nodev,relatime,data=ordered)

For new installations, during installation create a custom partition setup and specify a separate partition for / home.

For systems that were previously installed, create a new partition and configure /etc/fstab as appropriate.

Impact:

Resizing filesystems is a common activity in cloud-hosted servers. Separate filesystem partitions may prevent successful resizing, or may require the installation of additional tools solely for the purpose of resizing operations. The use of these additional tools may introduce their own security considerations.

References:

1. AJ Lewis, "LVM HOWTO", http://tldp.org/HOWTO/LVM-HOWTO/

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.14 Ensure nodev option set on /home partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The nodev mount option specifies that the filesystem cannot contain special devices.

Rationale:

Since the user partitions are not intended to support devices, set this option to ensure that users cannot attempt to create block or character special devices.

Audit:

Verify that the nodev option is set if a /home partition exists. Run the following command and verify that nothing is returned:

mount | grep -E '\s/home\s' | grep -v nodev

Edit the /etc/fstab file and add nodev to the fourth field (mounting options) for the /home partition. See the fstab (5) manual page for more information.

mount -o remount, nodev /home

Notes:

The actions in this recommendation refer to the <code>/homepartition</code>, which is the default user partition that is defined in many distributions. If you have created other user partitions, it is recommended that the Remediation and Audit steps be applied to these partitions as well.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 <u>Establish Secure Configurations</u>

1.1.15 Ensure nodev option set on /dev/shm partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The nodev mount option specifies that the filesystem cannot contain special devices.

Rationale:

Since the /dev/shm filesystem is not intended to support devices, set this option to ensure that users cannot attempt to create special devices in /dev/shm partitions.

Audit:

Verify that the nodev option is set if a /dev/shm partition exists. Run the following command and verify that nothing is returned:

mount | grep -E '\s/dev/shm\s' | grep -v nodev

Edit the /etc/fstab file and add nodev to the fourth field (mounting options) for the /dev/shm partition. See the fstab(5) manual page for more information. Run the following command to remount /dev/shm:

mount -o remount, nodev /dev/shm

Notes:

Some distributions mount /dev/shm through other means and require /dev/shm to be added to /etc/fstab even though it is already being mounted on boot. Others may configure /dev/shm in other locations and may override /etc/fstab configuration. Consult the documentation appropriate for your distribution.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.16 Ensure nosuid option set on /dev/shm partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The nosuid mount option specifies that the filesystem cannot contain setuid files.

Rationale:

Setting this option on a file system prevents users from introducing privileged programs onto the system and allowing non-root users to execute them.

Audit:

Verify that the nosuid option is set if a /dev/shm partition exists. Run the following command and verify that nothing is returned:

mount | grep -E '\s/dev/shm\s' | grep -v nosuid

Edit the /etc/fstab file and add nosuid to the fourth field (mounting options) for the /dev/shm partition. See the fstab(5) manual page for more information. Run the following command to remount /dev/shm:

mount -o remount, nosuid /dev/shm

Notes:

Some distributions mount /dev/shm through other means and require /dev/shm to be added to /etc/fstab even though it is already being mounted on boot. Others may configure /dev/shm in other locations and may override /etc/fstab configuration. Consult the documentation appropriate for your distribution.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.17 Ensure noexec option set on /dev/shm partition (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The noexec mount option specifies that the filesystem cannot contain executable binaries.

Rationale:

Setting this option on a file system prevents users from executing programs from shared memory. This deters users from introducing potentially malicious software on the system.

Audit:

Verify that the noexec option is set if a /dev/shm partition exists. Run the following command and verify that nothing is returned:

mount | grep -E '\s/dev/shm\s' | grep -v noexec

Edit the /etc/fstab file and add noexec to the fourth field (mounting options) for the /dev/shm partition. See the fstab(5) manual page for more information. Run the following command to remount /dev/shm:

mount -o remount, noexec /dev/shm

Notes:

Some distributions mount /dev/shm through other means and require /dev/shm to be added to /etc/fstab even though it is already being mounted on boot. Others may configure /dev/shm in other locations and may override /etc/fstab configuration. Consult the documentation appropriate for your distribution.

CIS Controls:

Version 6

2 <u>Inventory of Authorized and Unauthorized Software</u> Inventory of Authorized and Unauthorized Software

Version 7

2.6 Address unapproved software

Ensure that unauthorized software is either removed or the inventory is updated in a timely manner

1.1.18 Ensure nodev option set on removable media partitions (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The nodev mount option specifies that the filesystem cannot contain special devices.

Rationale:

Removable media containing character and block special devices could be used to circumvent security controls by allowing non-root users to access sensitive device files such as /dev/kmem or the raw disk partitions.

Audit:

Run the following command and verify that the nodev option is set on all removable media partitions.

mount

Remediation:

Edit the /etc/fstab file and add nodev to the fourth field (mounting options) of all removable media partitions. Look for entries that have mount points that contain words such as floppy or cdrom. See the fstab(5) manual page for more information.

CIS Controls:

Version 6

13 <u>Data Protection</u>
Data Protection

Data i i ottettioi

Version 7

5.1 Establish Secure Configurations

1.1.19 Ensure nosuid option set on removable media partitions (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The nosuid mount option specifies that the filesystem cannot contain setuid files.

Rationale:

Setting this option on a file system prevents users from introducing privileged programs onto the system and allowing non-root users to execute them.

Audit:

Run the following command and verify that the nosuid option is set on all removable media partitions.

mount

Remediation:

Edit the /etc/fstab file and add nosuid to the fourth field (mounting options) of all removable media partitions. Look for entries that have mount points that contain words such as floppy or cdrom. See the fstab(5) manual page for more information.

CIS Controls:

Version 6

13 <u>Data Protection</u>

Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.20 Ensure noexec option set on removable media partitions (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The noexec mount option specifies that the filesystem cannot contain executable binaries.

Rationale:

Setting this option on a file system prevents users from executing programs from the removable media. This deters users from being able to introduce potentially malicious software on the system.

Audit:

Run the following command and verify that the noexec option is set on all removable media partitions.

mount

Remediation:

Edit the /etc/fstab file and add noexec to the fourth field (mounting options) of all removable media partitions. Look for entries that have mount points that contain words such as floppy or cdrom. See the fstab(5) manual page for more information.

CIS Controls:

Version 6

8 <u>Malware Defenses</u> Malware Defenses

Version 7

2.6 Address unapproved software

Ensure that unauthorized software is either removed or the inventory is updated in a timely manner

1.1.21 Ensure sticky bit is set on all world-writable directories (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Setting the sticky bit on world writable directories prevents users from deleting or renaming files in that directory that are not owned by them.

Rationale:

This feature prevents the ability to delete or rename files in world writable directories (such as /tmp) that are owned by another user.

Audit:

Run the following command to verify no world writable directories exist without the sticky bit set:

```
# df --local -P | awk '{if (NR!=1) print $6}' | xargs -I '{}' find '{}' -xdev -type d \( -perm -0002 -a ! -perm -1000 \) 2>/dev/null
```

No output should be returned.

Run the following command to set the sticky bit on all world writable directories:

```
# df --local -P | awk '{if (NR!=1) print $6}' | xargs -I '{}' find '{}' -xdev
-type d \( -perm -0002 -a ! -perm -1000 \) 2>/dev/null | xargs -I '{}' chmod
a+t '{}'
```

Notes:

Some distributions may not support the --local option to df.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.1.22 Disable Automounting (Scored)

Profile Applicability:

- Level 1 Server
- Level 2 Workstation

Description:

autofs allows automatic mounting of devices, typically including CD/DVDs and USB drives.

Rationale:

With automounting enabled anyone with physical access could attach a USB drive or disc and have its contents available in system even if they lacked permissions to mount it themselves.

Audit:

Run one of the following commands to verify autofs is not enabled:

```
# chkconfig --list autofs
autofs 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or autofs is not available.

```
# systemctl is-enabled autofs
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep autofs
```

Verify no S* lines are returned.

Remediation:

Run one of the following commands to disable autofs:

```
# chkconfig autofs off

# systemctl disable autofs

# update-rc.d autofs disable
```

Impact:

The use of portable hard drives is very common for workstation users. If your organization allows the use of portable storage or media on workstations and physical access controls to workstations is considered adequate there is little value add in turning off automounting.

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

This control should align with the tolerance of the use of portable drives and optical media in the organization. On a server requiring an admin to manually mount media can be part of defense-in-depth to reduce the risk of unapproved software or information being introduced or proprietary software or information being exfiltrated. If admins commonly use flash drives and Server access has sufficient physical controls, requiring manual mounting may not increase security.

CIS Controls:

Version 6

8.3 Limit Use Of External Devices (i.e. USB)

Limit use of external devices to those with an approved, documented business need. Monitor for use and attempted use of external devices. Configure laptops, workstations, and servers so that they will not auto-run content from removable media, like USB tokens (i.e., "thumb drives"), USB hard drives, CDs/DVDs, FireWire devices, external serial advanced technology attachment devices, and mounted network shares. Configure systems so that they automatically conduct an anti-malware scan of removable media when inserted.

Version 7

8.4 <u>Configure Anti-Malware Scanning of Removable Devices</u>

Configure devices so that they automatically conduct an anti-malware scan of removable media when inserted or connected.

8.5 Configure Devices Not To Auto-run Content

Configure devices to not auto-run content from removable media.

1.1.23 Disable USB Storage (Scored)

Profile Applicability:

- Level 1 Server
- Level 2 Workstation

Description:

USB storage provides a means to transfer and store files insuring persistence and availability of the files independent of network connection status. Its popularity and utility has led to USB-based malware being a simple and common means for network infiltration and a first step to establishing a persistent threat within a networked environment.

Rationale:

Restricting USB access on the system will decrease the physical attack surface for a device and diminish the possible vectors to introduce malware.

Audit:

Run the following commands and verify the output is as indicated:

```
# modprobe -n -v usb-storage
install /bin/true
# lsmod | grep usb-storage
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/usb-storage.conf and add the following line:

install usb-storage /bin/true

Run the following command to unload the usb-storage module:

rmmod usb-storage

CIS Controls:

Version 6

8.3 Limit Use Of External Devices (i.e. USB)

Limit use of external devices to those with an approved, documented business need. Monitor for use and attempted use of external devices. Configure laptops, workstations, and servers so that they will not auto-run content from removable media, like USB tokens (i.e., "thumb drives"), USB hard drives, CDs/DVDs, FireWire devices, external serial advanced technology attachment devices, and mounted network shares. Configure systems so that they automatically conduct an anti-malware scan of removable media when inserted.

Version 7

8.4 Configure Anti-Malware Scanning of Removable Devices

Configure devices so that they automatically conduct an anti-malware scan of removable media when inserted or connected.

8.5 Configure Devices Not To Auto-run Content

Configure devices to not auto-run content from removable media.

1.2 Configure Software Updates

Most distributions use a package manager such as yum, apt, or zypper to install and update software packages. Patch management procedures may vary widely between enterprises. Large enterprises may choose to install a local updates server that can be used in place of their distributions servers, whereas a single deployment of a system may prefer to get updates directly. Updates can be performed automatically or manually, depending on the site's policy for patch management. Many large enterprises prefer to test patches on a non-production system before rolling out to production.

For the purpose of this benchmark, the requirement is to ensure that a patch management system is configured and maintained. The specifics on patch update procedures are left to the organization.

1.2.1 Ensure package manager repositories are configured (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Systems need to have package manager repositories configured to ensure they receive the latest patches and updates.

Rationale:

If a system's package repositories are misconfigured important patches may not be identified or a rogue repository could introduce compromised software.

Audit:

Verify package repositories are configured correctly. Depending on the package management in use one of the following command groups may provide the needed information:

```
# yum repo-list

# apt-cache policy

# zypper repos
```

Configure your package manager repositories according to site policy.

CIS Controls:

Version 6

4.5 <u>Use Automated Patch Management And Software Update Tools</u>

Deploy automated patch management tools and software update tools for operating system and software/applications on all systems for which such tools are available and safe. Patches should be applied to all systems, even systems that are properly air gapped.

Version 7

3.4 <u>Deploy Automated Operating System Patch Management Tools</u>

Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.

3.5 <u>Deploy Automated Software Patch Management Tools</u>

Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.

1.2.2 Ensure GPG keys are configured (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Most packages managers implement GPG key signing to verify package integrity during installation.

Rationale:

It is important to ensure that updates are obtained from a valid source to protect against spoofing that could lead to the inadvertent installation of malware on the system.

Audit:

Verify GPG keys are configured correctly for your package manager. Depending on the package management in use one of the following command groups may provide the needed information:

```
# rpm -q gpg-pubkey --qf '%{name}-%{version}-%{release} --> %{summary}\n'
# apt-key list
# zypper repos
```

Update your package manager GPG keys in accordance with site policy.

CIS Controls:

Version 6

4.5 <u>Use Automated Patch Management And Software Update Tools</u>

Deploy automated patch management tools and software update tools for operating system and software/applications on all systems for which such tools are available and safe. Patches should be applied to all systems, even systems that are properly air gapped.

Version 7

3.4 <u>Deploy Automated Operating System Patch Management Tools</u>

Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.

3.5 <u>Deploy Automated Software Patch Management Tools</u>

Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.

1.3 Filesystem Integrity Checking

AIDE is a file integrity checking tool, similar in nature to Tripwire. While it cannot prevent intrusions, it can detect unauthorized changes to configuration files by alerting when the files are changed. When setting up AIDE, decide internally what the site policy will be concerning integrity checking. Review the AIDE quick start guide and AIDE documentation before proceeding.

1.3.1 Ensure AIDE is installed (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

AIDE takes a snapshot of filesystem state including modification times, permissions, and file hashes which can then be used to compare against the current state of the filesystem to detect modifications to the system.

Rationale:

By monitoring the filesystem state compromised files can be detected to prevent or limit the exposure of accidental or malicious misconfigurations or modified binaries.

Audit:

Verify AIDE is installed. Depending on the package management in use one of the following commands may provide the needed information:

```
# rpm -q aide
# dpkg -s aide
```

Install AIDE using the appropriate package manager or manual installation:

```
# yum install aide
# dnf install aide
# apt-get install aide
# zypper install aide
# emerge aide
```

Configure AIDE as appropriate for your environment. Consult the AIDE documentation for options.

Initialize AIDE:

```
# aide --init
```

References:

1. AIDE stable manual: http://aide.sourceforge.net/stable/manual.html

Notes:

The prelinking feature can interfere with AIDE because it alters binaries to speed up their start up times. Run prelink -ua to restore the binaries to their prelinked state, thus avoiding false positives from AIDE.

CIS Controls:

Version 6

3.5 <u>Use File Integrity Tools For Critical System Files</u>

Use file integrity checking tools to ensure that critical system files (including sensitive system and application executables, libraries, and configurations) have not been altered. The reporting system should: have the ability to account for routine and expected changes; highlight and alert on unusual or unexpected alterations; show the history of configuration changes over time and identify who made the change (including the original logged-in account in the event of a user ID switch, such as with the su or sudo command). These integrity checks should identify suspicious system alterations such as: owner and permissions changes to files or directories; the use of alternate data streams which could be used to hide malicious activities; and the introduction of extra files into key system areas (which could indicate malicious payloads left by attackers or additional files inappropriately added during batch distribution processes).

Version 7

14.9 Enforce Detail Logging for Access or Changes to Sensitive Data

Enforce detailed audit logging for access to sensitive data or changes to sensitive data (utilizing tools such as File Integrity Monitoring or Security Information and Event Monitoring).

1.3.2 Ensure filesystem integrity is regularly checked (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Periodic checking of the filesystem integrity is needed to detect changes to the filesystem.

Rationale:

Periodic file checking allows the system administrator to determine on a regular basis if critical files have been changed in an unauthorized fashion.

Audit:

Run the following to verify that aidcheck.service and aidcheck.timer are enabled and running

```
# systemctl is-enabled aidcheck.service
# systemctl status aidcheck.service

# systemctl is-enabled aidcheck.timer
# systemctl status aidcheck.timer
```

٥r

Run the following commands to determine if there is a <code>cron</code> job scheduled to run the aide check.

```
# crontab -u root -l | grep aide
# grep -r aide /etc/cron.* /etc/crontab
```

Ensure a cron job in compliance with site policy is returned.

Run the following commands:

```
# cp ./config/aidecheck.service /etc/systemd/system/aidecheck.service
# cp ./config/aidecheck.timer /etc/systemd/system/aidecheck.timer
# chmod 0644 /etc/systemd/system/aidecheck.*

# systemctl reenable aidecheck.timer
# systemctl restart aidecheck.timer
# systemctl daemon-reload
```

or

Run the following command:

```
# crontab -u root -e
```

Add the following line to the crontab:

```
0 5 * * * /usr/sbin/aide --check
```

References:

- 1. https://github.com/konstruktoid/hardening/blob/master/config/aidecheck.servic
 e
- 2. https://github.com/konstruktoid/hardening/blob/master/config/aidecheck.timer

Notes:

The checking in this recommendation occurs every day at 5am. Alter the frequency and time of the checks in compliance with site policy.

CIS Controls:

Version 6

3.5 <u>Use File Integrity Tools For Critical System Files</u>

Use file integrity checking tools to ensure that critical system files (including sensitive system and application executables, libraries, and configurations) have not been altered. The reporting system should: have the ability to account for routine and expected changes; highlight and alert on unusual or unexpected alterations; show the history of configuration changes over time and identify who made the change (including the original logged-in account in the event of a user ID switch, such as with the su or sudo command). These integrity checks should identify suspicious system alterations such as: owner and permissions changes to files or directories; the use of alternate data streams which could be used to hide malicious activities; and the introduction of extra files into key system areas (which could indicate malicious payloads left by attackers or additional files inappropriately added during batch distribution processes).

Version 7

14.9 Enforce Detail Logging for Access or Changes to Sensitive Data

Enforce detailed audit logging for access to sensitive data or changes to sensitive data (utilizing tools such as File Integrity Monitoring or Security Information and Event Monitoring).

1.4 Secure Boot Settings

The recommendations in this section focus on securing the bootloader and settings involved in the boot process directly.

1.4.1 Ensure permissions on bootloader config are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The grub configuration file contains information on boot settings and passwords for unlocking boot options. The grub configuration is usually <code>grub.cfg</code> stored in /boot/grub2/ or /boot/grub/.

Rationale:

Setting the permissions to read and write for root only prevents non-root users from seeing the boot parameters or changing them. Non-root users who read the boot parameters may be able to identify weaknesses in security upon boot and be able to exploit them.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access does not grant permissions to group or other:

```
# stat /boot/grub2/grub.cfg
Access: (0400/-r----) Uid: ( 0/ root) Gid: ( 0/ root)
```

OR

```
# stat /boot/grub/grub.cfg
Access: (0400/-r----) Uid: (   0/ root) Gid: (   0/ root)
```

Run the following commands to set permissions on your grub configuration:

```
# chown root:root /boot/grub2/grub.cfg
# chmod og-rwx /boot/grub2/grub.cfg
```

OR

```
# chown root:root /boot/grub/grub.cfg
# chmod og-rwx /boot/grub/grub.cfg
```

Notes:

This recommendation is designed around the grub bootloader, if LILO or another bootloader is in use in your environment enact equivalent settings.

Replace /boot/grub2/grub.cfg with the appropriate grub configuration file for your environment

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

1.4.2 Ensure bootloader password is set (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Setting the boot loader password will require that anyone rebooting the system must enter a password before being able to set command line boot parameters

Rationale:

Requiring a boot password upon execution of the boot loader will prevent an unauthorized user from entering boot parameters or changing the boot partition. This prevents users from weakening security (e.g. turning off SELinux at boot time).

Audit:

For grub based systems run the following command and verify output matches:

```
# grep "^\s*password" /boot/grub/menu.lst
password --md5 <encrypted-password>
```

For grub2 based systems run the following commands and verify output matches:

```
# grep "^\s*GRUB2_PASSWORD" /boot/grub2/user.cfg
GRUB2_PASSWORD=<encrypted-password>
```

OR

```
# grep "^\s*set superusers" /boot/grub/grub.cfg
set superusers="<username>"
# grep "^\s*password" /boot/grub/grub.cfg
password_pbkdf2 <username> <encrypted-password>
```

For grub based systems create an encrypted password with grub-md5-crypt:

```
# grub-crypt
Password: <password>
Retype Password: <password>
<encrypted-password>
```

Copy and paste the <encrypted-password> into the global section of /boot/grub/menu.lst:

```
password <encrypted-password>
```

For grub2 based systems

Create an encrypted password with grub2-setpassword:

```
# grub2-setpassword
Enter password: <password>
Confirm password: <password>
```

OR

create an encrypted password with grub-mkpasswd-pbkdf2:

```
# grub-mkpasswd-pbkdf2
Enter password: <password>
Reenter password: <password>
Your PBKDF2 is <encrypted-password>
```

Add the following into /etc/grub.d/00_header or a custom /etc/grub.d configuration file:

```
cat <<EOF
set superusers="<username>"
password_pbkdf2 <username> <encrypted-password>
EOF
```

Run the following command to update the grub2 configuration:

```
# grub2-mkconfig -o /boot/grub2/grub.cfg
```

OR

```
# update-grub
```

Impact:

If password protection is enabled, only the designated superuser can edit a Grub 2 menu item by pressing "e" or access the GRUB 2 command line by pressing "c"

If GRUB 2 is set up to boot automatically to a password-protected menu entry the user has no option to back out of the password prompt to select another menu entry. Holding the SHIFT key will not display the menu in this case. The user must enter the correct username and password. If unable, the configuration files will have to be edited via the LiveCD or other means to fix the problem

You can add --unrestricted to the menu entries to allow the system to boot without entering a password. Password will still be required to edit menu items.

Notes:

This recommendation is designed around the grub bootloader, if LILO or another bootloader is in use in your environment enact equivalent settings.

Replace /boot/grub2/grub.cfg or /boot/grub/grub.cfg with the appropriate grub configuration file for your environment

The superuser/user information and password do not have to be contained in the /etc/grub.d/00_header file. The information can be placed in any /etc/grub.d file as long as that file is incorporated into grub.cfg. The user may prefer to enter this data into a custom file, such as /etc/grub.d/40_custom so it is not overwritten should the Grub package be updated. If placing the information in a custom file, do not include the "cat << EOF" and "EOF" lines as the content is automatically added from these files.

CIS Controls:

Version 6

5.1 <u>Minimize And Sparingly Use Administrative Privileges</u>

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

1.4.3 Ensure authentication required for single user mode (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Single user mode is used for recovery when the system detects an issue during boot or by manual selection from the bootloader.

Rationale:

Requiring authentication in single user mode prevents an unauthorized user from rebooting the system into single user to gain root privileges without credentials.

Audit:

Perform the following to determine if a password is set for the root user:

```
# grep ^root:[*\!]: /etc/shadow
```

No results should be returned.

Remediation:

Run the following command and follow the prompts to set a password for the root user:

passwd root

CIS Controls:

Version 6

5.1 <u>Minimize And Sparingly Use Administrative Privileges</u>

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

1.4.4 Ensure interactive boot is not enabled (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Interactive boot allows console users to interactively select which services start on boot. Not all distributions support this capability.

The PROMPT_FOR_CONFIRM option provides console users the ability to interactively boot the system and select which services to start on boot .

Rationale:

Turn off the PROMPT_FOR_CONFIRM option on the console to prevent console users from potentially overriding established security settings.

Audit:

If interactive boot is available verify it is disabled on your system. On some distributions this is configured via the PROMPT FOR CONFIRM option in /etc/sysconfig/boot:

grep "^PROMPT_FOR_CONFIRM=" /etc/sysconfig/boot PROMPT FOR CONFIRM="no"

If interactive boot is available disable it.

CIS Controls:

Version 6

5.1 <u>Minimize And Sparingly Use Administrative Privileges</u>

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

1.5 Additional Process Hardening		

1.5.1 Ensure core dumps are restricted (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

A core dump is the memory of an executable program. It is generally used to determine why a program aborted. It can also be used to glean confidential information from a core file. The system provides the ability to set a soft limit for core dumps, but this can be overridden by the user.

Rationale:

Setting a hard limit on core dumps prevents users from overriding the soft variable. If core dumps are required, consider setting limits for user groups (see <code>limits.conf(5)</code>). In addition, setting the <code>fs.suid_dumpable</code> variable to 0 will prevent setuid programs from dumping core.

Audit:

Run the following commands and verify output matches:

```
# grep "hard core" /etc/security/limits.conf /etc/security/limits.d/*
* hard core 0
# sysctl fs.suid_dumpable
fs.suid_dumpable = 0
# grep "fs\.suid_dumpable" /etc/sysctl.conf /etc/sysctl.d/*
fs.suid_dumpable = 0
```

Run the following command to check if systemd-coredump is installed:

```
# systemctl is-enabled coredump.service
```

if enabled or disabled is returned systemd-coredump is installed

Add the following line to /etc/security/limits.conf or a /etc/security/limits.d/* file:

* hard core 0

Set the following parameter in /etc/sysctl.conf or a /etc/sysctl.d/* file:

fs.suid dumpable = 0

Run the following command to set the active kernel parameter:

sysctl -w fs.suid dumpable=0

If systemd-coredump is installed:

edit /etc/systemd/coredump.conf and add/modify the following lines:

Storage=none ProcessSizeMax=0

Run the command:

systemctl daemon-reload

CIS Controls:

Version 6

13 Data Protection

Data Protection

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

1.5.2 Ensure XD/NX support is enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Recent processors in the x86 family support the ability to prevent code execution on a per memory page basis. Generically and on AMD processors, this ability is called No Execute (NX), while on Intel processors it is called Execute Disable (XD). This ability can help prevent exploitation of buffer overflow vulnerabilities and should be activated whenever possible. Extra steps must be taken to ensure that this protection is enabled, particularly on 32-bit x86 systems. Other processors, such as Itanium and POWER, have included such support since inception and the standard kernel for those platforms supports the feature.

Rationale:

Enabling any feature that can protect against buffer overflow attacks enhances the security of the system.

Audit:

Run the following command and verify your kernel has identified and activated NX/XD protection.

```
# journalctl | grep 'protection: active'
kernel: NX (Execute Disable) protection: active
```

OR

on systems without journalctl

```
[[ -n $(grep noexec[0-9]*=off /proc/cmdline) || -z $(grep -E -i ' (pae|nx) ' /proc/cpuinfo) || -n $(grep '\sNX\s.*\sprotection:\s' /var/log/dmesg | grep - v active) ]] && echo "NX Protection is not active"
```

Nothing should be returned

On 32 bit systems install a kernel with PAE support, no installation is required on 64 bit systems:

If necessary configure your bootloader to load the new kernel and reboot the system. You may need to enable NX or XD support in your bios.

Notes:

Ensure your system supports the XD or NX bit and has PAE support before implementing this recommendation as this may prevent it from booting if these are not supported by your hardware.

CIS Controls:

Version 6

8.4 Enable Anti-exploitation Features (i.e. DEP, ASLR, EMET)

Enable anti-exploitation features such as Data Execution Prevention (DEP), Address Space Layout Randomization (ASLR), virtualization/containerization, etc. For increased protection, deploy capabilities such as Enhanced Mitigation Experience Toolkit (EMET) that can be configured to apply these protections to a broader set of applications and executables.

Version 7

8.3 <u>Enable Operating System Anti-Exploitation Features/ Deploy Anti-Exploit Technologies</u>

Enable anti-exploitation features such as Data Execution Prevention (DEP) or Address Space Layout Randomization (ASLR) that are available in an operating system or deploy appropriate toolkits that can be configured to apply protection to a broader set of applications and executables.

1.5.3 Ensure address space layout randomization (ASLR) is enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Address space layout randomization (ASLR) is an exploit mitigation technique which randomly arranges the address space of key data areas of a process.

Rationale:

Randomly placing virtual memory regions will make it difficult to write memory page exploits as the memory placement will be consistently shifting.

Audit:

Run the following command and verify output matches:

```
# sysctl kernel.randomize va space
kernel.randomize_va_space = 2
# grep "kernel\.randomize_va_space" /etc/sysctl.conf /etc/sysctl.d/*
kernel.randomize_va_space = 2
```

Set the following parameter in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
kernel.randomize va space = 2
```

Run the following command to set the active kernel parameter:

```
# sysctl -w kernel.randomize va space=2
```

CIS Controls:

Version 6

8.4 Enable Anti-exploitation Features (i.e. DEP, ASLR, EMET)

Enable anti-exploitation features such as Data Execution Prevention (DEP), Address Space Layout Randomization (ASLR), virtualization/containerization, etc. For increased protection, deploy capabilities such as Enhanced Mitigation Experience Toolkit (EMET) that can be configured to apply these protections to a broader set of applications and executables.

Version 7

8.3 <u>Enable Operating System Anti-Exploitation Features/ Deploy Anti-Exploit Technologies</u>

Enable anti-exploitation features such as Data Execution Prevention (DEP) or Address Space Layout Randomization (ASLR) that are available in an operating system or deploy appropriate toolkits that can be configured to apply protection to a broader set of applications and executables.

1.5.4 Ensure prelink is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

prelinkis a program that modifies ELF shared libraries and ELF dynamically linked binaries in such a way that the time needed for the dynamic linker to perform relocations at startup significantly decreases.

Rationale:

The prelinking feature can interfere with the operation of AIDE, because it changes binaries. Prelinking can also increase the vulnerability of the system if a malicious user is able to compromise a common library such as libc.

Audit:

Verify prelink is not installed. Depending on the package management in use one of the following commands may provide the needed information:

```
# rpm -q prelink
# dpkg -s prelink
```

Run the following command to restore binaries to normal:

```
# prelink -ua
```

Uninstall prelink using the appropriate package manager or manual installation:

```
# yum remove prelink
# apt-get remove prelink
# zypper remove prelink
```

CIS Controls:

Version 6

3.5 <u>Use File Integrity Tools For Critical System Files</u>

Use file integrity checking tools to ensure that critical system files (including sensitive system and application executables, libraries, and configurations) have not been altered. The reporting system should: have the ability to account for routine and expected changes; highlight and alert on unusual or unexpected alterations; show the history of configuration changes over time and identify who made the change (including the original logged-in account in the event of a user ID switch, such as with the su or sudo command). These integrity checks should identify suspicious system alterations such as: owner and permissions changes to files or directories; the use of alternate data streams which could be used to hide malicious activities; and the introduction of extra files into key system areas (which could indicate malicious payloads left by attackers or additional files inappropriately added during batch distribution processes).

Version 7

14.9 Enforce Detail Logging for Access or Changes to Sensitive Data

Enforce detailed audit logging for access to sensitive data or changes to sensitive data (utilizing tools such as File Integrity Monitoring or Security Information and Event Monitoring).

1.6 Mandatory Access Control

Mandatory Access Control (MAC) provides an additional layer of access restrictions to processes on top of the base Discretionary Access Controls. By restricting how processes can access files and resources on a system the potential impact from vulnerabilities in the processes can be reduced.

Impact: Mandatory Access Control limits the capabilities of applications and daemons on a system, while this can prevent unauthorized access the configuration of MAC can be complex and difficult to implement correctly preventing legitimate access from occurring.

1.6.1 Ensure Mandatory Access Control Software is Installed

Not all Linux Distributions include Mandatory Access Control software in the base install.

1.6.1.1 Ensure SELinux or AppArmor are installed (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

SELinux and AppArmor provide Mandatory Access Controls.

Rationale:

Without a Mandatory Access Control system installed only the default Discretionary Access Control system will be available.

Audit:

Verify either SELinux or AppArmor is installed. Depending on the package management in use one of the following command groups may provide the needed information:

```
# rpm -q libselinux
# rpm -q apparmor
# dpkg -s libselinux1
# dpkg -s apparmor
```

Install SELinux or apparmor using the appropriate package manager or manual installation:

```
# yum install libselinux

# apt-get install libselinux1

# zypper install libselinux
```

The previous commands install SELinux, use the appropriate package if AppArmor is desired.

Notes:

SELinux and AppArmor both have several package names in use on different distributions. Research the appropriate packages for your environment.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

1.6.2 Configure SELinux

SELinux provides a Mandatory Access Control (MAC) system that greatly augments the default Discretionary Access Control (DAC) model. Under SELinux, every process and every object (files, sockets, pipes) on the system is assigned a security context, a label that includes detailed type information about the object. The kernel allows processes to access objects only if that access is explicitly allowed by the policy in effect. The policy defines transitions, so that a user can be allowed to run software, but the software can run under a different context than the user's default. This automatically limits the damage that the software can do to files accessible by the calling user. The user does not need to take any action to gain this benefit. For an action to occur, both the traditional DAC permissions must be satisfied as well as the SELinux MAC rules. The action will not be allowed if either one of these models does not permit the action. In this way, SELinux rules can only make a system's permissions more restrictive and secure. SELinux requires a complex policy to allow all the actions required of a system under normal operation. Three such policies have been designed for use with RHEL7 and are included with the system: targeted, strict, and mls. These are described as follows:

- targeted: consists mostly of Type Enforcement (TE) rules, and a small number of Role-Based Access Control (RBAC) rules. Targeted restricts the actions of many types of programs, but leaves interactive users largely unaffected.
- strict: also uses TE and RBAC rules, but on more programs and more aggressively.
- mls: implements Multi-Level Security (MLS), which introduces even more kinds of labels (sensitivity and category) and rules that govern access based on these.

This section provides guidance for the configuration of the targetedpolicy.

Note: This section only applies if SELinux is in use on the system. Recommendations for AppArmor are also included, and additional Mandatory Access Control systems exist beyond these two.

References:

- 1. NSA SELinux resources:
 - 1. http://www.nsa.gov/research/selinux
 - 2. http://www.nsa.gov/research/selinux/list.shtml
- 2. Fedora SELinux resources:
 - 1. FAQ: http://docs.fedoraproject.org/selinux-faq
 - 2. User Guide: http://docs.fedoraproject.org/selinux-user-guide
 - 3. Managing Services Guide: http://docs.fedoraproject.org/selinux-managing-confined-services-guide
- 3. SELinux Project web page and wiki:
 - 1. http://www.selinuxproject.org
- 4. Chapters 43-45 of Red Hat Enterprise Linux 5: Deployment Guide (Frank Mayer, Karl MacMillan and David Caplan),
- 5. SELinux by Example: Using Security Enhanced Linux (Prentice Hall, August 6, 2006)

1.6.2.1 Ensure SELinux is not disabled in bootloader configuration (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Configure SELINUX to be enabled at boot time and verify that it has not been overwritten by the grub boot parameters.

Rationale:

SELinux must be enabled at boot time in your grub configuration to ensure that the controls it provides are not overridden.

Audit:

For grub based systems run the following command and verify that no kernel line has the selinux=0 or enforcing=0 parameters set:

```
# grep "^\s*kernel" /boot/grub/menu.lst
```

For grub2 based systems run the following command and verify that no linux line has the selinux=0 or enforcing=0 parameters set:

grep "^\s*linux" /boot/grub2/grub.cfg

For grub based systems edit /boot/grub/menu.lst and remove all instances of selinux=0 and enforcing=0 on all kernel lines.

For grub2 based systems edit /etc/default/grub and remove all instances of selinux=0 and enforcing=0 from all CMDLINE_LINUX parameters:

```
GRUB_CMDLINE_LINUX_DEFAULT="quiet"
GRUB_CMDLINE_LINUX=""
```

Run the following command to update the grub2 configuration:

```
# update-grub
```

or

```
# grub2-mkconfig -o /boot/grub2/guub.cfg
```

Notes:

This recommendation is designed around the grub bootloader, if LILO or another bootloader is in use in your environment enact equivalent settings.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

1.6.2.2 Ensure the SELinux state is enforcing (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Set SELinux to enable when the system is booted.

Rationale:

SELinux must be enabled at boot time to ensure that the controls it provides are in effect at all times.

Audit:

Run the following commands and ensure output matches:

```
# grep SELINUX=enforcing /etc/selinux/config
SELINUX=enforcing

# sestatus
SELinux status: enabled
Current mode: enforcing
Mode from config file: enforcing
```

Edit the /etc/selinux/config file to set the SELINUX parameter:

SELINUX=enforcing

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

1.6.2.3 Ensure SELinux policy is configured (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Configure SELinux to meet or exceed the default targeted policy, which constrains daemons and system software only.

Rationale:

Security configuration requirements vary from site to site. Some sites may mandate a policy that is stricter than the default policy, which is perfectly acceptable. This item is intended to ensure that at least the default recommendations are met.

Audit:

Run the following commands and ensure output matches either "targeted "or "mls":

```
# grep SELINUXTYPE=targeted /etc/selinux/config
SELINUXTYPE=targeted

# sestatus
Policy from config file: targeted
```

Edit the /etc/selinux/config file to set the SELINUXTYPE parameter:

SELINUXTYPE=targeted

Notes:

If your organization requires stricter policies, ensure that they are set in the /etc/selinux/config file.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

1.6.2.4 Ensure SETroubleshoot is not installed (Scored)

Profile Applicability:

• Level 2 - Server

Description:

The SETroubleshoot service notifies desktop users of SELinux denials through a user-friendly interface. The service provides important information around configuration errors, unauthorized intrusions, and other potential errors.

Rationale:

The SETroubleshoot service is an unnecessary daemon to have running on a server, especially if X Windows is disabled.

Audit:

Verify setroubleshoot is not installed. Depending on the package management in use one of the following commands may provide the needed information:

```
# rpm -q setroubleshoot
# dpkg -s setroubleshoot
```

Uninstall setroubleshoot using the appropriate package manager or manual installation:

```
# yum remove setroubleshoot
# apt-get remove setroubleshoot
# zypper remove setroubleshoot
```

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

1.6.2.5 Ensure the MCS Translation Service (mcstrans) is not installed (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The mcstransd daemon provides category label information to client processes requesting information. The label translations are defined in /etc/selinux/targeted/setrans.conf

Rationale:

Since this service is not used very often, remove it to reduce the amount of potentially vulnerable code running on the system.

Audit:

Verify mostrans is not installed. Depending on the package management in use one of the following commands may provide the needed information:

rpm -q mcstrans
dpkg -s mcstrans

Uninstall mostrans using the appropriate package manager or manual installation:

yum remove mcstrans
apt-get remove mcstrans
zypper remove mcstrans

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

1.6.2.6 Ensure no unconfined daemons exist (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Daemons that are not defined in SELinux policy will inherit the security context of their parent process.

Rationale:

Since daemons are launched and descend from the <code>init</code> process, they will inherit the security context label <code>initrc_t</code>. This could cause the unintended consequence of giving the process more permission than it requires.

Audit:

Run the following command and verify not output is produced:

```
# ps -eZ | grep -E "initrc" | grep -E -v -w "tr|ps|grep|bash|awk" | tr ':' '
' | awk '{ print $NF }'
```

Investigate any unconfined daemons found during the audit action. They may need to have an existing security context assigned to them or a policy built for them.

Notes:

Occasionally certain daemons such as backup or centralized management software may require running unconfined. Any such software should be carefully analyzed and documented before such an exception is made.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

1.6.3 Configure AppArmor

AppArmor provides a Mandatory Access Control (MAC) system that greatly augments the default Discretionary Access Control (DAC) model. Under AppArmor MAC rules are applied by file paths instead of by security contexts as in other MAC systems. As such it does not require support in the filesystem and can be applied to network mounted filesystems for example. AppArmor security policies define what system resources applications can access and what privileges they can do so with. This automatically limits the damage that the software can do to files accessible by the calling user. The user does not need to take any action to gain this benefit. For an action to occur, both the traditional DAC permissions must be satisfied as well as the AppArmor MAC rules. The action will not be allowed if either one of these models does not permit the action. In this way, AppArmor rules can only make a system's permissions more restrictive and secure.

Note: This section only applies if AppArmor is in use on the system. Recommendations for SELinux are also included, and additional Mandatory Access Control systems exist beyond these two.

References:

- 1. AppArmor Documentation: http://wiki.apparmor.net/index.php/Documentation
- 2. Ubuntu AppArmor Documentation: https://help.ubuntu.com/community/AppArmor
- 3. SUSE AppArmor Documentation: https://www.suse.com/documentation/apparmor/

1.6.3.1 Ensure AppArmor is not disabled in bootloader configuration (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Configure AppArmor to be enabled at boot time and verify that it has not been overwritten by the bootloader boot parameters.

Rationale:

AppArmor must be enabled at boot time in your bootloader configuration to ensure that the controls it provides are not overridden.

Audit:

For grub based systems run the following command and verify that no kernel line has the apparmor=0 parameter set:

```
# grep "^\s*kernel" /boot/grub/menu.lst
```

For grub2 based systems run the following command and verify that no linux line the apparmor=0 parameter set:

grep "^\s*linux" /boot/grub/menu.lst

For grub based systems edit /boot/grub/menu.lst and remove all instances of apparmor=0 on all kernel lines.

For grub2 based systems edit /etc/default/grub and remove all instances of apparmor=0 from all CMDLINE LINUX parameters:

```
GRUB_CMDLINE_LINUX_DEFAULT="quiet"
GRUB_CMDLINE_LINUX=""
```

Run the following command to update the grub2 configuration:

```
# update-grub
```

Notes:

This recommendation is designed around the grub bootloader, if LILO or another bootloader is in use in your environment enact equivalent settings.

Replace /boot/grub/menu.lst with the appropriate grub configuration file for your environment.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

1.6.3.2 Ensure all AppArmor Profiles are enforcing (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

AppArmor profiles define what resources applications are able to access.

Rationale:

Security configuration requirements vary from site to site. Some sites may mandate a policy that is stricter than the default policy, which is perfectly acceptable. This item is intended to ensure that any policies that exist on the system are activated.

Audit:

Run the following command and verify that profiles are loaded, no profiles are in complain mode, and no processes are unconfined:

```
# apparmor status
apparmor module is loaded.
17 profiles are loaded.
17 profiles are in enforce mode.
  /bin/ping
  /sbin/klogd
  /sbin/syslog-ng
  /sbin/syslogd
  /usr/lib/PolicyKit/polkit-explicit-grant-helper
  /usr/lib/PolicyKit/polkit-grant-helper
  /usr/lib/PolicyKit/polkit-grant-helper-pam
  /usr/lib/PolicyKit/polkit-read-auth-helper
  /usr/lib/PolicyKit/polkit-resolve-exe-helper
  /usr/lib/PolicyKit/polkit-revoke-helper
  /usr/lib/PolicyKit/polkitd
  /usr/sbin/avahi-daemon
  /usr/sbin/identd
  /usr/sbin/mdnsd
  /usr/sbin/nscd
  /usr/sbin/ntpd
  /usr/sbin/traceroute
O profiles are in complain mode.
1 processes have profiles defined.
1 processes are in enforce mode :
  /usr/sbin/nscd (3979)
O processes are in complain mode.
O processes are unconfined but have a profile defined.
```

Run the following command to set all profiles to enforce mode:

enforce /etc/apparmor.d/*

Any unconfined processes may need to have a profile created or activated for them and then be restarted.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

1.7 Warning Banners

Presenting a warning message prior to the normal user login may assist in the prosecution of trespassers on the computer system. Changing some of these login banners also has the side effect of hiding OS version information and other detailed system information from attackers attempting to target specific exploits at a system.

Guidelines published by the US Department of Defense require that warning messages include at least the name of the organization that owns the system, the fact that the system is subject to monitoring and that such monitoring is in compliance with local statutes, and that use of the system implies consent to such monitoring. It is important that the organization's legal counsel review the content of all messages before any system modifications are made, as these warning messages are inherently site-specific. More information (including citations of relevant case law) can be found at http://www.justice.gov/criminal/cybercrime/

Note: The text provided in the remediation actions for these items is intended as an example only. Please edit to include the specific text for your organization as approved by your legal department.

1.7.1 Command Line Warning Banners

The /etc/motd, /etc/issue, and /etc/issue.net files govern warning banners for standard command line logins for both local and remote users.

1.7.1.1 Ensure message of the day is configured properly (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The contents of the /etc/motd file are displayed to users after login and function as a message of the day for authenticated users.

Unix-based systems have typically displayed information about the OS release and patch level upon logging in to the system. This information can be useful to developers who are developing software for a particular OS platform. If mingetty(8) supports the following options, they display operating system information: $\mbox{$\mbox{$\mbox{$$}$}$}$ - machine architecture $\mbox{$\mbox{$$}$}$ - operating system release $\mbox{$\mbox{$$}$}$ - operating system name $\mbox{$\mbox{$$}$}$ - operating system version

Rationale:

Warning messages inform users who are attempting to login to the system of their legal status regarding the system and must include the name of the organization that owns the system and any monitoring policies that are in place. Displaying OS and patch level information in login banners also has the side effect of providing detailed system information to attackers attempting to target specific exploits of a system. Authorized users can easily get this information by running the "uname -a" command once they have logged in.

Audit:

Run the following command and verify that the contents match site policy:

```
# cat /etc/motd
```

Run the following command and verify no results are returned:

```
# grep -E -i "(\\v|\\r|\\m|\\s|$(grep '^ID=' /etc/os-release | cut -d= -f2 | sed -e 's/"//g'))" /etc/motd
```

Edit the /etc/motd file with the appropriate contents according to your site policy, remove any instances of $\mbox{\em m}$, $\mbox{\em v}$, $\mbox{\em v}$ or references to the os platform

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.7.1.2 Ensure local login warning banner is configured properly (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The contents of the /etc/issue file are displayed to users prior to login for local terminals.

Unix-based systems have typically displayed information about the OS release and patch level upon logging in to the system. This information can be useful to developers who are developing software for a particular OS platform. If $\mathtt{mingetty}(8)$ supports the following options, they display operating system information: $\mbox{$\mbox{$\mbox{$$}$}$}$ - machine architecture $\mbox{$\mbox{$$}$}$ - operating system release $\mbox{$\mbox{$$}$}$ - operating system name $\mbox{$\mbox{$$}$}$ - operating system version - or the operating system's name

Rationale:

Warning messages inform users who are attempting to login to the system of their legal status regarding the system and must include the name of the organization that owns the system and any monitoring policies that are in place. Displaying OS and patch level information in login banners also has the side effect of providing detailed system information to attackers attempting to target specific exploits of a system. Authorized users can easily get this information by running the "uname -a" command once they have logged in.

Audit:

Run the following command and verify that the contents match site policy:

```
# cat /etc/issue
```

Run the following command and verify no results are returned:

```
# grep -E -i "(\\v|\\r|\\m|\\s|$(grep '^ID=' /etc/os-release | cut -d= -f2 | sed -e 's/"//g'))" /etc/issue
```

Edit the /etc/issue file with the appropriate contents according to your site policy, remove any instances of $\mbox{\ \ n}$, $\mbox{\ \ r}$, $\mbox{\ \ v}$ or references to the OS platform

echo "Authorized uses only. All activity may be monitored and reported." >
/etc/issue

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.7.1.3 Ensure remote login warning banner is configured properly (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The contents of the /etc/issue.net file are displayed to users prior to login for remote connections from configured services.

Unix-based systems have typically displayed information about the OS release and patch level upon logging in to the system. This information can be useful to developers who are developing software for a particular OS platform. If $\mathtt{mingetty}(8)$ supports the following options, they display operating system information: $\mbox{$\mbox{\backslashm}$}$ - machine architecture $\mbox{$\mbox{\backslashr}$}$ - operating system release $\mbox{$\mbox{\backslashs}$}$ - operating system name $\mbox{$\mbox{\backslashv}$}$ - operating system version

Rationale:

Warning messages inform users who are attempting to login to the system of their legal status regarding the system and must include the name of the organization that owns the system and any monitoring policies that are in place. Displaying OS and patch level information in login banners also has the side effect of providing detailed system information to attackers attempting to target specific exploits of a system. Authorized users can easily get this information by running the "uname -a" command once they have logged in.

Audit:

Run the following command and verify that the contents match site policy:

```
# cat /etc/issue.net
```

Run the following command and verify no results are returned:

```
# grep -E -i "(\\v|\\r|\\m|\\s|$(grep '^ID=' /etc/os-release | cut -d= -f2 | sed -e 's/"//g'))" /etc/issue.net
```

Edit the /etc/issue.net file with the appropriate contents according to your site policy, remove any instances of $\mbox{\ m}$, $\mbox{\ r}$, $\mbox{\ v}$ or references to the $\mbox{\ os}$ platform

echo "Authorized uses only. All activity may be monitored and reported." >
/etc/issue.net

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.7.1.4 Ensure permissions on /etc/motd are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The contents of the /etc/motd file are displayed to users after login and function as a message of the day for authenticated users.

Rationale:

If the /etc/motd file does not have the correct ownership it could be modified by unauthorized users with incorrect or misleading information.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access is 644:

```
# stat /etc/motd
Access: (0644/-rw-r--r--) Uid: ( 0/ root) Gid: ( 0/ root)
```

Remediation:

Run the following commands to set permissions on /etc/motd:

```
# chown root:root /etc/motd
# chmod 644 /etc/motd
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

1.7.1.5 Ensure permissions on /etc/issue are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The contents of the /etc/issue file are displayed to users prior to login for local terminals.

Rationale:

If the /etc/issue file does not have the correct ownership it could be modified by unauthorized users with incorrect or misleading information.

Audit:

Run the following command and verify Uid and Gid are both O/root and Access is 644:

```
# stat /etc/issue
Access: (0644/-rw-r--r--) Uid: ( 0/ root) Gid: ( 0/ root)
```

Remediation:

Run the following commands to set permissions on /etc/issue:

```
# chown root:root /etc/issue
# chmod 644 /etc/issue
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

1.7.1.6 Ensure permissions on /etc/issue.net are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The contents of the /etc/issue.net file are displayed to users prior to login for remote connections from configured services.

Rationale:

If the /etc/issue.net file does not have the correct ownership it could be modified by unauthorized users with incorrect or misleading information.

Audit:

Run the following command and verify Uid and Gid are both O/root and Access is 644:

```
# stat /etc/issue.net
Access: (0644/-rw-r--r--) Uid: ( 0/ root) Gid: ( 0/ root)
```

Remediation:

Run the following commands to set permissions on /etc/issue.net:

```
# chown root:root /etc/issue.net
# chmod 644 /etc/issue.net
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

1.7.2 Ensure GDM login banner is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

GDM is the GNOME Display Manager which handles graphical login for GNOME based systems.

Rationale:

Warning messages inform users who are attempting to login to the system of their legal status regarding the system and must include the name of the organization that owns the system and any monitoring policies that are in place.

Audit:

If GDM is installed on the system verify that /etc/gdm3/greeter.dconf-defaults file exists and contains the following:

[org/gnome/login-screen]
banner-message-enable=true
banner-message-text='<banner message>'

Edit or create the file /etc/gdm3/greeter.dconf-defaults and add the following:

[org/gnome/login-screen]
banner-message-enable=true
banner-message-text='Authorized uses only. All activity may be monitored and
reported.'

Notes:

Additional options and sections may appear in the /etc/dconf/db/gdm.d/01-banner-message file.

If a different GUI login service is in use, consult your documentation and apply an equivalent banner.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

1.8 Ensure updates, patches, and additional security software are installed (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Periodically patches are released for included software either due to security flaws or to include additional functionality.

Rationale:

Newer patches may contain security enhancements that would not be available through the latest full update. As a result, it is recommended that the latest software patches be used to take advantage of the latest functionality. As with any software installation, organizations need to determine if a given update meets their requirements and verify the compatibility and supportability of any additional software against the update revision that is selected.

Audit:

Verify there are no updates or patches to install. Depending on the package management in use one of the following command groups may provide the needed information:

```
# yum check-update

# apt-get -s upgrade

# zypper list-updates
```

Use your package manager to update all packages on the system according to site policy.

Notes:

Site policy may mandate a testing period before install onto production systems for available updates.

CIS Controls:

Version 6

4.5 <u>Use Automated Patch Management And Software Update Tools</u>

Deploy automated patch management tools and software update tools for operating system and software/applications on all systems for which such tools are available and safe. Patches should be applied to all systems, even systems that are properly air gapped.

Version 7

3.4 <u>Deploy Automated Operating System Patch Management Tools</u>

Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.

3.5 <u>Deploy Automated Software Patch Management Tools</u>

Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.

2 Services

While applying system updates and patches helps correct known vulnerabilities, one of the best ways to protect the system against as yet unreported vulnerabilities is to disable all services that are not required for normal system operation. This prevents the exploitation of vulnerabilities discovered at a later date. If a service is not enabled, it cannot be exploited. The actions in this section of the document provide guidance on some services which can be safely disabled and under which circumstances, greatly reducing the number of possible threats to the resulting system. Additionally some services which should remain enabled but with secure configuration are covered as well as insecure service clients.

2.1 inetd Services

inetd is a super-server daemon that provides internet services and passes connections to configured services. While not commonly used inetd and any unneeded inetd based services should be disabled if possible.

2.1.1 Ensure chargen services are not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

chargenis a network service that responds with 0 to 512 ASCII characters for each connection it receives. This service is intended for debugging and testing purposes. It is recommended that this service be disabled.

Rationale:

Disabling this service will reduce the remote attack surface of the system.

Audit:

Verify the chargen service is not enabled. Run the following command and verify results are as indicated:

```
grep -R "^chargen" /etc/inetd.*
```

No results should be returned

check /etc/xinetd.conf and /etc/xinetd.d/* and verify all chargen services have
disable = yes set.

Comment out or remove any lines starting with chargen from /etc/inetd.conf and /etc/inetd.d/*.

Set disable = yes on all chargen services in /etc/xinetd.conf and /etc/xinetd.d/*.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.1.2 Ensure daytime services are not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

daytime is a network service that responds with the server's current date and time. This service is intended for debugging and testing purposes. It is recommended that this service be disabled.

Rationale:

Disabling this service will reduce the remote attack surface of the system.

Audit:

Verify the daytime service is not enabled. Run the following command and verify results are as indicated:

```
grep -R "^daytime" /etc/inetd.*
```

No results should be returned

check /etc/xinetd.conf and /etc/xinetd.d/* and verify all daytime services have disable = yes set.

Comment out or remove any lines starting with daytime from /etc/inetd.conf and /etc/inetd.d/*.

Set disable = yes on all daytime services in /etc/xinetd.conf and /etc/xinetd.d/*.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.1.3 Ensure discard services are not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

discardis a network service that simply discards all data it receives. This service is intended for debugging and testing purposes. It is recommended that this service be disabled.

Rationale:

Disabling this service will reduce the remote attack surface of the system.

Audit:

Verify the discard service is not enabled. Run the following command and verify results are as indicated:

```
grep -R "^discard" /etc/inetd.*
```

No results should be returned

check /etc/xinetd.conf and /etc/xinetd.d/* and verify all discard services have disable = yes set.

Comment out or remove any lines starting with discard from /etc/inetd.conf and /etc/inetd.d/* .

Set disable = yes on all discard services in /etc/xinetd.conf and /etc/xinetd.d/*.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.1.4 Ensure echo services are not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

echois a network service that responds to clients with the data sent to it by the client. This service is intended for debugging and testing purposes. It is recommended that this service be disabled.

Rationale:

Disabling this service will reduce the remote attack surface of the system.

Audit:

Verify the echo service is not enabled. Run the following command and verify results are as indicated:

grep -R "^echo" /etc/inetd.*

No results should be returned

check /etc/xinetd.conf and /etc/xinetd.d/* and verify all echo services have disable =
yes set.

Comment out or remove any lines starting with echo from /etc/inetd.conf and /etc/inetd.d/* .

Set disable = yes on all echo services in /etc/xinetd.conf and /etc/xinetd.d/*.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.1.5 Ensure time services are not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

time is a network service that responds with the server's current date and time as a 32 bit integer. This service is intended for debugging and testing purposes. It is recommended that this service be disabled.

Rationale:

Disabling this service will reduce the remote attack surface of the system.

Audit:

Verify the time service is not enabled. Run the following command and verify results are as indicated:

```
grep -R "^time" /etc/inetd.*
```

No results should be returned

check /etc/xinetd.conf and /etc/xinetd.d/* and verify all time services have disable =
yes set.

Comment out or remove any lines starting with time from /etc/inetd.conf and /etc/inetd.d/* .

Set disable = yes on all time services in /etc/xinetd.conf and /etc/xinetd.d/*.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.1.6 Ensure rsh server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Berkeley rsh-server (rsh, rlogin, rexec) package contains legacy services that exchange credentials in clear-text.

Rationale:

These legacy services contain numerous security exposures and have been replaced with the more secure SSH package.

Audit:

Verify the rsh services are not enabled. Run the following commands and verify results are as indicated:

```
grep -R "^shell" /etc/inetd.*
grep -R "^login" /etc/inetd.*
grep -R "^exec" /etc/inetd.*
```

No results should be returned

check /etc/xinetd.conf and /etc/xinetd.d/* and verify all rsh , rlogin , and rexec services have disable = yes set.

Comment out or remove any lines starting with shell, login, or exec from /etc/inetd.conf and /etc/inetd.d/*.

Set disable = yes on all rsh, rlogin, and rexec services in /etc/xinetd.conf and /etc/xinetd.d/*.

CIS Controls:

Version 6

3.4 Use Only Secure Channels For Remote System Administration

Perform all remote administration of servers, workstation, network devices, and similar equipment over secure channels. Protocols such as telnet, VNC, RDP, or others that do not actively support strong encryption should only be used if they are performed over a secondary encryption channel, such as SSL, TLS or IPSEC.

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

4.5 <u>Use Multifactor Authentication For All Administrative Access</u>

Use multi-factor authentication and encrypted channels for all administrative account access.

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.1.7 Ensure talk server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The talk software makes it possible for users to send and receive messages across systems through a terminal session. The talk client (allows initiate of talk sessions) is installed by default.

Rationale:

The software presents a security risk as it uses unencrypted protocols for communication.

Audit:

Verify the talk service is not enabled. Run the following commands and verify results are as indicated:

```
grep -R "^talk" /etc/inetd.*
grep -R "^ntalk" /etc/inetd.*
```

No results should be returned

check /etc/xinetd.conf and /etc/xinetd.d/* and verify all talk services have disable =
yes set.

Comment out or remove any lines starting with talk or ntalk from /etc/inetd.conf and /etc/inetd.d/* .

Set disable = yes on all talk services in /etc/xinetd.conf and /etc/xinetd.d/*.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.1.8 Ensure telnet server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The telnet-server package contains the telnet daemon, which accepts connections from users from other systems via the telnet protocol.

Rationale:

The telnet protocol is insecure and unencrypted. The use of an unencrypted transmission medium could allow a user with access to sniff network traffic the ability to steal credentials. The ssh package provides an encrypted session and stronger security.

Audit:

Verify the telnet service is not enabled. Run the following command and verify results are as indicated:

```
grep -R "^telnet" /etc/inetd.*
```

No results should be returned

check /etc/xinetd.conf and /etc/xinetd.d/* and verify all telnet services have disable
= yes set.

Comment out or remove any lines starting with telnet from /etc/inetd.conf and /etc/inetd.d/*.

Set disable = yes on all telnet services in /etc/xinetd.conf and /etc/xinetd.d/*.

CIS Controls:

Version 6

3.4 <u>Use Only Secure Channels For Remote System Administration</u>

Perform all remote administration of servers, workstation, network devices, and similar equipment over secure channels. Protocols such as telnet, VNC, RDP, or others that do not actively support strong encryption should only be used if they are performed over a secondary encryption channel, such as SSL, TLS or IPSEC.

9.1 <u>Limit Open Ports, Protocols, and Services</u>

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

4.5 <u>Use Multifactor Authentication For All Administrative Access</u>

Use multi-factor authentication and encrypted channels for all administrative account access.

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.1.9 Ensure tftp server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Trivial File Transfer Protocol (TFTP) is a simple file transfer protocol, typically used to automatically transfer configuration or boot machines from a boot server. The packages tftp and atftp are both used to define and support a TFTP server.

Rationale:

TFTP does not support authentication nor does it ensure the confidentiality or integrity of data. It is recommended that TFTP be removed, unless there is a specific need for TFTP. In that case, extreme caution must be used when configuring the services.

Audit:

Verify the tftp service is not enabled. Run the following command and verify results are as indicated:

grep -R "^tftp" /etc/inetd.*

No results should be returned

check /etc/xinetd.conf and /etc/xinetd.d/* and verify all tftp services have disable =
yes set.

Comment out or remove any lines starting with tftp from /etc/inetd.conf and /etc/inetd.d/* .

Set disable = yes on all tftp services in /etc/xinetd.conf and /etc/xinetd.d/*.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.1.10 Ensure xinetd is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The eXtended InterNET Daemon (xinetd) is an open source super daemon that replaced the original inetd daemon. The xinetd daemon listens for well known services and dispatches the appropriate daemon to properly respond to service requests.

Rationale:

If there are no xinetd services required, it is recommended that the daemon be disabled.

Audit:

Run one of the following commands to verify xinetd is not enabled:

Verify all runlevels are listed as "off" or autofs is not available.

```
# systemctl is-enabled xinetd
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep xinetd
```

Verify no S* lines are returned.

Run one of the following commands to disable xinetd:

```
# chkconfig xinetd off

# systemctl disable xinetd

# update-rc.d xinetd disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

2.2 Special Purpose Services

This section describes services that are installed on systems that specifically need to run these services. If any of these services are not required, it is recommended that they be disabled or deleted from the system to reduce the potential attack surface.

2.2.1 Time Synchronization

It is recommended that physical systems and virtual guests lacking direct access to the physical host's clock be configured to synchronize their time using a service such as NTP or chrony.

2.2.1.1 Ensure time synchronization is in use (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

System time should be synchronized between all systems in an environment. This is typically done by establishing an authoritative time server or set of servers and having all systems synchronize their clocks to them.

Rationale:

Time synchronization is important to support time sensitive security mechanisms like Kerberos and also ensures log files have consistent time records across the enterprise, which aids in forensic investigations.

Audit:

On physical systems or virtual systems where host based time synchronization is not available verify that NTP, chrony, or timesyncd is installed. Depending on the package management in use one of the following command groups may provide the needed information:

```
# rpm -q ntp
# rpm -q chrony

# dpkg -s ntp
# dpkg -s chrony
```

On virtual systems where host based time synchronization is available consult your virtualization software documentation and verify that host based synchronization is in use.

On physical systems or virtual systems where host based time synchronization is not available install NTP or chrony using the appropriate package manager or manual installation:

```
# yum install ntp
# dnf install ntp
# apt-get install ntp
# zypper install ntp
# emerge ntp
```

The previous commands install NTP, use the appropriate package if chrony is desired. On virtual systems where host based time synchronization is available consult your virtualization software documentation and setup host based synchronization.

Notes:

systemd-timesyncd is part of systemd. Some versions of systemd have been compiled without systemd-timesycnd. On these distributions, chrony or NTP should be used instead of systemd-timesycnd.

CIS Controls:

Version 6

6.1 <u>Use At Least Two Synchronized Time Sources For All Servers And Network</u> Equipment

Include at least two synchronized time sources from which all servers and network equipment retrieve time information on a regular basis so that timestamps in logs are consistent.

Version 7

6.1 <u>Utilize Three Synchronized Time Sources</u>

Use at least three synchronized time sources from which all servers and network devices retrieve time information on a regular basis so that timestamps in logs are consistent.

2.2.1.2 Ensure ntp is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

ntp is a daemon which implements the Network Time Protocol (NTP). It is designed to synchronize system clocks across a variety of systems and use a source that is highly accurate. More information on NTP can be found at http://www.ntp.org. ntp can be configured to be a client and/or a server.

This recommendation only applies if ntp is in use on the system.

Rationale:

If ntp is in use on the system proper configuration is vital to ensuring time synchronization is working properly.

Audit:

Run the following command and verify output matches:

```
# grep "^restrict" /etc/ntp.conf
restrict -4 default kod nomodify notrap nopeer noquery
restrict -6 default kod nomodify notrap nopeer noquery
```

The -4 in the first line is optional and options after default can appear in any order. Additional restriction lines may exist.

Run the following command and verify remote server is configured properly:

```
# grep -E "^(server|pool)" /etc/ntp.conf
server <remote-server>
```

Multiple servers may be configured.

Verify that ntp is configured to run as the ntp user by running one of the following commands as appropriate for your distribution and verifying output matches:

```
# grep "^OPTIONS" /etc/sysconfig/ntpd
OPTIONS="-u ntp:ntp"
# grep "^NTPD_OPTIONS" /etc/sysconfig/ntp
OPTIONS="-u ntp:ntp"
```

Additional options may be present.

```
# grep "RUNASUSER=ntp" /etc/init.d/ntp
RUNASUSER=ntp
```

Add or edit restrict lines in /etc/ntp.conf to match the following:

```
restrict -4 default kod nomodify notrap nopeer noquery restrict -6 default kod nomodify notrap nopeer noquery
```

Add or edit server or pool lines to /etc/ntp.conf as appropriate:

```
server <remote-server>
```

Configure ntp to run as the ntp user by adding or editing one of the following files as appropriate for your distribution:

/etc/sysconfig/ntpd:

```
OPTIONS="-u ntp:ntp"
```

/etc/sysconfig/ntp:

```
NTPD_OPTIONS="-u ntp:ntp"
```

/etc/init.d/ntp:

RUNASUSER=ntp

CIS Controls:

Version 6

6.1 <u>Use At Least Two Synchronized Time Sources For All Servers And Network</u> <u>Equipment</u>

Include at least two synchronized time sources from which all servers and network equipment retrieve time information on a regular basis so that timestamps in logs are consistent.

Version 7

6.1 <u>Utilize Three Synchronized Time Sources</u>

Use at least three synchronized time sources from which all servers and network devices retrieve time information on a regular basis so that timestamps in logs are consistent.

2.2.1.3 Ensure chrony is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

chrony is a daemon which implements the Network Time Protocol (NTP) is designed to synchronize system clocks across a variety of systems and use a source that is highly accurate. More information on chrony can be found at http://chrony.tuxfamily.org/. chrony can be configured to be a client and/or a server.

Rationale:

If chrony is in use on the system proper configuration is vital to ensuring time synchronization is working properly.

This recommendation only applies if chrony is in use on the system.

Audit:

Run the following command and verify remote server is configured properly:

```
# grep -E "^(server|pool)" /etc/chrony.conf
server <remote-server>
```

Multiple servers may be configured.

Run the following command and verify the first field for the chronyd process is chrony:

```
# ps -ef | grep chronyd chrony 491 1 0 20:32 ? 00:00:00 /usr/sbin/chronyd
```

Add or edit server or pool lines to /etc/chrony.conf as appropriate:

server <remote-server>

Configure chrony to run as the chrony user by configuring the appropriate startup script for your distribution. Startup scripts are typically stored in /etc/init.d or /etc/systemd.

CIS Controls:

Version 6

6.1 <u>Use At Least Two Synchronized Time Sources For All Servers And Network Equipment</u>

Include at least two synchronized time sources from which all servers and network equipment retrieve time information on a regular basis so that timestamps in logs are consistent.

Version 7

6.1 <u>Utilize Three Synchronized Time Sources</u>

Use at least three synchronized time sources from which all servers and network devices retrieve time information on a regular basis so that timestamps in logs are consistent.

2.2.1.4 Ensure systemd-timesyncd is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

systemd-timesyncd is a daemon that has been added for synchronizing the system clock across the network. It implements an SNTP client. In contrast to NTP implementations such as chrony or the NTP reference server this only implements a client side, and does not bother with the full NTP complexity, focusing only on querying time from one remote server and synchronizing the local clock to it. The daemon runs with minimal privileges, and has been hooked up with networkd to only operate when network connectivity is available. The daemon saves the current clock to disk every time a new NTP sync has been acquired, and uses this to possibly correct the system clock early at bootup, in order to accommodate for systems that lack an RTC such as the Raspberry Pi and embedded devices, and make sure that time monotonically progresses on these systems, even if it is not always correct. To make use of this daemon a new system user and group "systemd-timesync" needs to be created on installation of systemd.

This recommendation only applies if timesyncd is in use on the system.

Rationale:

Proper configuration is vital to ensuring time synchronization is working properly.

Audit:

Ensure that timesyncd is enabled and started Run the following commands:

```
#systemctl is-enabled systemd-timesyncd.service
```

This should return:

```
enabled
```

Review /etc/systemd/timesyncd.conf and ensure that the NTP servers, NTP FallbackNTP servers, and RootDistanceMaxSec listed are in accordance with local policy Run the following command

```
timedatectl status
```

This should return something similar to:

```
Local time: Tue 2019-06-04 15:40:45 EDT

Universal time: Tue 2019-06-04 19:40:45 UTC

RTC time: Tue 2019-06-04 19:40:45

Time zone: America/New_York (EDT, -0400)

NTP enabled: yes

NTP synchronized: yes

RTC in local TZ: no

DST active: yes

Last DST change: DST began at

Sun 2019-03-10 01:59:59 EST

Sun 2019-03-10 03:00:00 EDT

Next DST change: DST ends (the clock jumps one hour backwards) at

Sun 2019-11-03 01:59:59 EDT

Sun 2019-11-03 01:00:00 EST
```

Run the following command to enable systemd-timesyncd

```
systemctl enable systemd-timesyncd.service
```

edit the file /etc/systemd/timesyncd.conf and add/modify the following lines:

```
NTP=0.debian.pool.ntp.org 1.debian.pool.ntp.org #Servers listed should be In Accordence With Local Policy

FallbackNTP=2.debian.pool.ntp.org 3.debian.pool.ntp.org #Servers listed should be In Accordence With Local Policy

RootDistanceMax=1 #should be In Accordence With Local Policy
```

Run the following commands to start systemd-timesyncd.service

```
# systemctl start systemd-timesyncd.service
# timedatectl set-ntp true
```

Notes:

some versions of systemd have been compiled without systemd-timesycnd. On these distributions, chrony or NTP should be used instead of systemd-timesycnd.

Not all options are avalible on all versions of systemd-timesyncd

CIS Controls:

Version 6

6.1 <u>Use At Least Two Synchronized Time Sources For All Servers And Network</u> Equipment

Include at least two synchronized time sources from which all servers and network equipment retrieve time information on a regular basis so that timestamps in logs are consistent.

Version 7

6.1 <u>Utilize Three Synchronized Time Sources</u>

Use at least three synchronized time sources from which all servers and network devices retrieve time information on a regular basis so that timestamps in logs are consistent.

2.2.2 Ensure X Window System is not installed (Scored)

Profile Applicability:

• Level 1 - Server

Description:

The X Window System provides a Graphical User Interface (GUI) where users can have multiple windows in which to run programs and various add on. The X Windows system is typically used on workstations where users login, but not on servers where users typically do not login.

Rationale:

Unless your organization specifically requires graphical login access via X Windows, remove it to reduce the potential attack surface.

Audit:

Verify X Windows System is not installed. Depending on the package management in use one of the following commands may provide the needed information:

```
rpm -qa xorg-x11*

dpkg -l xserver-xorg*
```

Remove the X Windows System packages using the appropriate package manager or manual installation:

```
yum remove xorg-x11*

apt-get remove xserver-xorg*

zypper remove xorg-x11*
```

Impact:

Many Linux systems run applications which require a Java runtime. Some Linux Java packages have a dependency on specific X Windows xorg-x11-fonts. One workaround to avoid this dependency is to use the "headless" Java packages for your specific Java runtime, if provided by your distribution.

CIS Controls:

Version 6

2 <u>Inventory of Authorized and Unauthorized Software</u> Inventory of Authorized and Unauthorized Software

Version 7

2.6 Address unapproved software

Ensure that unauthorized software is either removed or the inventory is updated in a timely manner

2.2.3 Ensure Avahi Server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Avahi is a free zeroconf implementation, including a system for multicast DNS/DNS-SD service discovery. Avahi allows programs to publish and discover services and hosts running on a local network with no specific configuration. For example, a user can plug a computer into a network and Avahi automatically finds printers to print to, files to look at and people to talk to, as well as network services running on the machine.

Rationale:

Automatic discovery of network services is not normally required for system functionality. It is recommended to disable the service to reduce the potential attack surface.

Audit:

Run one of the following commands to verify avahi-daemon is not enabled:

```
# chkconfig --list avahi-daemon avahi-daemon 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or avahi-daemon is not available.

```
# systemctl is-enabled avahi-daemon disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep avahi-daemon
```

Run one of the following commands to disable avahi-daemon:

```
# chkconfig avahi-daemon off

# systemctl disable avahi-daemon

# update-rc.d avahi-daemon disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.4 Ensure CUPS is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 2 Workstation

Description:

The Common Unix Print System (CUPS) provides the ability to print to both local and network printers. A system running CUPS can also accept print jobs from remote systems and print them to local printers. It also provides a web based remote administration capability.

Rationale:

If the system does not need to print jobs or accept print jobs from other systems, it is recommended that CUPS be disabled to reduce the potential attack surface.

Audit:

Run one of the following commands to verify cups is not enabled:

```
# chkconfig --list cups
cups 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or cups is not available.

```
# systemctl is-enabled cups
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep cups
```

Run one of the following commands to disable cups:

```
# chkconfig cups off

# systemctl disable cups

# update-rc.d cups disable
```

Impact:

Disabling CUPS will prevent printing from the system, a common task for workstation systems.

References:

1. More detailed documentation on CUPS is available at the project homepage at http://www.cups.org.

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.5 Ensure DHCP Server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Dynamic Host Configuration Protocol (DHCP) is a service that allows machines to be dynamically assigned IP addresses.

Rationale:

Unless a system is specifically set up to act as a DHCP server, it is recommended that this service be deleted to reduce the potential attack surface.

Audit:

Run one of the following commands to verify dhepd is not enabled:

```
# chkconfig --list dhcpd
dhcpd 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or dhopd is not available.

```
# systemctl is-enabled dhcpd
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep dhcpd
```

Run one of the following commands to disable dhcpd:

```
# chkconfig dhcpd off

# systemctl disable dhcpd

# update-rc.d dhcpd disable
```

References:

1. More detailed documentation on DHCP is available at http://www.isc.org/software/dhcp.

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.6 Ensure LDAP server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Lightweight Directory Access Protocol (LDAP) was introduced as a replacement for NIS/YP. It is a service that provides a method for looking up information from a central database.

Rationale:

If the system will not need to act as an LDAP server, it is recommended that the software be disabled to reduce the potential attack surface.

Audit:

Run one of the following commands to verify slapd is not enabled:

```
# chkconfig --list slapd
slapd
0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or slapd is not available.

```
# systemctl is-enabled slapd
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep slapd
```

Run one of the following commands to disable slapd:

```
# chkconfig slapd off

# systemctl disable slapd

# update-rc.d slapd disable
```

References:

1. For more detailed documentation on OpenLDAP, go to the project homepage at http://www.openldap.org.

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.7 Ensure NFS and RPC are not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Network File System (NFS) is one of the first and most widely distributed file systems in the UNIX environment. It provides the ability for systems to mount file systems of other servers through the network.

Rationale:

If the system does not export NFS shares or act as an NFS client, it is recommended that these services be disabled to reduce the remote attack surface.

Audit:

Run one of the following commands to verify nfs is not enabled:

```
# chkconfig --list nfs
nfs
0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or nfs is not available.

```
# systemctl is-enabled nfs
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep nfs
```

Verify no S* lines are returned.

Run one of the following commands to verify rpcbind is not enabled:

```
# chkconfig --list rpcbind
autofs 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or rpcbind is not available.

```
# systemctl is-enabled rpcbind
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep rpcbind
```

Run one of the following commands to disable nfs and rpcbind:

```
# chkconfig nfs off
# chkconfig rpcbind off

# systemctl disable nfs
# systemctl disable rpcbind

# update-rc.d nfs disable
# update-rc.d rpcbind disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.8 Ensure DNS Server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Domain Name System (DNS) is a hierarchical naming system that maps names to IP addresses for computers, services and other resources connected to a network.

Rationale:

Unless a system is specifically designated to act as a DNS server, it is recommended that the package be deleted to reduce the potential attack surface.

Audit:

Run one of the following commands to verify named is not enabled:

```
# chkconfig --list named
named 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or named is not available.

```
# systemctl is-enabled named
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep named
```

Run one of the following commands to disable named:

```
# chkconfig named off

# systemctl disable named

# update-rc.d named disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.9 Ensure FTP Server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The File Transfer Protocol (FTP) provides networked computers with the ability to transfer files.

Rationale:

FTP does not protect the confidentiality of data or authentication credentials. It is recommended SFTP be used if file transfer is required. Unless there is a need to run the system as a FTP server (for example, to allow anonymous downloads), it is recommended that the package be deleted to reduce the potential attack surface.

Audit:

Run one of the following commands to verify vsftpd is not enabled:

```
# chkconfig --list vsftpd
vsftpd 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or vsftpd is not available.

```
# systemctl is-enabled vsftpd
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep vsftpd
```

Run one of the following commands to disable vsftpd:

```
# chkconfig vsftpd off

# systemctl disable vsftpd

# update-rc.d vsftpd disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

Additional FTP servers also exist and should be audited.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.10 Ensure HTTP server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

HTTP or web servers provide the ability to host web site content.

Rationale:

Unless there is a need to run the system as a web server, it is recommended that the package be deleted to reduce the potential attack surface.

Audit:

Run one of the following commands to verify httpd is not enabled:

```
# chkconfig --list httpd
httpd 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or httpd is not available.

```
# systemctl is-enabled httpd
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep httpd
```

Run one of the following commands to disable httpd:

```
# chkconfig httpd off

# systemctl disable httpd

# update-rc.d httpd disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

Several httpd servers exist and can use other service names. apache, apache2, lighttpd, and nginx are example services that provide an HTTP server. These and other services should also be audited.

CIS Controls:

Version 6

9.1 <u>Limit Open Ports, Protocols, and Services</u>

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.11 Ensure IMAP and POP3 server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

dovecot is an open source IMAP and POP3 server for Linux based systems.

Rationale:

Unless POP3 and/or IMAP servers are to be provided by this system, it is recommended that the service be deleted to reduce the potential attack surface.

Audit:

Run one of the following commands to verify dovecot is not enabled:

```
# chkconfig --list dovecot
dovecot 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or dovecot is not available.

```
# systemctl is-enabled dovecot
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep dovecot
```

Run one of the following commands to disable dovecot:

```
# chkconfig dovecot off

# systemctl disable dovecot

# update-rc.d dovecot disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

Several IMAP/POP3 servers exist and can use other service names. courier-imap and cyrus-imap are example services that provide a mail server. These and other services should also be audited.

CIS Controls:

Version 6

9.1 <u>Limit Open Ports, Protocols, and Services</u>

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.12 Ensure Samba is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Samba daemon allows system administrators to configure their Linux systems to share file systems and directories with Windows desktops. Samba will advertise the file systems and directories via the Server Message Block (SMB) protocol. Windows desktop users will be able to mount these directories and file systems as letter drives on their systems.

Rationale:

If there is no need to mount directories and file systems to Windows systems, then this service can be deleted to reduce the potential attack surface.

Audit:

Run one of the following commands to verify smb is not enabled:

```
# chkconfig --list smb 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or smb is not available.

```
# systemctl is-enabled smb
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep smb
```

Run one of the following commands to disable smb:

```
# chkconfig smb off

# systemctl disable smb

# update-rc.d smb disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

On some distributions the samba service is known as samba, not smb.

CIS Controls:

Version 6

9.1 <u>Limit Open Ports, Protocols, and Services</u>

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.13 Ensure HTTP Proxy Server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Squid is a standard proxy server used in many distributions and environments.

Rationale:

If there is no need for a proxy server, it is recommended that the squid proxy be deleted to reduce the potential attack surface.

Audit:

Run one of the following commands to verify squid is not enabled:

```
# chkconfig --list squid
squid 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or squid is not available.

```
# systemctl is-enabled squid
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep squid
```

Run one of the following commands to disable squid:

```
# chkconfig squid off

# systemctl disable squid

# update-rc.d squid disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

On some distributions the squid service is known as squid3, not squid. Several HTTP proxy servers exist. These and other services should be checked.

CIS Controls:

Version 6

9.1 <u>Limit Open Ports, Protocols, and Services</u>

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.14 Ensure SNMP Server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Simple Network Management Protocol (SNMP) server is used to listen for SNMP commands from an SNMP management system, execute the commands or collect the information and then send results back to the requesting system.

Rationale:

The SNMP server can communicate using SNMP v1, which transmits data in the clear and does not require authentication to execute commands. Unless absolutely necessary, it is recommended that the SNMP service not be used. If SNMP is required the server should be configured to disallow SNMP v1.

Audit:

Run one of the following commands to verify snmpd is not enabled:

```
# chkconfig --list snmpd
snmpd
0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or snmpd is not available.

```
# systemctl is-enabled snmpd
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep snmpd
```

Run one of the following commands to disable snmpd:

```
# chkconfig snmpd off

# systemctl disable snmpd

# update-rc.d snmpd disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.15 Ensure mail transfer agent is configured for local-only mode (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Mail Transfer Agents (MTA), such as sendmail and Postfix, are used to listen for incoming mail and transfer the messages to the appropriate user or mail server. If the system is not intended to be a mail server, it is recommended that the MTA be configured to only process local mail.

Rationale:

The software for all Mail Transfer Agents is complex and most have a long history of security issues. While it is important to ensure that the system can process local mail messages, it is not necessary to have the MTA's daemon listening on a port unless the server is intended to be a mail server that receives and processes mail from other systems.

Audit:

Run the following command to verify that the MTA is not listening on any non-loopback address (127.0.0.1 or ::1) Nothing should be returned

```
# ss -lntu | grep -E ':25\s' | grep -E -v '\s(127.0.0.1|::1):25\s'
```

Edit /etc/postfix/main.cf and add the following line to the RECEIVING MAIL section. If the line already exists, change it to look like the line below:

inet interfaces = loopback-only

Restart postfix with one of the following commands:

systemctl restart postfix

OR

service postfix restart

Notes:

This recommendation is designed around the postfix mail server, depending on your environment you may have an alternative MTA installed such as sendmail. If this is the case consult the documentation for your installed MTA to configure the recommended state.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.16 Ensure rsync service is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The rsyncd service can be used to synchronize files between systems over network links.

Rationale:

The rsyncd service presents a security risk as it uses unencrypted protocols for communication.

Audit:

Run one of the following commands to verify rsyncd is not enabled:

```
# chkconfig --list rsyncd
rsyncd
0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or rsyncd is not available.

```
# systemctl is-enabled rsyncd
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep rsyncd
```

Run one of the following commands to disable rsyncd:

```
# chkconfig rsyncd off

# systemctl disable rsyncd

# update-rc.d rsyncd disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

On some distributions the rsync service is known as rsync, not rsyncd.

CIS Controls:

Version 6

9.1 <u>Limit Open Ports, Protocols, and Services</u>

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.2.17 Ensure NIS Server is not enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Network Information Service (NIS) (formally known as Yellow Pages) is a client-server directory service protocol for distributing system configuration files. The NIS server is a collection of programs that allow for the distribution of configuration files.

Rationale:

The NIS service is inherently an insecure system that has been vulnerable to DOS attacks, buffer overflows and has poor authentication for querying NIS maps. NIS generally has been replaced by such protocols as Lightweight Directory Access Protocol (LDAP). It is recommended that the service be disabled and other, more secure services be used

Audit:

Run one of the following commands to verify ypserv is not enabled:

```
# chkconfig --list ypserv
ypserv 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

Verify all runlevels are listed as "off" or ypserv is not available.

```
# systemctl is-enabled ypserv
disabled
```

Verify result is not "enabled".

```
# ls /etc/rc*.d | grep ypserv
```

Run one of the following commands to disable ypserv:

```
# chkconfig ypserv off

# systemctl disable ypserv

# update-rc.d ypserv disable
```

Notes:

Additional methods of disabling a service exist. Consult your distribution documentation for appropriate methods.

On some distributions the NIS service is known as nis, not ypserv.

CIS Controls:

Version 6

9.1 <u>Limit Open Ports, Protocols, and Services</u>

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

2.3 Service Clients

A number of insecure services exist. While disabling the servers prevents a local attack against these services, it is advised to remove their clients unless they are required.

Note: This should not be considered a comprehensive list of insecure service clients. You may wish to consider additions to those listed here for your environment.

2.3.1 Ensure NIS Client is not installed (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Network Information Service (NIS), formerly known as Yellow Pages, is a client-server directory service protocol used to distribute system configuration files. The NIS client (ypbind) was used to bind a machine to an NIS server and receive the distributed configuration files.

Rationale:

The NIS service is inherently an insecure system that has been vulnerable to DOS attacks, buffer overflows and has poor authentication for querying NIS maps. NIS generally has been replaced by such protocols as Lightweight Directory Access Protocol (LDAP). It is recommended that the service be removed.

Audit:

Verify ypbind is not installed. Depending on the package management in use one of the following commands may provide the needed information:

rpm -q ypbind
dpkg -s ypbind

Uninstall ypbind using the appropriate package manager or manual installation:

```
yum remove ypbind

apt-get remove ypbind

zypper remove ypbind
```

Impact:

Many insecure service clients are used as troubleshooting tools and in testing environments. Uninstalling them can inhibit capability to test and troubleshoot. If they are required it is advisable to remove the clients after use to prevent accidental or intentional misuse.

CIS Controls:

Version 6

2 <u>Inventory of Authorized and Unauthorized Software</u> Inventory of Authorized and Unauthorized Software

Version 7

2.6 Address unapproved software

Ensure that unauthorized software is either removed or the inventory is updated in a timely manner

2.3.2 Ensure rsh client is not installed (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The rsh package contains the client commands for the rsh services.

Rationale:

These legacy clients contain numerous security exposures and have been replaced with the more secure SSH package. Even if the server is removed, it is best to ensure the clients are also removed to prevent users from inadvertently attempting to use these commands and therefore exposing their credentials. Note that removing the ${\tt rsh}$ package removes the clients for ${\tt rsh}$, ${\tt rcp}$ and ${\tt rlogin}$.

Audit:

Verify rsh is not installed. Depending on the package management in use one of the following commands may provide the needed information:

```
rpm -q rsh
dpkg -s rsh
```

Uninstall rsh using the appropriate package manager or manual installation:

```
yum remove rsh
apt-get remove rsh
zypper remove rsh
```

Impact:

Many insecure service clients are used as troubleshooting tools and in testing environments. Uninstalling them can inhibit capability to test and troubleshoot. If they are required it is advisable to remove the clients after use to prevent accidental or intentional misuse.

CIS Controls:

Version 6

3.4 Use Only Secure Channels For Remote System Administration

Perform all remote administration of servers, workstation, network devices, and similar equipment over secure channels. Protocols such as telnet, VNC, RDP, or others that do not actively support strong encryption should only be used if they are performed over a secondary encryption channel, such as SSL, TLS or IPSEC.

Version 7

4.5 <u>Use Multifactor Authentication For All Administrative Access</u>

Use multi-factor authentication and encrypted channels for all administrative account access.

2.3.3 Ensure talk client is not installed (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The talk software makes it possible for users to send and receive messages across systems through a terminal session. The talk client, which allows initialization of talk sessions, is installed by default.

Rationale:

The software presents a security risk as it uses unencrypted protocols for communication.

Audit:

Verify talk is not installed. Depending on the package management in use one of the following commands may provide the needed information:

```
rpm -q talk
dpkg -s talk
```

Uninstall talk using the appropriate package manager or manual installation:

```
yum remove talk
apt-get remove talk
zypper remove talk
```

Impact:

Many insecure service clients are used as troubleshooting tools and in testing environments. Uninstalling them can inhibit capability to test and troubleshoot. If they are required it is advisable to remove the clients after use to prevent accidental or intentional misuse.

CIS Controls:

Version 6

2 <u>Inventory of Authorized and Unauthorized Software</u> Inventory of Authorized and Unauthorized Software

Version 7

2.6 Address unapproved software

Ensure that unauthorized software is either removed or the inventory is updated in a timely manner

2.3.4 Ensure telnet client is not installed (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The telnet package contains the telnet client, which allows users to start connections to other systems via the telnet protocol.

Rationale:

The telnet protocol is insecure and unencrypted. The use of an unencrypted transmission medium could allow an unauthorized user to steal credentials. The ssh package provides an encrypted session and stronger security and is included in most Linux distributions.

Audit:

Verify telnet is not installed. Depending on the package management in use one of the following commands may provide the needed information:

```
# rpm -q telnet
# dpkg -s telnet
```

Uninstall telnet using the appropriate package manager or manual installation:

```
# yum remove telnet
# apt-get remove telnet
# zypper remove telnet
```

Impact:

Many insecure service clients are used as troubleshooting tools and in testing environments. Uninstalling them can inhibit capability to test and troubleshoot. If they are required it is advisable to remove the clients after use to prevent accidental or intentional misuse.

CIS Controls:

Version 6

3.4 <u>Use Only Secure Channels For Remote System Administration</u>

Perform all remote administration of servers, workstation, network devices, and similar equipment over secure channels. Protocols such as telnet, VNC, RDP, or others that do not actively support strong encryption should only be used if they are performed over a secondary encryption channel, such as SSL, TLS or IPSEC.

Version 7

4.5 <u>Use Multifactor Authentication For All Administrative Access</u>

Use multi-factor authentication and encrypted channels for all administrative account access.

2.3.5 Ensure LDAP client is not installed (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Lightweight Directory Access Protocol (LDAP) was introduced as a replacement for NIS/YP. It is a service that provides a method for looking up information from a central database.

Rationale:

If the system will not need to act as an LDAP client, it is recommended that the software be removed to reduce the potential attack surface.

Audit:

Verify openIdap-clients is not installed. Depending on the package management in use one of the following commands may provide the needed information:

```
# rpm -q openldap-clients
# dpkg -s openldap-clients
```

Uninstall openldap-clients using the appropriate package manager or manual installation:

```
# yum remove openIdap-clients
# apt-get remove openIdap-clients
# zypper remove openIdap-clients
```

Impact:

Removing the LDAP client will prevent or inhibit using LDAP for authentication in your environment.

Notes:

The openIdap-clients package can go by other names on some distributions. openIdap2-client, and Idap-utils are known alternative package names.

CIS Controls:

Version 6

2 <u>Inventory of Authorized and Unauthorized Software</u> Inventory of Authorized and Unauthorized Software

Version 7

2.6 Address unapproved software

Ensure that unauthorized software is either removed or the inventory is updated in a timely manner

3 Network Configuration

This section provides guidance on for securing the network configuration of the system through kernel parameters, access list control, and firewall settings.

3.1 Network Parameters (Host Only)

The following network parameters are intended for use if the system is to act as a host only. A system is considered host only if the system has a single interface, or has multiple interfaces but will not be configured as a router.

3.1.1 Ensure IP forwarding is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The net.ipv4.ip_forward and net.ipv6.conf.all.forwarding flags are used to tell the system whether it can forward packets or not.

Rationale:

Setting the flags to 0 ensures that a system with multiple interfaces (for example, a hard proxy), will never be able to forward packets, and therefore, never serve as a router.

Audit:

```
# sysctl net.ipv4.ip_forward
net.ipv4.ip_forward = 0

# grep "net\.ipv4\.ip_forward" /etc/sysctl.conf /etc/sysctl.d/*
net.ipv4.ip_forward = 0

# sysctl net.ipv6.conf.all.forwarding
net.ipv6.conf.all.forwarding = 0

# grep "net\.ipv6\.conf\.all\.forwarding" /etc/sysctl.conf /etc/sysctl.d/*
net.ipv6.conf.all.forwarding = 0
```

Set the following parameter in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.ip_forward = 0
net.ipv6.conf.all.forwarding = 0
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.ip_forward=0
# sysctl -w net.ipv6.conf.all.forwarding=0
# sysctl -w net.ipv4.route.flush=1
# sysctl -w net.ipv6.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers</u>

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 Establish Secure Configurations

3.1.2 Ensure packet redirect sending is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

ICMP Redirects are used to send routing information to other hosts. As a host itself does not act as a router (in a host only configuration), there is no need to send redirects.

Rationale:

An attacker could use a compromised host to send invalid ICMP redirects to other router devices in an attempt to corrupt routing and have users access a system set up by the attacker as opposed to a valid system.

Audit:

```
# sysctl net.ipv4.conf.all.send_redirects
net.ipv4.conf.all.send_redirects = 0

# sysctl net.ipv4.conf.default.send_redirects
net.ipv4.conf.default.send_redirects = 0

# grep "net\.ipv4\.conf\.all\.send_redirects" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.all.send_redirects = 0

# grep "net\.ipv4\.conf\.default\.send_redirects" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.default.send_redirects = 0
```

Set the following parameters in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.conf.all.send_redirects = 0
net.ipv4.conf.default.send_redirects = 0
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.conf.all.send_redirects=0
# sysctl -w net.ipv4.conf.default.send_redirects=0
# sysctl -w net.ipv4.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers</u>

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 <u>Establish Secure Configurations</u>

3.2 Network Parameters (Host and Router)

The following network parameters are intended for use on both host only and router systems. A system acts as a router if it has at least two interfaces and is configured to perform routing functions.

3.2.1 Ensure source routed packets are not accepted (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

In networking, source routing allows a sender to partially or fully specify the route packets take through a network. In contrast, non-source routed packets travel a path determined by routers in the network. In some cases, systems may not be routable or reachable from some locations (e.g. private addresses vs. Internet routable), and so source routed packets would need to be used.

Rationale:

```
Setting net.ipv4.conf.all.accept_source_route, net.ipv4.conf.default.accept_source_route, net.ipv6.conf.all.accept_source_route and
```

net.ipv6.conf.default.accept_source_route to 0 disables the system from accepting source routed packets. Assume this system was capable of routing packets to Internet routable addresses on one interface and private addresses on another interface. Assume that the private addresses were not routable to the Internet routable addresses and vice versa. Under normal routing circumstances, an attacker from the Internet routable addresses could not use the system as a way to reach the private address systems. If, however, source routed packets were allowed, they could be used to gain access to the private address systems as the route could be specified, rather than rely on routing protocols that did not allow this routing.

Audit:

```
# sysctl net.ipv4.conf.all.accept source route
net.ipv4.conf.all.accept source route = 0
# sysctl net.ipv4.conf.default.accept source route
net.ipv4.conf.default.accept source route = 0
# grep "net\.ipv4\.conf\.all\.accept source route" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.all.accept source route= 0
# grep "net\.ipv4\.conf\.default\.accept source route" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.default.accept source route= 0
# sysctl net.ipv6.conf.all.accept source route
net.ipv6.conf.all.accept source route = 0
# sysctl net.ipv6.conf.default.accept source route
net.ipv6.conf.default.accept source route = 0
# grep "net\.ipv6\.conf\.all\.accept source route" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.all.accept source route= 0
# grep "net\.ipv6\.conf\.default\.accept source route" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv6.conf.default.accept source route= 0
```

Set the following parameters in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.conf.all.accept source route = 0
net.ipv4.conf.default.accept_source_route = 0
net.ipv6.conf.all.accept_source_route = 0
net.ipv6.conf.default.accept_source_route = 0
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.conf.all.accept_source_route=0
# sysctl -w net.ipv4.conf.default.accept_source_route=0
# sysctl -w net.ipv6.conf.all.accept_source_route=0
# sysctl -w net.ipv6.conf.default.accept_source_route=0
# sysctl -w net.ipv4.route.flush=1
# sysctl -w net.ipv6.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers</u>

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 Establish Secure Configurations

3.2.2 Ensure ICMP redirects are not accepted (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

ICMP redirect messages are packets that convey routing information and tell your host (acting as a router) to send packets via an alternate path. It is a way of allowing an outside routing device to update your system routing tables. By setting

net.ipv4.conf.all.accept_redirects and net.ipv6.conf.all.accept_redirects to 0, the system will not accept any ICMP redirect messages, and therefore, won't allow outsiders to update the system's routing tables.

Rationale:

Attackers could use bogus ICMP redirect messages to maliciously alter the system routing tables and get them to send packets to incorrect networks and allow your system packets to be captured.

Audit:

```
# sysctl net.ipv4.conf.all.accept redirects
net.ipv4.conf.all.accept redirects = 0
# sysctl net.ipv4.conf.default.accept redirects
net.ipv4.conf.default.accept redirects = 0
# grep "net\.ipv4\.conf\.all\.accept redirects" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.all.accept redirects= 0
# grep "net\.ipv4\.conf\.default\.accept redirects" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.default.accept redirects= 0
# sysctl net.ipv6.conf.all.accept redirects
net.ipv6.conf.all.accept redirects = 0
# sysctl net.ipv6.conf.default.accept redirects
net.ipv6.conf.default.accept redirects = 0
# grep "net\.ipv6\.conf\.all\.accept redirects" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv6.conf.all.accept redirects= 0
# grep "net\.ipv6\.conf\.default\.accept redirects" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv6.conf.default.accept redirects= 0
```

Set the following parameters in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.conf.all.accept redirects = 0
net.ipv4.conf.default.accept_redirects = 0
net.ipv6.conf.all.accept_redirects = 0
net.ipv6.conf.default.accept_redirects = 0
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.conf.all.accept_redirects=0
# sysctl -w net.ipv4.conf.default.accept_redirects=0
# sysctl -w net.ipv6.conf.all.accept_redirects=0
# sysctl -w net.ipv6.conf.default.accept_redirects=0
# sysctl -w net.ipv4.route.flush=1
# sysctl -w net.ipv6.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers</u>

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 Establish Secure Configurations

3.2.3 Ensure secure ICMP redirects are not accepted (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Secure ICMP redirects are the same as ICMP redirects, except they come from gateways listed on the default gateway list. It is assumed that these gateways are known to your system, and that they are likely to be secure.

Rationale:

It is still possible for even known gateways to be compromised. Setting net.ipv4.conf.all.secure_redirects to 0 protects the system from routing table updates by possibly compromised known gateways.

Audit:

```
# sysctl net.ipv4.conf.all.secure_redirects
net.ipv4.conf.all.secure_redirects = 0

# sysctl net.ipv4.conf.default.secure_redirects
net.ipv4.conf.default.secure_redirects = 0

# grep "net\.ipv4\.conf\.all\.secure_redirects" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.all.secure_redirects= 0

# grep "net\.ipv4\.conf\.default\.secure_redirects" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.default.secure_redirects= 0
```

Set the following parameters in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.conf.all.secure_redirects = 0
net.ipv4.conf.default.secure_redirects = 0
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.conf.all.secure_redirects=0
# sysctl -w net.ipv4.conf.default.secure_redirects=0
# sysctl -w net.ipv4.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers</u>

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 <u>Establish Secure Configurations</u>

3.2.4 Ensure suspicious packets are logged (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

When enabled, this feature logs packets with un-routable source addresses to the kernel log.

Rationale:

Enabling this feature and logging these packets allows an administrator to investigate the possibility that an attacker is sending spoofed packets to their system.

Audit:

```
# sysctl net.ipv4.conf.all.log_martians
net.ipv4.conf.all.log_martians = 1

# sysctl net.ipv4.conf.default.log_martians
net.ipv4.conf.default.log_martians = 1

# grep "net\.ipv4\.conf\.all\.log_martians" /etc/sysctl.conf /etc/sysctl.d/*
net.ipv4.conf.all.log_martians = 1

# grep "net\.ipv4\.conf\.default\.log_martians" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.conf.default.log_martians = 1
```

Set the following parameters in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.conf.all.log_martians = 1
net.ipv4.conf.default.log_martians = 1
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.conf.all.log_martians=1
# sysctl -w net.ipv4.conf.default.log_martians=1
# sysctl -w net.ipv4.route.flush=1
```

CIS Controls:

Version 6

6 Maintenance, Monitoring, and Analysis of Audit Logs

Maintenance, Monitoring, and Analysis of Audit Logs

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

3.2.5 Ensure broadcast ICMP requests are ignored (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Setting net.ipv4.icmp_echo_ignore_broadcasts to 1 will cause the system to ignore all ICMP echo and timestamp requests to broadcast and multicast addresses.

Rationale:

Accepting ICMP echo and timestamp requests with broadcast or multicast destinations for your network could be used to trick your host into starting (or participating) in a Smurf attack. A Smurf attack relies on an attacker sending large amounts of ICMP broadcast messages with a spoofed source address. All hosts receiving this message and responding would send echo-reply messages back to the spoofed address, which is probably not routable. If many hosts respond to the packets, the amount of traffic on the network could be significantly multiplied.

Audit:

```
# sysctl net.ipv4.icmp_echo_ignore_broadcasts
net.ipv4.icmp_echo_ignore_broadcasts = 1

# grep "net\.ipv4\.icmp_echo_ignore_broadcasts" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.icmp_echo_ignore_broadcasts = 1
```

Set the following parameters in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.icmp_echo_ignore_broadcasts = 1
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.icmp_echo_ignore_broadcasts=1
# sysctl -w net.ipv4.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops,</u> Workstations, and Servers

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 Establish Secure Configurations

3.2.6 Ensure bogus ICMP responses are ignored (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Setting <code>icmp_ignore_bogus_error_responses</code> to 1 prevents the kernel from logging bogus responses (RFC-1122 non-compliant) from broadcast reframes, keeping file systems from filling up with useless log messages.

Rationale:

Some routers (and some attackers) will send responses that violate RFC-1122 and attempt to fill up a log file system with many useless error messages.

Audit:

```
# sysctl net.ipv4.icmp_ignore_bogus_error_responses
net.ipv4.icmp_ignore_bogus_error_responses = 1
# grep "net.ipv4.icmp_ignore_bogus_error_responses" /etc/sysctl.conf
/etc/sysctl.d/*
net.ipv4.icmp_ignore_bogus_error_responses = 1
```

Set the following parameter in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.icmp_ignore_bogus_error_responses = 1
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.icmp_ignore_bogus_error_responses=1
# sysctl -w net.ipv4.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops,</u> Workstations, and Servers

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 Establish Secure Configurations

3.2.7 Ensure Reverse Path Filtering is enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Setting net.ipv4.conf.all.rp_filter and net.ipv4.conf.default.rp_filter to 1 forces the Linux kernel to utilize reverse path filtering on a received packet to determine if the packet was valid. Essentially, with reverse path filtering, if the return packet does not go out the same interface that the corresponding source packet came from, the packet is dropped (and logged if log martians is set).

Rationale:

Setting these flags is a good way to deter attackers from sending your system bogus packets that cannot be responded to. One instance where this feature breaks down is if asymmetrical routing is employed. This would occur when using dynamic routing protocols (bgp, ospf, etc) on your system. If you are using asymmetrical routing on your system, you will not be able to enable this feature without breaking the routing.

Audit:

```
# sysctl net.ipv4.conf.all.rp_filter
net.ipv4.conf.all.rp_filter = 1

# sysctl net.ipv4.conf.default.rp_filter
net.ipv4.conf.default.rp_filter = 1

# grep "net\.ipv4\.conf\.all\.rp_filter" /etc/sysctl.conf /etc/sysctl.d/*
net.ipv4.conf.all.rp_filter = 1

# grep "net\.ipv4\.conf\.default\.rp_filter" /etc/sysctl.conf /etc/sysctl.d/*
net.ipv4.conf.default\.rp_filter = 1
```

Set the following parameters in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.conf.all.rp_filter = 1
net.ipv4.conf.default.rp_filter = 1
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.conf.all.rp_filter=1
# sysctl -w net.ipv4.conf.default.rp_filter=1
# sysctl -w net.ipv4.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers</u>

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 <u>Establish Secure Configurations</u>

3.2.8 Ensure TCP SYN Cookies is enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

When tcp_syncookies is set, the kernel will handle TCP SYN packets normally until the half-open connection queue is full, at which time, the SYN cookie functionality kicks in. SYN cookies work by not using the SYN queue at all. Instead, the kernel simply replies to the SYN with a SYN|ACK, but will include a specially crafted TCP sequence number that encodes the source and destination IP address and port number and the time the packet was sent. A legitimate connection would send the ACK packet of the three way handshake with the specially crafted sequence number. This allows the system to verify that it has received a valid response to a SYN cookie and allow the connection, even though there is no corresponding SYN in the queue.

Rationale:

Attackers use SYN flood attacks to perform a denial of service attacked on a system by sending many SYN packets without completing the three way handshake. This will quickly use up slots in the kernel's half-open connection queue and prevent legitimate connections from succeeding. SYN cookies allow the system to keep accepting valid connections, even if under a denial of service attack.

Audit:

```
# sysctl net.ipv4.tcp_syncookies
net.ipv4.tcp_syncookies = 1

# grep "net\.ipv4\.tcp_syncookies" /etc/sysctl.conf /etc/sysctl.d/*
net.ipv4.tcp_syncookies = 1
```

Set the following parameters in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv4.tcp_syncookies = 1
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv4.tcp_syncookies=1
# sysctl -w net.ipv4.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops,</u> Workstations, and Servers

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 Establish Secure Configurations

3.2.9 Ensure IPv6 router advertisements are not accepted (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

This setting disables the system's ability to accept IPv6 router advertisements.

Rationale:

It is recommended that systems do not accept router advertisements as they could be tricked into routing traffic to compromised machines. Setting hard routes within the system (usually a single default route to a trusted router) protects the system from bad routes.

Audit:

```
# sysctl net.ipv6.conf.all.accept_ra
net.ipv6.conf.all.accept_ra = 0

# sysctl net.ipv6.conf.default.accept_ra
net.ipv6.conf.default.accept_ra = 0

# grep "net\.ipv6\.conf\.all\.accept_ra" /etc/sysctl.conf /etc/sysctl.d/*
net.ipv6.conf.all.accept_ra = 0

# grep "net\.ipv6\.conf\.default\.accept_ra" /etc/sysctl.conf /etc/sysctl.d/*
net.ipv6.conf.default.accept_ra = 0
```

Set the following parameters in /etc/sysctl.conf or a /etc/sysctl.d/* file:

```
net.ipv6.conf.all.accept_ra = 0
net.ipv6.conf.default.accept_ra = 0
```

Run the following commands to set the active kernel parameters:

```
# sysctl -w net.ipv6.conf.all.accept_ra=0
# sysctl -w net.ipv6.conf.default.accept_ra=0
# sysctl -w net.ipv6.route.flush=1
```

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers</u>

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

5.1 <u>Establish Secure Configurations</u>

3.3 TCP Wrappers

3.3.1 Ensure TCP Wrappers is installed (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Many Linux distributions provide value-added firewall solutions which provide easy, advanced management of network traffic into and out of the local system. When these solutions are available and appropriate for an environment they should be used.

In cases where a value-added firewall is not provided by a distribution, TCP Wrappers provides a simple access list and standardized logging method for services capable of supporting it. Services that are called from <code>inetd</code> and <code>xinetd</code> support the use of TCP wrappers. Any service that can support TCP wrappers will have the <code>libwrap.so</code> library attached to it.

Rationale:

TCP Wrappers provide a good simple access list mechanism to services that may not have that support built in. It is recommended that all services that can support TCP Wrappers, use it.

Audit:

Run the following command and verify TCP Wrappers is installed:

```
# rpm -q tcp_wrappers
# dpkg -s tcpd
```

Run the following command to install TCP Wrappers:

```
# yum install tcp_wrappers
# apt-get install tcpd
# zypper install tcpd
```

Impact:

Some Linux distributions have deprecated the use of TCP Wrappers in favor of value-added firewall solutions. In these cases the provided firewall solution should be used.

Notes:

To verify if a service supports TCP Wrappers, run the following command:

```
# ldd <path-to-daemon> | grep libwrap.so
```

If there is any output, then the service supports TCP Wrappers.

CIS Controls:

Version 6

9.2 <u>Leverage Host-based Firewalls</u>

Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.

3.3.2 Ensure /etc/hosts.allow is configured (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/hosts.allow file specifies which IP addresses are permitted to connect to the host. It is intended to be used in conjunction with the /etc/hosts.deny file.

Rationale:

The /etc/hosts.allow file supports access control by IP and helps ensure that only authorized systems can connect to the system.

Audit:

Run the following command and verify the contents of the /etc/hosts.allow file:

cat /etc/hosts.allow

Run the following command to create /etc/hosts.allow:

```
# echo "ALL: <net>/<mask>, <net>/<mask>, ..." >/etc/hosts.allow
```

where each <net>/<mask> combination (for example, "192.168.1.0/255.255.255.0") represents one network block in use by your organization that requires access to this system.

Notes:

Contents of the /etc/hosts.allow file will vary depending on your network configuration.

CIS Controls:

Version 6

9.2 Leverage Host-based Firewalls

Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

3.3.3 Ensure /etc/hosts.deny is configured (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/hosts.deny file specifies which IP addresses are **not** permitted to connect to the host. It is intended to be used in conjunction with the /etc/hosts.allow file.

Rationale:

The /etc/hosts.deny file serves as a failsafe so that any host not specified in /etc/hosts.allow is denied access to the system.

Audit:

Run the following command and verify the contents of the /etc/hosts.deny file:

cat /etc/hosts.deny
ALL: ALL

Run the following command to create /etc/hosts.deny:

echo "ALL: ALL" >> /etc/hosts.deny

Notes:

Contents of the /etc/hosts.deny file may include additional options depending on your network configuration.

CIS Controls:

Version 6

9.2 <u>Leverage Host-based Firewalls</u>

Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

3.3.4 Ensure permissions on /etc/hosts.allow are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/hosts.allow file contains networking information that is used by many applications and therefore must be readable for these applications to operate.

Rationale:

It is critical to ensure that the /etc/hosts.allow file is protected from unauthorized write access. Although it is protected by default, the file permissions could be changed either inadvertently or through malicious actions.

Audit:

Run the following command and verify Uid and Gid are both O/root and Access is 644:

```
# stat /etc/hosts.allow
Access: (0644/-rw-r--r--) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to set permissions on /etc/hosts.allow:

```
# chown root:root /etc/hosts.allow
# chmod 644 /etc/hosts.allow
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

3.3.5 Ensure permissions on /etc/hosts.deny are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/hosts.deny file contains network information that is used by many system applications and therefore must be readable for these applications to operate.

Rationale:

It is critical to ensure that the /etc/hosts.deny file is protected from unauthorized write access. Although it is protected by default, the file permissions could be changed either inadvertently or through malicious actions.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access is 644:

```
# stat /etc/hosts.deny
Access: (0644/-rw-r--r--) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to set permissions on /etc/hosts.deny:

```
# chown root:root /etc/hosts.deny
# chmod 644 /etc/hosts.deny
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

3.4 Uncommon Network Protocols

The Linux kernel modules support several network protocols that are not commonly used. If these protocols are not needed, it is recommended that they be disabled in the kernel.

Note: This should not be considered a comprehensive list of uncommon network protocols, you may wish to consider additions to those listed here for your environment.

3.4.1 Ensure DCCP is disabled (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The Datagram Congestion Control Protocol (DCCP) is a transport layer protocol that supports streaming media and telephony. DCCP provides a way to gain access to congestion control, without having to do it at the application layer, but does not provide insequence delivery.

Rationale:

If the protocol is not required, it is recommended that the drivers not be installed to reduce the potential attack surface.

Audit:

Run the following commands and verify the output is as indicated:

```
# modprobe -n -v dccp
install /bin/true

# lsmod | grep dccp
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/dccp.conf and add the following line:

install dccp /bin/true

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

3.4.2 Ensure SCTP is disabled (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The Stream Control Transmission Protocol (SCTP) is a transport layer protocol used to support message oriented communication, with several streams of messages in one connection. It serves a similar function as TCP and UDP, incorporating features of both. It is message-oriented like UDP, and ensures reliable in-sequence transport of messages with congestion control like TCP.

Rationale:

If the protocol is not being used, it is recommended that kernel module not be loaded, disabling the service to reduce the potential attack surface.

Audit:

Run the following commands and verify the output is as indicated:

```
# modprobe -n -v sctp
install /bin/true

# lsmod | grep sctp
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/sctp.conf and add the following line:

install sctp /bin/true

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

3.4.3 Ensure RDS is disabled (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The Reliable Datagram Sockets (RDS) protocol is a transport layer protocol designed to provide low-latency, high-bandwidth communications between cluster nodes. It was developed by the Oracle Corporation.

Rationale:

If the protocol is not being used, it is recommended that kernel module not be loaded, disabling the service to reduce the potential attack surface.

Audit:

Run the following commands and verify the output is as indicated:

```
# modprobe -n -v rds
install /bin/true

# lsmod | grep rds
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/rds.conf and add the following line:

install rds /bin/true

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

3.4.4 Ensure TIPC is disabled (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The Transparent Inter-Process Communication (TIPC) protocol is designed to provide communication between cluster nodes.

Rationale:

If the protocol is not being used, it is recommended that kernel module not be loaded, disabling the service to reduce the potential attack surface.

Audit:

Run the following commands and verify the output is as indicated:

```
# modprobe -n -v tipc
install /bin/true

# lsmod | grep tipc
<No output>
```

Edit or create a file in the /etc/modprobe.d/ directory ending in .conf Example: vim /etc/modprobe.d/tipc.conf and add the following line:

install tipc /bin/true

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

3.5 Firewall Configuration

IPtables is an application that allows a system administrator to configure the IPv4 tables, IPv6 tables, chains and rules provided by the Linux kernel firewall. While several methods of configuration exist this section is intended only to ensure the resulting IPtables and rules are in place, not how they are configured. If IPv6 is in use in your environment, similar settings should be applied to the IP6tables as well.

3.5.1 Configure IPv6 ip6tables

Ip6tables is used to set up, maintain, and inspect the tables of IPv6 packet filter rules in the Linux kernel. Several different tables may be defined. Each table contains a number of built-in chains and may also contain user-defined chains. Each chain is a list of rules which can match a set of packets. Each rule specifies what to do with a packet that matches. This is called a `target', which may be a jump to a user-defined chain in the same table.

If IPv6 in enabled on the system, the ip6tables should be configured.

Note: This section broadly assumes starting with an empty ip6tables firewall ruleset (established by flushing the rules with ip6tables -F). Remediation steps included only affect the live system, you will also need to configure your default firewall configuration to apply on boot. Configuration of a live systems firewall directly over a remote connection will often result in being locked out. It is advised to have a known good firewall configuration set to run on boot and to configure an entire firewall structure in a script that is then run and tested before saving to boot. The following script will implement the firewall rules of this section and open port 22(ssh) from anywhere:

```
#!/bin/bash
# Flush ip6tables rules
ip6tables -F
# Ensure default deny firewall policy
ip6tables -P INPUT DROP
ip6tables -P OUTPUT DROP
ip6tables -P FORWARD DROP
# Ensure loopback traffic is configured
ip6tables -A INPUT -i lo -j ACCEPT
ip6tables -A OUTPUT -o lo -j ACCEPT
ip6tables -A INPUT -s ::1 -j DROP
# Ensure outbound and established connections are configured
ip6tables -A OUTPUT -p tcp -m state --state NEW, ESTABLISHED -j ACCEPT
ip6tables -A OUTPUT -p udp -m state --state NEW, ESTABLISHED -j ACCEPT
ip6tables -A OUTPUT -p icmp -m state --state NEW, ESTABLISHED -j ACCEPT
ip6tables -A INPUT -p tcp -m state --state ESTABLISHED -j ACCEPT
ip6tables -A INPUT -p udp -m state --state ESTABLISHED -j ACCEPT
ip6tables -A INPUT -p icmp -m state --state ESTABLISHED -j ACCEPT
# Open inbound ssh(tcp port 22) connections
ip6tables -A INPUT -p tcp --dport 22 -m state --state NEW -j ACCEPT
```

3.5.1.1 Ensure IPv6 default deny firewall policy (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

A default deny all policy on connections ensures that any unconfigured network usage will be rejected.

Rationale:

With a default accept policy the firewall will accept any packet that is not configured to be denied. It is easier to white list acceptable usage than to black list unacceptable usage.

Audit:

Run the following command and verify that the policy for the INPUT, OUTPUT, and FORWARD chains is DROP or REJECT:

```
# ip6tables -L
Chain INPUT (policy DROP)
Chain FORWARD (policy DROP)
Chain OUTPUT (policy DROP)
```

OR

If IPv6 is disabled:

Run the following command and verify that no lines are returned.

```
# grep "^\s*linux" /boot/grub2/grub.cfg | grep -v ipv6.disable=1
```

OR

```
# grep "^\s*linux" /boot/grub/grub.cfg | grep -v ipv6.disable=1
```

Run the following commands to implement a default DROP policy:

```
# ip6tables -P INPUT DROP
# ip6tables -P OUTPUT DROP
# ip6tables -P FORWARD DROP
```

Notes:

Changing firewall settings while connected over network can result in being locked out of the system.

Remediation will only affect the active system firewall, be sure to configure the default policy in your firewall management to apply on boot as well.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

3.5.1.2 Ensure IPv6 loopback traffic is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Configure the loopback interface to accept traffic. Configure all other interfaces to deny traffic to the loopback network (::1).

Rationale:

Loopback traffic is generated between processes on machine and is typically critical to operation of the system. The loopback interface is the only place that loopback network (::1) traffic should be seen, all other interfaces should ignore traffic on this network as an anti-spoofing measure.

Audit:

Run the following commands and verify output includes the listed rules in order (packet and byte counts may differ):

```
# ip6tables -L INPUT -v -n
Chain INPUT (policy DROP 0 packets, 0 bytes)
pkts bytes target prot opt in
                                 out
                                         source
destination
   0 0 ACCEPT
                  all
                           10
                                         ::/0
                                                             ::/0
   0
        0 DROP
                    all
                                         ::1
                                                             ::/0
# ip6tables -L OUTPUT -v -n
Chain OUTPUT (policy DROP 0 packets, 0 bytes)
pkts bytes target prot opt in
                                         source
destination
      0 ACCEPT
                   all *
                                 10
                                          ::/0
                                                             ::/0
```

OR

If IPv6 is disabled:

Run the following command and verify that no lines are returned.

```
# grep "^\s*linux" /boot/grub2/grub.cfg | grep -v ipv6.disable=1
```

OR

```
# grep "^\s*linux" /boot/grub/grub.cfg | grep -v ipv6.disable=1
```

Run the following commands to implement the loopback rules:

```
# ip6tables -A INPUT -i lo -j ACCEPT
# ip6tables -A OUTPUT -o lo -j ACCEPT
# ip6tables -A INPUT -s ::1 -j DROP
```

Notes:

Changing firewall settings while connected over network can result in being locked out of the system.

Remediation will only affect the active system firewall, be sure to configure the default policy in your firewall management to apply on boot as well.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

3.5.1.3 Ensure IPv6 outbound and established connections are configured (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Configure the firewall rules for new outbound, and established IPv6 connections.

Rationale:

If rules are not in place for new outbound, and established connections all packets will be dropped by the default policy preventing network usage.

Audit:

Run the following command and verify all rules for new outbound, and established connections match site policy:

```
# ip6tables -L -v -n
```

OR

If IPv6 is disabled:

Run the following command and verify that no lines are returned.

```
# grep "^\s*linux" /boot/grub2/grub.cfg | grep -v ipv6.disable=1
```

OR

```
# grep "^\s*linux" /boot/grub/grub.cfg | grep -v ipv6.disable=1
```

Configure iptables in accordance with site policy. The following commands will implement a policy to allow all outbound connections and all established connections:

```
# ip6tables -A OUTPUT -p tcp -m state --state NEW, ESTABLISHED -j ACCEPT
# ip6tables -A OUTPUT -p udp -m state --state NEW, ESTABLISHED -j ACCEPT
# ip6tables -A OUTPUT -p icmp -m state --state NEW, ESTABLISHED -j ACCEPT
# ip6tables -A INPUT -p tcp -m state --state ESTABLISHED -j ACCEPT
# ip6tables -A INPUT -p udp -m state --state ESTABLISHED -j ACCEPT
# ip6tables -A INPUT -p icmp -m state --state ESTABLISHED -j ACCEPT
```

Notes:

Changing firewall settings while connected over network can result in being locked out of the system.

Remediation will only affect the active system firewall, be sure to configure the default policy in your firewall management to apply on boot as well.

CIS Controls:

Version 6

9.1 <u>Limit Open Ports, Protocols, and Services</u>

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

3.5.1.4 Ensure IPv6 firewall rules exist for all open ports (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Any ports that have been opened on non-loopback addresses need firewall rules to govern traffic.

Rationale:

Without a firewall rule configured for open ports default firewall policy will drop all packets to these ports.

Audit:

Run the following command to determine open ports:

```
# ss -6tuln
Netid State
                Recv-Q Send-Q Local Address:Port
                                                                    Peer
Address:Port
                 0
                       0
      UNCONN
udp
                                          ::1:123
:::*
                0
                       0
udp
     UNCONN
                                           :::123
:::*
tcp
     LISTEN
                 0
                      128
                                           :::22
:::*
                 0
                       20
tcp
      LISTEN
                                          ::1:25
:::*
```

Run the following command to determine firewall rules:

```
# ip6tables -L INPUT -v -n
Chain INPUT (policy DROP 0 packets, 0 bytes)
pkts bytes target prot opt in
                                  out
                                          source
destination
                  all
                             10
   0 0 ACCEPT
                                          ::/0
                                                              ::/0
                            *
      0 DROP
0 ACCEPT
                    all
                                          ::1
                                                              ::/0
                                          ::/0
                    tcp
                                                              ::/0
tcp dpt:22 state NEW
```

Verify all open ports listening on non-localhost addresses have at least one firewall rule. The last line identified by the "tcp dpt:22 state NEW" identifies it as a firewall rule for new connections on tcp port 22.

OR

If IPv6 is disabled:

Run the following command and verify that no lines are returned.

```
# grep "^\s*linux" /boot/grub2/grub.cfg | grep -v ipv6.disable=1
```

OR

```
# grep "^\s*linux" /boot/grub/grub.cfg | grep -v ipv6.disable=1
```

For each port identified in the audit which does not have a firewall rule establish a proper rule for accepting inbound connections:

```
# ip6tables -A INPUT -p protocol> --dport <port> -m state --state NEW -j
ACCEPT
```

Notes:

Changing firewall settings while connected over network can result in being locked out of the system.

Remediation will only affect the active system firewall, be sure to configure the default policy in your firewall management to apply on boot as well.

The remediation command opens up the port to traffic from all sources. Consult iptables documentation and set any restrictions in compliance with site policy.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

3.5.2 Configure IPv4 iptables

Iptables is used to set up, maintain, and inspect the tables of IP packet filter rules in the Linux kernel. Several different tables may be defined. Each table contains a number of built-in chains and may also contain user-defined chains.

Each chain is a list of rules which can match a set of packets. Each rule specifies what to do with a packet that matches. This is called a 'target', which may be a jump to a user-defined chain in the same table.

Note: This section broadly assumes starting with an empty IPtables firewall ruleset (established by flushing the rules with iptables -F). Remediation steps included only affect the live system, you will also need to configure your default firewall configuration to apply on boot. Configuration of a live systems firewall directly over a remote connection will often result in being locked out. It is advised to have a known good firewall configuration set to run on boot and to configure an entire firewall structure in a script that is then run and tested before saving to boot. The following script will implement the firewall rules of this section and open port 22(ssh) from anywhere:

```
#!/bin/bash
# Flush IPtables rules
iptables -F
# Ensure default deny firewall policy
iptables -P INPUT DROP
iptables -P OUTPUT DROP
iptables -P FORWARD DROP
# Ensure loopback traffic is configured
iptables -A INPUT -i lo -j ACCEPT
iptables -A OUTPUT -o lo -j ACCEPT
iptables -A INPUT -s 127.0.0.0/8 -j DROP
# Ensure outbound and established connections are configured
iptables -A OUTPUT -p tcp -m state --state NEW, ESTABLISHED -j ACCEPT
iptables -A OUTPUT -p udp -m state --state NEW, ESTABLISHED -j ACCEPT
iptables -A OUTPUT -p icmp -m state --state NEW, ESTABLISHED -j ACCEPT
iptables -A INPUT -p tcp -m state --state ESTABLISHED -j ACCEPT
iptables -A INPUT -p udp -m state --state ESTABLISHED -j ACCEPT
iptables -A INPUT -p icmp -m state --state ESTABLISHED -j ACCEPT
# Open inbound ssh(tcp port 22) connections
iptables -A INPUT -p tcp --dport 22 -m state --state NEW -j ACCEPT
```

3.5.2.1 Ensure default deny firewall policy (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

A default deny all policy on connections ensures that any unconfigured network usage will be rejected.

Rationale:

With a default accept policy the firewall will accept any packet that is not configured to be denied. It is easier to white list acceptable usage than to black list unacceptable usage.

Audit:

Run the following command and verify that the policy for the INPUT, OUTPUT, and FORWARD chains is DROP or REJECT:

```
# iptables -L
Chain INPUT (policy DROP)
Chain FORWARD (policy DROP)
Chain OUTPUT (policy DROP)
```

Run the following commands to implement a default DROP policy:

```
# iptables -P INPUT DROP
# iptables -P OUTPUT DROP
# iptables -P FORWARD DROP
```

Notes:

Changing firewall settings while connected over network can result in being locked out of the system.

Remediation will only affect the active system firewall, be sure to configure the default policy in your firewall management to apply on boot as well.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

3.5.2.2 Ensure loopback traffic is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Configure the loopback interface to accept traffic. Configure all other interfaces to deny traffic to the loopback network (127.0.0.0/8).

Rationale:

Loopback traffic is generated between processes on machine and is typically critical to operation of the system. The loopback interface is the only place that loopback network (127.0.0.0/8) traffic should be seen, all other interfaces should ignore traffic on this network as an anti-spoofing measure.

Audit:

Run the following commands and verify output includes the listed rules in order (packet and byte counts may differ):

```
# iptables -L INPUT -v -n
Chain INPUT (policy DROP 0 packets, 0 bytes)
pkts bytes target prot opt in
                                 out
                                        source
destination
  0 0 ACCEPT all -- lo
                                        0.0.0.0/0
                                                           0.0.0.0/0
                   all -- *
                                         127.0.0.0/8
       0 DROP
                                                           0.0.0.0/0
# iptables -L OUTPUT -v -n
Chain OUTPUT (policy DROP 0 packets, 0 bytes)
pkts bytes target prot opt in
                                         source
destination
                  all -- *
        0 ACCEPT
                                  10
                                         0.0.0.0/0
                                                            0.0.0.0/0
```

Run the following commands to implement the loopback rules:

```
# iptables -A INPUT -i lo -j ACCEPT
# iptables -A OUTPUT -o lo -j ACCEPT
# iptables -A INPUT -s 127.0.0.0/8 -j DROP
```

Notes:

Changing firewall settings while connected over network can result in being locked out of the system.

Remediation will only affect the active system firewall, be sure to configure the default policy in your firewall management to apply on boot as well.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

3.5.2.3 Ensure outbound and established connections are configured (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Configure the firewall rules for new outbound, and established connections.

Rationale:

If rules are not in place for new outbound, and established connections all packets will be dropped by the default policy preventing network usage.

Audit:

Run the following command and verify all rules for new outbound, and established connections match site policy:

iptables -L -v -n

Configure iptables in accordance with site policy. The following commands will implement a policy to allow all outbound connections and all established connections:

```
# iptables -A OUTPUT -p tcp -m state --state NEW, ESTABLISHED -j ACCEPT
# iptables -A OUTPUT -p udp -m state --state NEW, ESTABLISHED -j ACCEPT
# iptables -A OUTPUT -p icmp -m state --state NEW, ESTABLISHED -j ACCEPT
# iptables -A INPUT -p tcp -m state --state ESTABLISHED -j ACCEPT
# iptables -A INPUT -p udp -m state --state ESTABLISHED -j ACCEPT
# iptables -A INPUT -p icmp -m state --state ESTABLISHED -j ACCEPT
```

Notes:

Changing firewall settings while connected over network can result in being locked out of the system.

Remediation will only affect the active system firewall, be sure to configure the default policy in your firewall management to apply on boot as well.

CIS Controls:

Version 6

9.1 <u>Limit Open Ports, Protocols, and Services</u>

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.

3.5.2.4 Ensure firewall rules exist for all open ports (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Any ports that have been opened on non-loopback addresses need firewall rules to govern traffic.

Rationale:

Without a firewall rule configured for open ports default firewall policy will drop all packets to these ports.

Audit:

Run the following command to determine open ports:

```
# ss -4tuln
Netid State
             Recv-Q Send-Q Local Address:Port
                                                          Peer
Address:Port
udp UNCONN 0
                   0
                                      *:68
*:*
udp UNCONN 0
                   0
                                      *:123
* : *
   LISTEN 0
                    128
                                      *:22
tcp
*:*
```

Run the following command to determine firewall rules:

Verify all open ports listening on non-localhost addresses have at least one firewall rule. The last line identified by the "tcp dpt:22 state NEW" identifies it as a firewall rule for new connections on tcp port 22.

For each port identified in the audit which does not have a firewall rule establish a proper rule for accepting inbound connections:

```
# iptables -A INPUT -p protocol> --dport <port> -m state --state NEW -j
ACCEPT
```

Notes:

Changing firewall settings while connected over network can result in being locked out of the system.

Remediation will only affect the active system firewall, be sure to configure the default policy in your firewall management to apply on boot as well.

The remediation command opens up the port to traffic from all sources. Consult iptables documentation and set any restrictions in compliance with site policy.

CIS Controls:

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

9.4 <u>Apply Host-based Firewalls or Port Filtering</u>

Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.

3.5.3 Ensure iptables is installed (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

iptables allows configuration of the IPv4 and IPv6 tables in the linux kernel and the rules stored within them. Most firewall configuration utilities operate as a front end to iptables.

Rationale:

iptables is required for firewall management and configuration.

Audit:

Run the following command and verify iptables is installed:

```
# rpm -q iptables
# dpkg -s iptables
```

Run the following command to install iptables:

```
# yum install iptables
# apt-get install iptables
# zypper install iptables
```

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.

3.6 Ensure wireless interfaces are disabled (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 2 Workstation

Description:

Wireless networking is used when wired networks are unavailable. Debian contains a wireless tool kit to allow system administrators to configure and use wireless networks.

Rationale:

If wireless is not to be used, wireless devices can be disabled to reduce the potential attack surface.

Audit:

Run the following command to determine wireless interfaces on the system:

iwconfig

Run the following command and verify wireless interfaces are active:

ip link show up

Run the following command to disable any wireless interfaces:

ip link set <interface> down

Disable any wireless interfaces in your network configuration.

Impact:

Many if not all laptop workstations and some desktop workstations will connect via wireless requiring these interfaces be enabled.

CIS Controls:

Version 6

15.4 Configure Only Authorized Wireless Access On Client Machines

Where a specific business need for wireless access has been identified, configure wireless access on client machines to allow access only to authorized wireless networks. For devices that do not have an essential wireless business purpose, disable wireless access in the hardware configuration (basic input/output system or extensible firmware interface).

Version 7

15.4 <u>Disable Wireless Access on Devices if Not Required</u>

Disable wireless access on devices that do not have a business purpose for wireless access.

15.5 Limit Wireless Access on Client Devices

Configure wireless access on client machines that do have an essential wireless business purpose, to allow access only to authorized wireless networks and to restrict access to other wireless networks.

3.7 Disable IPv6 (Not Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Although IPv6 has many advantages over IPv4, not all organizations have IPv6 or dual stack configurations implemented.

Rationale:

If IPv6 or dual stack is not to be used, it is recommended that IPv6 be disabled to reduce the attack surface of the system.

Audit:

Depending or your distribution, run the appropriate following command and verify no lines should be returned.

```
# grep "^\s*linux" /boot/grub2/grub.cfg | grep -v ipv6.disabled=1
```

or

grep "^\s*linux" /boot/grub/grub.cfg | grep -v ipv6.disabled=1

Edit /etc/default/grub and add ipv6.disable=1 to the GRUB CMDLINE LINUX parameters:

GRUB CMDLINE LINUX="ipv6.disable=1"

Depending or your distribution, run the appropriate following command to update the grub2 configuration:

grub2-mkconfig -o /boot/grub2/grub.cfg

or

update-grub

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops,</u> Workstations, and Servers

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

11 <u>Secure Configurations for Network Devices such as Firewalls, Routers and switches</u> Secure Configurations for Network Devices such as Firewalls, Routers and switches

Version 7

9.4 Apply Host-based Firewalls or Port Filtering

Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.

4 Logging and Auditing

The items in this section describe how to configure logging, log monitoring, and auditing, using tools included in most distributions.

It is recommended that rsyslogbe used for logging (with logwatchproviding summarization) and auditd be used for auditing (with aureportproviding summarization) to automatically monitor logs for intrusion attempts and other suspicious system behavior.

In addition to the local log files created by the steps in this section, it is also recommended that sites collect copies of their system logs on a secure, centralized log server via an encrypted connection. Not only does centralized logging help sites correlate events that may be occurring on multiple systems, but having a second copy of the system log information may be critical after a system compromise where the attacker has modified the local log files on the affected system(s). If a log correlation system is deployed, configure it to process the logs described in this section.

Because it is often necessary to correlate log information from many different systems (particularly after a security incident) it is recommended that the time be synchronized among systems and devices connected to the local network. The standard Internet protocol for time synchronization is the Network Time Protocol (NTP), which is supported by most network-ready devices. See the ntpd(8) manual page for more information on configuring NTP.

It is important that all logs described in this section be monitored on a regular basis and correlated to determine trends. A seemingly innocuous entry in one log could be more significant when compared to an entry in another log.

Note on log file permissions: There really isn't a "one size fits all" solution to the permissions on log files. Many sites utilize group permissions so that administrators who are in a defined security group, such as "wheel" do not have to elevate privileges to root in order to read log files. Also, if a third party log aggregation tool is used, it may need to have group permissions to read the log files, which is preferable to having it run setuid to root. Therefore, there are two remediation and audit steps for log file permissions. One is for systems that do not have a secured group method implemented that only permits root to read the log files (root:root 600). The other is for sites that do have such a setup and are designated as root:securegrp 640where securegrpis the defined security group (in some cases wheel).

4.1 Configure System Accounting (auditd)

System auditing, through <code>auditd</code>, allows system administrators to monitor their systems such that they can detect unauthorized access or modification of data. By default, auditd will audit SELinux AVC denials, system logins, account modifications, and authentication events. Events will be logged to /var/log/audit/audit.log. The recording of these events will use a modest amount of disk space on a system. If significantly more events are captured, additional on system or off system storage may need to be allocated.

The recommendations in this section implement an audit policy that produces large quantities of logged data. In some environments it can be challenging to store or process these logs and as such they are marked as Level 2 for both Servers and Workstations. **Note:** For 64 bit systems that have arch as a rule parameter, you will need two rules: one for 64 bit and one for 32 bit systems. For 32 bit systems, only one rule is needed.

Note: Several recommendations in this section filter based off of auid>=500 for unprivileged non-system users. Some distributions split at UID 1000 instead, consult your documentation and/or the UID_MIN setting in /etc/login.defs to determine which is appropriate for you.

Note: Once all configuration changes have been made to /etc/audit/rules.d/audit.rules, the auditd configuration must be reloaded with the following command:

service auditd reload

4.1.1 Configure Data Retention

When auditing, it is important to carefully configure the storage requirements for audit logs. By default, auditd will max out the log files at 5MB and retain only 4 copies of them. Older versions will be deleted. It is possible on a system that the 20 MBs of audit logs may fill up the system causing loss of audit data. While the recommendations here provide guidance, check your site policy for audit storage requirements.

4.1.1.1 Ensure audit log storage size is configured (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Configure the maximum size of the audit log file. Once the log reaches the maximum size, it will be rotated and a new log file will be started.

Rationale:

It is important that an appropriate size is determined for log files so that they do not impact the system and audit data is not lost.

Audit:

Run the following command and ensure output is in compliance with site policy:

```
# grep max_log_file /etc/audit/auditd.conf
max_log_file = <MB>
```

Set the following parameter in /etc/audit/auditd.conf in accordance with site policy:

max log file = <MB>

Notes:

The max_log_file parameter is measured in megabytes.

Other methods of log rotation may be appropriate based on site policy. One example is time-based rotation strategies which don't have native support in auditd configurations. Manual audit of custom configurations should be evaluated for effectiveness and completeness.

CIS Controls:

Version 6

6.3 Ensure Audit Logging Systems Are Not Subject To Loss (i.e. rotation/archive)
Ensure that all systems that store logs have adequate storage space for the logs
generated on a regular basis, so that log files will not fill up between log rotation intervals.
The logs must be archived and digitally signed on a periodic basis.

Version 7

6.4 Ensure adequate storage for logs

Ensure that all systems that store logs have adequate storage space for the logs generated.

4.1.1.2 Ensure system is disabled when audit logs are full (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The auditd daemon can be configured to halt the system when the audit logs are full.

Rationale:

In high security contexts, the risk of detecting unauthorized access or nonrepudiation exceeds the benefit of the system's availability.

Audit:

Run the following commands and verify output matches:

```
# grep space_left_action /etc/audit/auditd.conf
space_left_action = email
# grep action_mail_acct /etc/audit/auditd.conf
action_mail_acct = root
# grep admin_space_left_action /etc/audit/auditd.conf
admin_space_left_action = halt
```

Set the following parameters in /etc/audit/auditd.conf:

```
space left action = email
action_mail_acct = root
admin_space_left_action = halt
```

CIS Controls:

Version 6

6.3 Ensure Audit Logging Systems Are Not Subject To Loss (i.e. rotation/archive)
Ensure that all systems that store logs have adequate storage space for the logs
generated on a regular basis, so that log files will not fill up between log rotation intervals.

The logs must be archived and digitally signed on a periodic basis.

Version 7

6.4 Ensure adequate storage for logs

Ensure that all systems that store logs have adequate storage space for the logs generated.

4.1.1.3 Ensure audit logs are not automatically deleted (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The max_log_file_action setting determines how to handle the audit log file reaching the max file size. A value of keep logs will rotate the logs but never delete old logs.

Rationale:

In high security contexts, the benefits of maintaining a long audit history exceed the cost of storing the audit history.

Audit:

Run the following command and verify output matches:

```
# grep max_log_file_action /etc/audit/auditd.conf
max_log_file_action = keep_logs
```

Remediation:

Set the following parameter in /etc/audit/auditd.conf:

```
max_log_file_action = keep_logs
```

CIS Controls:

Version 6

6.3 Ensure Audit Logging Systems Are Not Subject To Loss (i.e. rotation/archive)
Ensure that all systems that store logs have adequate storage space for the logs
generated on a regular basis, so that log files will not fill up between log rotation intervals.
The logs must be archived and digitally signed on a periodic basis.

Version 7

6.4 Ensure adequate storage for logs

Ensure that all systems that store logs have adequate storage space for the logs generated.

4.1.2 Ensure auditd is installed (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

auditd is the userspace component to the Linux Auditing System. It's responsible for writing audit records to the disk

Rationale:

The capturing of system events provides system administrators with information to allow them to determine if unauthorized access to their system is occurring.

Audit:

Run the following command and verify auditd is installed:

```
# rpm -q audit audit-libs
# dpkg -s auditd audispd-plugins
```

Run the following command to Install auditd

```
# yum install audit audit-libs
# apt-get install auditd audispd-plugins
# zipper install audit audit-libs
```

CIS Controls:

Version 6

6.2 Ensure Audit Log Settings Support Appropriate Log Entry Formatting

Validate audit log settings for each hardware device and the software installed on it, ensuring that logs include a date, timestamp, source addresses, destination addresses, and various other useful elements of each packet and/or transaction. Systems should record logs in a standardized format such as syslog entries or those outlined by the Common Event Expression initiative. If systems cannot generate logs in a standardized format, log normalization tools can be deployed to convert logs into such a format.

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

4.1.3 Ensure auditd service is enabled (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Turn on the auditd daemon to record system events.

Rationale:

The capturing of system events provides system administrators with information to allow them to determine if unauthorized access to their system is occurring.

Audit:

Run one of the following commands to verify auditd is enabled:

```
# chkconfig --list auditd auditd 0:off 1:off 2:on 3:on 4:on 5:on 6:off
```

Verify runlevels 2 through 5 are "on".

```
# systemctl is-enabled auditd
enabled
```

Verify result is "enabled".

```
# ls /etc/rc*.d | grep auditd
```

Verify S* lines are returned for runlevels 2 through 5.

Run one of the following commands to enable auditd:

```
# chkconfig auditd on

# systemctl enable auditd

# update-rc.d auditd enable
```

Notes:

Additional methods of enabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

6.2 Ensure Audit Log Settings Support Appropriate Log Entry Formatting

Validate audit log settings for each hardware device and the software installed on it, ensuring that logs include a date, timestamp, source addresses, destination addresses, and various other useful elements of each packet and/or transaction. Systems should record logs in a standardized format such as syslog entries or those outlined by the Common Event Expression initiative. If systems cannot generate logs in a standardized format, log normalization tools can be deployed to convert logs into such a format.

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

4.1.4 Ensure auditing for processes that start prior to auditd is enabled (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Configure grub so that processes that are capable of being audited can be audited even if they start up prior to audited startup.

Rationale:

Audit events need to be captured on processes that start up prior to auditd, so that potential malicious activity cannot go undetected.

Audit:

For grub2 based systems run the following command and verify that each linux line has the audit=1 parameter set:

```
# grep "^\s*linux" /boot/grub2/grub.cfg
```

or

```
# grep "^\s*linux" /boot/grub/grub.cfg
```

For grub based systems run the following command and verify that each kernel line has the audit=1 parameter set:

```
# grep "^\s*kernel" /boot/grub/menu.lst
```

For grub2 based systems edit /etc/default/grub and add audit=1 to GRUB_CMDLINE_LINUX:

GRUB CMDLINE LINUX="audit=1"

Run the following command to update the grub2 configuration:

grub2-mkconfig -o /boot/grub2/grub.cfg

or

update-grub

For grub based systems edit /boot/grub/menu.lst to include audit=1 on all kernel lines.

Notes:

This recommendation is designed around the grub bootloader, if LILO or another bootloader is in use in your environment enact equivalent settings.

Replace /boot/grub2/grub.cfg, /boot/grub/grun.cfg, /boot/grub/menu.lst with the appropriate grub configuration file for your environment.

CIS Controls:

Version 6

6.2 Ensure Audit Log Settings Support Appropriate Log Entry Formatting

Validate audit log settings for each hardware device and the software installed on it, ensuring that logs include a date, timestamp, source addresses, destination addresses, and various other useful elements of each packet and/or transaction. Systems should record logs in a standardized format such as syslog entries or those outlined by the Common Event Expression initiative. If systems cannot generate logs in a standardized format, log normalization tools can be deployed to convert logs into such a format.

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

4.1.5 Ensure events that modify date and time information are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Capture events where the system date and/or time has been modified. The parameters in this section are set to determine if the adjtimex (tune kernel clock), settimeofday (Set time, using timeval and timezone structures) stime (using seconds since 1/1/1970) or clock_settime (allows for the setting of several internal clocks and timers) system calls have been executed and always write an audit record to the /var/log/audit.log file upon exit, tagging the records with the identifier "time-change"

Rationale:

Unexpected changes in system date and/or time could be a sign of malicious activity on the system.

Audit:

On a 32 bit system run the following commands:

```
# grep time-change /etc/audit/rules.d/*.rules
# auditctl -l | grep time-change
```

Verify output of both matches:

```
-a always,exit -F arch=b32 -S adjtimex -S settimeofday -S stime -k time-change
-a always,exit -F arch=b32 -S clock_settime -k time-change
-w /etc/localtime -p wa -k time-change
```

On a 64 bit system run the following commands:

```
# grep time-change /etc/audit/rules.d/*.rules
# auditctl -l | grep time-change
```

Verify output of both matches:

```
-a always, exit -F arch=b64 -S adjtimex -S settimeofday -k time-change
-a always, exit -F arch=b32 -S adjtimex -S settimeofday -S stime -k time-
change
-a always, exit -F arch=b64 -S clock_settime -k time-change
-a always, exit -F arch=b32 -S clock_settime -k time-change
-w /etc/localtime -p wa -k time-change
```

For 32 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-a always, exit -F arch=b32 -S adjtimex -S settimeofday -S stime -k time-change
-a always, exit -F arch=b32 -S clock_settime -k time-change
-w /etc/localtime -p wa -k time-change
```

For 64 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-a always, exit -F arch=b64 -S adjtimex -S settimeofday -k time-change
-a always, exit -F arch=b32 -S adjtimex -S settimeofday -S stime -k time-
change
-a always, exit -F arch=b64 -S clock_settime -k time-change
-a always, exit -F arch=b32 -S clock_settime -k time-change
-w /etc/localtime -p wa -k time-change
```

Notes:

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

3.6 <u>Implement Automated Configuration Monitoring System (i.e. Configuration Assessment Tools)</u>

Implement and test an automated configuration monitoring system that verifies all remotely testable secure configuration elements, and alerts when unauthorized changes occur. This includes detecting new listening ports, new administrative users, changes to group and local policy objects (where applicable), and new services running on a system. Whenever possible use tools compliant with the Security Content Automation Protocol (SCAP) in order to streamline reporting and integration.

Version 7

5.5 <u>Implement Automated Configuration Monitoring Systems</u>

Utilize a Security Content Automation Protocol (SCAP) compliant configuration monitoring system to verify all security configuration elements, catalog approved exceptions, and alert when unauthorized changes occur.

4.1.6 Ensure events that modify user/group information are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Record events affecting the <code>group</code>, <code>passwd</code> (user IDs), <code>shadow</code> and <code>gshadow</code> (passwords) or <code>/etc/security/opasswd</code> (old passwords, based on remember parameter in the PAM configuration) files. The parameters in this section will watch the files to see if they have been opened for write or have had attribute changes (e.g. permissions) and tag them with the identifier "identity" in the audit log file.

Rationale:

Unexpected changes to these files could be an indication that the system has been compromised and that an unauthorized user is attempting to hide their activities or compromise additional accounts.

Audit:

Run the following commands:

```
# grep identity /etc/audit/rules.d/*.rules
# auditctl -l | grep identity
```

Verify output of both matches:

```
-w /etc/group -p wa -k identity
-w /etc/passwd -p wa -k identity
-w /etc/gshadow -p wa -k identity
-w /etc/shadow -p wa -k identity
-w /etc/security/opasswd -p wa -k identity
```

Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-w /etc/group -p wa -k identity
-w /etc/passwd -p wa -k identity
-w /etc/gshadow -p wa -k identity
-w /etc/shadow -p wa -k identity
-w /etc/security/opasswd -p wa -k identity
```

Notes:

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

5.4 Log Administrative User Addition And Removal

Configure systems to issue a log entry and alert when an account is added to or removed from a domain administrators' group, or when a new local administrator account is added on a system.

Version 7

4.8 Log and Alert on Changes to Administrative Group Membership

Configure systems to issue a log entry and alert when an account is added to or removed from any group assigned administrative privileges.

4.1.7 Ensure events that modify the system's network environment are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Record changes to network environment files or system calls. The below parameters monitor the sethostname (set the systems host name) or setdomainname (set the systems domainname) system calls, and write an audit event on system call exit. The other parameters monitor the /etc/issue and /etc/issue.net files (messages displayed prelogin), /etc/hosts (file containing host names and associated IP addresses) and /etc/sysconfig/network (directory containing network interface scripts and configurations) files.

Rationale:

Monitoring sethostname and setdomainname will identify potential unauthorized changes to host and domainname of a system. The changing of these names could potentially break security parameters that are set based on those names. The /etc/hosts file is monitored for changes in the file that can indicate an unauthorized intruder is trying to change machine associations with IP addresses and trick users and processes into connecting to unintended machines. Monitoring /etc/issue and /etc/issue.net is important, as intruders could put disinformation into those files and trick users into providing information to the intruder. Monitoring /etc/sysconfig/network is important as it can show if network interfaces or scripts are being modified in a way that can lead to the machine becoming unavailable or compromised. All audit records will be tagged with the identifier "system-locale."

Audit:

On a 32 bit system run the following commands:

```
# grep system-locale /etc/audit/rules.d/*.rules
# auditctl -l | grep system-locale
```

Verify output of both matches:

```
-a always,exit -F arch=b32 -S sethostname -S setdomainname -k system-locale
-w /etc/issue -p wa -k system-locale
-w /etc/issue.net -p wa -k system-locale
-w /etc/hosts -p wa -k system-locale
-w /etc/sysconfig/network -p wa -k system-locale
```

On a 64 bit system run the following commands:

```
# grep system-locale /etc/audit/rules.d/*.rules
# auditctl -l | grep system-locale
```

Verify output of both matches:

```
-a always, exit -F arch=b64 -S sethostname -S setdomainname -k system-locale
-a always, exit -F arch=b32 -S sethostname -S setdomainname -k system-locale
-w /etc/issue -p wa -k system-locale
-w /etc/issue.net -p wa -k system-locale
-w /etc/hosts -p wa -k system-locale
-w /etc/sysconfig/network -p wa -k system-locale
```

For 32 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-a always, exit -F arch=b32 -S sethostname -S setdomainname -k system-locale
-w /etc/issue -p wa -k system-locale
-w /etc/issue.net -p wa -k system-locale
-w /etc/hosts -p wa -k system-locale
-w /etc/sysconfig/network -p wa -k system-locale
```

For 64 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-a always, exit -F arch=b64 -S sethostname -S setdomainname -k system-locale
-a always, exit -F arch=b32 -S sethostname -S setdomainname -k system-locale
-w /etc/issue -p wa -k system-locale
-w /etc/issue.net -p wa -k system-locale
-w /etc/hosts -p wa -k system-locale
-w /etc/sysconfig/network -p wa -k system-locale
```

Notes:

/etc/sysconfig/network is common to Red Hat and SUSE based distributions.

You should expand or replace this coverage to any network configuration files on your system such as /etc/network on Debian based distributions.

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

3.6 <u>Implement Automated Configuration Monitoring System (i.e. Configuration</u> Assessment Tools)

Implement and test an automated configuration monitoring system that verifies all remotely testable secure configuration elements, and alerts when unauthorized changes occur. This includes detecting new listening ports, new administrative users, changes to group and local policy objects (where applicable), and new services running on a system. Whenever possible use tools compliant with the Security Content Automation Protocol (SCAP) in order to streamline reporting and integration.

Version 7

5.5 <u>Implement Automated Configuration Monitoring Systems</u>

Utilize a Security Content Automation Protocol (SCAP) compliant configuration monitoring system to verify all security configuration elements, catalog approved exceptions, and alert when unauthorized changes occur.

4.1.8 Ensure events that modify the system's Mandatory Access Controls are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor SELinux/AppArmor mandatory access controls. The parameters below monitor any write access (potential additional, deletion or modification of files in the directory) or attribute changes to the /etc/selinux or /etc/apparmor and /etc/apparmor.d directories.

Rationale:

Changes to files in these directories could indicate that an unauthorized user is attempting to modify access controls and change security contexts, leading to a compromise of the system.

Audit:

On systems using SELinux run the following commands:

```
# grep MAC-policy /etc/audit/rules.d/*.rules
# auditctl -l | grep MAC-policy
```

Verify output of both matches:

```
-w /etc/selinux/ -p wa -k MAC-policy
-w /usr/share/selinux/ -p wa -k MAC-policy
```

On systems using AppArmor run the following commands:

```
# grep MAC-policy /etc/audit/rules.d/*.rules
# auditctl -l | grep MAC-policy
```

Verify output of both matches:

```
-w /etc/apparmor/ -p wa -k MAC-policy
-w /etc/apparmor.d/ -p wa -k MAC-policy
```

On systems using SELinux Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-w /etc/selinux/ -p wa -k MAC-policy
-w /usr/share/selinux/ -p wa -k MAC-policy
```

On systems using AppArmor Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-w /etc/apparmor/ -p wa -k MAC-policy
-w /etc/apparmor.d/ -p wa -k MAC-policy
```

Notes:

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

3.6 <u>Implement Automated Configuration Monitoring System (i.e. Configuration Assessment Tools)</u>

Implement and test an automated configuration monitoring system that verifies all remotely testable secure configuration elements, and alerts when unauthorized changes occur. This includes detecting new listening ports, new administrative users, changes to group and local policy objects (where applicable), and new services running on a system. Whenever possible use tools compliant with the Security Content Automation Protocol (SCAP) in order to streamline reporting and integration.

Version 7

5.5 <u>Implement Automated Configuration Monitoring Systems</u>

Utilize a Security Content Automation Protocol (SCAP) compliant configuration monitoring system to verify all security configuration elements, catalog approved exceptions, and alert when unauthorized changes occur.

4.1.9 Ensure login and logout events are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor login and logout events. The parameters below track changes to files associated with login/logout events. The file /var/log/faillog tracks failed events from login. The file /var/log/lastlog maintain records of the last time a user successfully logged in. The file /var/log/tallylog maintains records of failures via the pam_tally2 module

Rationale:

Monitoring login/logout events could provide a system administrator with information associated with brute force attacks against user logins.

Audit:

Run the following commands:

```
# grep logins /etc/audit/rules.d/*.rules
# auditctl -l | grep logins
```

Verify output of both includes:

```
-w /var/log/faillog -p wa -k logins
-w /var/log/lastlog -p wa -k logins
-w /var/log/tallylog -p wa -k logins
```

Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-w /var/log/faillog -p wa -k logins
-w /var/log/lastlog -p wa -k logins
-w /var/log/tallylog -p wa -k logins
```

Notes:

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

5.5 Log Failed Administrative Login Attempts

Configure systems to issue a log entry and alert on any unsuccessful login to an administrative account.

16.10 Profile User Account Usage And Monitor For Anomalies

Profile each user's typical account usage by determining normal time-of-day access and access duration. Reports should be generated that indicate users who have logged in during unusual hours or have exceeded their normal login duration. This includes flagging the use of the user's credentials from a computer other than computers on which the user generally works.

16.4 Automatically Log Off Users After Standard Period Of Inactivity

Regularly monitor the use of all accounts, automatically logging off users after a standard period of inactivity.

Version 7

4.9 Log and Alert on Unsuccessful Administrative Account Login

Configure systems to issue a log entry and alert on unsuccessful logins to an administrative account.

16.11 <u>Lock Workstation Sessions After Inactivity</u>

Automatically lock workstation sessions after a standard period of inactivity.

16.13 Alert on Account Login Behavior Deviation

Alert when users deviate from normal login behavior, such as time-of-day, workstation location and duration.

4.1.10 Ensure session initiation information is collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor session initiation events. The parameters in this section track changes to the files associated with session events. The file /var/run/utmp tracks all currently logged in users. All audit records will be tagged with the identifier "session." The /var/log/wtmp file tracks logins, logouts, shutdown, and reboot events. The file /var/log/btmp keeps track of failed login attempts and can be read by entering the command /usr/bin/last -f /var/log/btmp. All audit records will be tagged with the identifier "logins."

Rationale:

Monitoring these files for changes could alert a system administrator to logins occurring at unusual hours, which could indicate intruder activity (i.e. a user logging in at a time when they do not normally log in).

Audit:

Run the following commands:

```
# grep -E '(session|logins)' /etc/audit/rules.d/*.rules
# auditctl -l | grep -E '(session|logins)'
```

Verify output of both includes:

```
-w /var/run/utmp -p wa -k session
-w /var/log/wtmp -p wa -k logins
-w /var/log/btmp -p wa -k logins
```

Remediation:

Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-w /var/run/utmp -p wa -k session
-w /var/log/wtmp -p wa -k logins
-w /var/log/btmp -p wa -k logins
```

Notes:

The last command can be used to read /var/log/wtmp (last with no parameters) and /var/run/utmp (last -f /var/run/utmp)

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

5.5 Log Failed Administrative Login Attempts

Configure systems to issue a log entry and alert on any unsuccessful login to an administrative account.

16.10 Profile User Account Usage And Monitor For Anomalies

Profile each user's typical account usage by determining normal time-of-day access and access duration. Reports should be generated that indicate users who have logged in during unusual hours or have exceeded their normal login duration. This includes flagging the use of the user's credentials from a computer other than computers on which the user generally works.

16.4 Automatically Log Off Users After Standard Period Of Inactivity

Regularly monitor the use of all accounts, automatically logging off users after a standard period of inactivity.

Version 7

4.9 Log and Alert on Unsuccessful Administrative Account Login

Configure systems to issue a log entry and alert on unsuccessful logins to an administrative account.

16.11 Lock Workstation Sessions After Inactivity

Automatically lock workstation sessions after a standard period of inactivity.

16.13 Alert on Account Login Behavior Deviation

Alert when users deviate from normal login behavior, such as time-of-day, workstation location and duration.

4.1.11 Ensure discretionary access control permission modification events are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor changes to file permissions, attributes, ownership and group. The parameters in this section track changes for system calls that affect file permissions and attributes. The chmod, fchmod and fchmodat system calls affect the permissions associated with a file. The chown, fchown, fchownat and lchown system calls affect owner and group attributes on a file. The setxattr, lsetxattr, fsetxattr (set extended file attributes) and removexattr, lremovexattr, fremovexattr (remove extended file attributes) control extended file attributes. In all cases, an audit record will only be written for non-system user ids (auid >= 500) and will ignore Daemon events (auid = 4294967295). All audit records will be tagged with the identifier "perm_mod."

Rationale:

Monitoring for changes in file attributes could alert a system administrator to activity that could indicate intruder activity or policy violation.

Audit:

On a 32 bit system run the following commands:

```
# grep perm_mod /etc/audit/rules.d/*.rules
```

Verify output matches:

```
-a always, exit -F arch=b32 -S chmod -S fchmod -S fchmodat -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b32 -S chown -S fchown -S fchownat -S lchown -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b32 -S setxattr -S lsetxattr -S fsetxattr -S removexattr -S lremovexattr -S fremovexattr -F auid>=500 -F auid!=4294967295 -k perm_mod

# auditctl -l | grep perm_mod
```

Verify output matches:

```
-a always, exit -F arch=b32 -S chmod -S fchmod -S fchmodat -F auid>=500 -F auid!=-1 -k perm_mod
-a always, exit -F arch=b32 -S chown -S fchown -S fchownat -S lchown -F auid>=500 -F auid!=-1 -k perm_mod
-a always, exit -F arch=b32 -S setxattr -S lsetxattr -S fsetxattr -S removexattr -S lremovexattr -S fremovexattr -F auid>=500 -F auid!=-1 -k perm_mod
```

On a 64 bit system run the following commands:

```
# grep auditctl -l | grep perm mod /etc/audit/rules.d/*.rules
```

Verify output matches:

```
-a always, exit -F arch=b64 -S chmod -S fchmod -S fchmodat -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b32 -S chmod -S fchmod -S fchmodat -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b64 -S chown -S fchown -S fchownat -S lchown -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b32 -S chown -S fchown -S fchownat -S lchown -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b64 -S setxattr -S lsetxattr -S fsetxattr -S removexattr -S lremovexattr -S fremovexattr -F auid>=500 -F auid!=4294967295 -k perm mod
-a always, exit -F arch=b32 -S setxattr -S lsetxattr -S fsetxattr -S removexattr -S lremovexattr -S fremovexattr -F auid>=500 -F auid!=4294967295 -k perm_mod

# auditctl -l | grep auditctl -l | grep perm_mod
```

Verify output matches:

```
-a always, exit -F arch=b64 -S chmod -S fchmod -S fchmodat -F auid>=500 -F auid!=-1 -k perm_mod
-a always, exit -F arch=b32 -S chmod -S fchmod -S fchmodat -F auid>=500 -F auid!=-1 -k perm_mod
-a always, exit -F arch=b64 -S chown -S fchown -S fchownat -S lchown -F auid>=500 -F auid!=-1 -k perm_mod
-a always, exit -F arch=b32 -S chown -S fchown -S fchownat -S lchown -F auid>=500 -F auid!=-1 -k perm_mod
-a always, exit -F arch=b64 -S setxattr -S lsetxattr -S fsetxattr -S removexattr -S lremovexattr -S fremovexattr -F auid>=500 -F auid!=-1 -k perm_mod
-a always, exit -F arch=b32 -S setxattr -S lsetxattr -S fsetxattr -S removexattr -S lremovexattr -S fremovexattr -F auid>=500 -F auid!=-1 -k perm_mod
```

For 32 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-a always, exit -F arch=b32 -S chmod -S fchmod -S fchmodat -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b32 -S chown -S fchown -S fchownat -S lchown -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b32 -S setxattr -S lsetxattr -S fsetxattr -S removexattr -S lremovexattr -S fremovexattr -F auid>=500 -F auid!=4294967295 -k perm_mod
```

For 64 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-a always, exit -F arch=b64 -S chmod -S fchmod -S fchmodat -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b32 -S chmod -S fchmod -S fchmodat -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b64 -S chown -S fchown -S fchownat -S lchown -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b32 -S chown -S fchown -S fchownat -S lchown -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b64 -S setxattr -S lsetxattr -S fsetxattr -S removexattr -S lremovexattr -S fremovexattr -F auid>=500 -F auid!=4294967295 -k perm_mod
-a always, exit -F arch=b32 -S setxattr -S lsetxattr -S fsetxattr -S removexattr -S lremovexattr -S fremovexattr -F auid>=500 -F auid!=4294967295 -k perm_mod
```

Notes:

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

3.6 <u>Implement Automated Configuration Monitoring System (i.e. Configuration Assessment Tools)</u>

Implement and test an automated configuration monitoring system that verifies all remotely testable secure configuration elements, and alerts when unauthorized changes occur. This includes detecting new listening ports, new administrative users, changes to group and local policy objects (where applicable), and new services running on a system. Whenever possible use tools compliant with the Security Content Automation Protocol (SCAP) in order to streamline reporting and integration.

Version 7

5.5 <u>Implement Automated Configuration Monitoring Systems</u>

Utilize a Security Content Automation Protocol (SCAP) compliant configuration monitoring system to verify all security configuration elements, catalog approved exceptions, and alert when unauthorized changes occur.

4.1.12 Ensure unsuccessful unauthorized file access attempts are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor for unsuccessful attempts to access files. The parameters below are associated with system calls that control creation (<code>creat</code>), opening (<code>open</code>, <code>openat</code>) and truncation (<code>truncate</code>, <code>ftruncate</code>) of files. An audit log record will only be written if the user is a non-privileged user (auid > = 500), is not a Daemon event (auid=4294967295) and if the system call returned EACCES (permission denied to the file) or EPERM (some other permanent error associated with the specific system call). All audit records will be tagged with the identifier "access."

Rationale:

Failed attempts to open, create or truncate files could be an indication that an individual or process is trying to gain unauthorized access to the system.

Audit:

On a 32 bit system run the following commands:

```
# grep access /etc/audit/rules.d/*.rules
```

Verify output matches:

```
-a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EACCES -F auid>=500 -F auid!=4294967295 -k access -a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EPERM -F auid>=500 -F auid!=4294967295 -k access # auditctl -l | grep access
```

Verify output matches:

```
-a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EACCES -F auid>=500 -F auid!=-1 -k access
-a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EPERM -F auid>=500 -F auid!=-1 -k access
```

On a 64 bit system run the following commands:

```
# grep access /etc/audit/rules.d/*.rules
```

Verify output matches:

```
-a always, exit -F arch=b64 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EACCES -F auid>=500 -F auid!=4294967295 -k access -a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EACCES -F auid>=500 -F auid!=4294967295 -k access -a always, exit -F arch=b64 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EPERM -F auid>=500 -F auid!=4294967295 -k access -a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EPERM -F auid>=500 -F auid!=4294967295 -k access + auditctl -I | grep access
```

Verify output matches:

```
-a always, exit -F arch=b64 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EACCES -F auid>=500 -F auid!=-1 -k access
-a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EACCES -F auid>=500 -F auid!=-1 -k access
-a always, exit -F arch=b64 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EPERM -F auid>=500 -F auid!=-1 -k access
-a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EPERM -F auid>=500 -F auid!=-1 -k access
```

For 32 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-a always,exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EACCES -F auid>=500 -F auid!=4294967295 -k access -a always,exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EPERM -F auid>=500 -F auid!=4294967295 -k access
```

For 64 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-a always, exit -F arch=b64 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EACCES -F auid>=500 -F auid!=4294967295 -k access -a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EACCES -F auid>=500 -F auid!=4294967295 -k access -a always, exit -F arch=b64 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EPERM -F auid>=500 -F auid!=4294967295 -k access -a always, exit -F arch=b32 -S creat -S open -S openat -S truncate -S ftruncate -F exit=-EPERM -F auid>=500 -F auid!=4294967295 -k access
```

Notes:

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

14.6 Enforce Detailed Audit Logging For Sensitive Information

Enforce detailed audit logging for access to nonpublic data and special authentication for sensitive data.

Version 7

14.9 Enforce Detail Logging for Access or Changes to Sensitive Data

Enforce detailed audit logging for access to sensitive data or changes to sensitive data (utilizing tools such as File Integrity Monitoring or Security Information and Event Monitoring).

4.1.13 Ensure use of privileged commands is collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor privileged programs (those that have the setuid and/or setgid bit set on execution) to determine if unprivileged users are running these commands.

Rationale:

Execution of privileged commands by non-privileged users could be an indication of someone trying to gain unauthorized access to the system.

Audit:

Run the following command replacing <partition> with a list of partitions where programs can be executed from on your system:

```
# find <partition> -xdev \( -perm -4000 -o -perm -2000 \) -type f | awk
'{print \
"-a always,exit -F path=" $1 " -F perm=x -F auid>=500 -F auid!=4294967295 \
-k privileged" }'
```

Verify all resulting lines are a .rules file in /etc/audit/rules.d/ and the output of auditctl -1.

NOTE: The .rules file output will be auid!=-1 not auid!=4294967295

To remediate this issue, the system administrator will have to execute a find command to locate all the privileged programs and then add an audit line for each one of them. The audit parameters associated with this are as follows:

-F path=" \$1 "-will populate each file name found through the find command and processed by awk. -F perm=x - will write an audit record if the file is executed. -F auid>=500 - will write a record if the user executing the command is not a privileged user. -F auid!= 4294967295 - will ignore Daemon events

All audit records should be tagged with the identifier "privileged".

Run the following command replacing with a list of partitions where programs can be executed from on your system:

```
# find <partition> -xdev \( -perm -4000 -o -perm -2000 \) -type f | awk
'{print \
"-a always,exit -F path=" $1 " -F perm=x -F auid>=500 -F auid!=4294967295 \
-k privileged" }'
```

Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules Example: vi /etc/audit/rules.d/audit.rules And add all resulting lines to the file.

Notes:

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

4.1.14 Ensure successful file system mounts are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor the use of the mount system call. The mount (and umount) system call controls the mounting and unmounting of file systems. The parameters below configure the system to create an audit record when the mount system call is used by a non-privileged user

Rationale:

It is highly unusual for a non privileged user to mount file systems to the system. While tracking mount commands gives the system administrator evidence that external media may have been mounted (based on a review of the source of the mount and confirming it's an external media type), it does not conclusively indicate that data was exported to the media. System administrators who wish to determine if data were exported, would also have to track successful open, creat and truncate system calls requiring write access to a file under the mount point of the external media file system. This could give a fair indication that a write occurred. The only way to truly prove it, would be to track successful writes to the external media. Tracking write system calls could quickly fill up the audit log and is not recommended. Recommendations on configuration options to track data export to media is beyond the scope of this document.

Audit:

On a 32 bit system run the following commands:

```
# grep mounts /etc/audit/rules.d/*.rules
```

Verify output matches:

```
-a always, exit -F arch=b32 -S mount -F auid>=500 -F auid!=4294967295 -k mounts
# auditctl -l | grep mounts
```

Verify output matches:

```
-a always, exit -F arch=b32 -S mount -F auid>=500 -F auid!=-1 -k mounts
```

On a 64 bit system run the following commands:

```
# grep mounts /etc/audit/rules.d/*.rules
```

Verify output matches:

```
-a always, exit -F arch=b64 -S mount -F auid>=500 -F auid!=4294967295 -k mounts
-a always, exit -F arch=b32 -S mount -F auid>=500 -F auid!=4294967295 -k mounts

# auditctl -l | grep mounts
```

Verify output matches:

```
-a always,exit -F arch=b64 -S mount -F auid>=500 -F auid!=-1 -k mounts
-a always,exit -F arch=b32 -S mount -F auid>=500 -F auid!=-1 -k mounts
```

For 32 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules

and add the following lines:

```
-a always,exit -F arch=b32 -S mount -F auid>=500 -F auid!=4294967295 -k mounts
```

For 64 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-a always, exit -F arch=b64 -S mount -F auid>=500 -F auid!=4294967295 -k mounts
-a always, exit -F arch=b32 -S mount -F auid>=500 -F auid!=4294967295 -k mounts
```

Notes:

This tracks successful and unsuccessful mount commands. File system mounts do not have to come from external media and this action still does not verify write (e.g. CD ROMS).

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

4.1.15 Ensure file deletion events by users are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor the use of system calls associated with the deletion or renaming of files and file attributes. This configuration statement sets up monitoring for the unlink (remove a file), unlinkat (remove a file attribute), rename (rename a file) and renameat (rename a file attribute) system calls and tags them with the identifier "delete".

Rationale:

Monitoring these calls from non-privileged users could provide a system administrator with evidence that inappropriate removal of files and file attributes associated with protected files is occurring. While this audit option will look at all events, system administrators will want to look for specific privileged files that are being deleted or altered.

Audit:

On a 32 bit system run the following commands:

```
# grep delete /etc/audit/rules.d/*.rules
```

Verify output matches:

```
-a always, exit -F arch=b32 -S unlink -S unlinkat -S rename -S renameat -F auid>=500 -F auid!=4294967295 -k delete
# auditctl -l | grep delete
```

Verify output matches:

```
-a always, exit -F arch=b32 -S unlink -S unlinkat -S rename -S renameat -F auid>=500 -F auid!=4294967295 -k delete
```

On a 64 bit system run the following commands:

```
# grep delete /etc/audit/rules.d/*.rules
```

Verify output matches:

```
-a always, exit -F arch=b64 -S unlink -S unlinkat -S rename -S renameat -F auid>=500 -F auid!=4294967295 -k delete
-a always, exit -F arch=b32 -S unlink -S unlinkat -S rename -S renameat -F auid>=500 -F auid!=4294967295 -k delete

# auditctl -l | grep delete
```

Verify output matches:

```
-a always, exit -F arch=b64 -S unlink -S unlinkat -S rename -S renameat -F auid>=500 -F auid!=-1 -k delete
-a always, exit -F arch=b32 -S unlink -S unlinkat -S rename -S renameat -F auid>=500 -F auid!=-1 -k delete
```

For 32 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules

and add the following lines:

```
-a always,exit -F arch=b32 -S unlink -S unlinkat -S rename -S renameat -F auid>=500 -F auid!=4294967295 -k delete
```

For 64 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

-a always, exit -F arch=b64 -S unlink -S unlinkat -S rename -S renameat -F auid>=500 -F auid!=4294967295 -k delete
-a always, exit -F arch=b32 -S unlink -S unlinkat -S rename -S renameat -F auid>=500 -F auid!=4294967295 -k delete

Notes:

At a minimum, configure the audit system to collect file deletion events for all users and root.

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

13 <u>Data Protection</u> Data Protection

4.1.16 Ensure changes to system administration scope (sudoers) is collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor scope changes for system administrations. If the system has been properly configured to force system administrators to log in as themselves first and then use the sudo command to execute privileged commands, it is possible to monitor changes in scope. The file /etc/sudoers will be written to when the file or its attributes have changed. The audit records will be tagged with the identifier "scope."

Rationale:

Changes in the /etc/sudoers file can indicate that an unauthorized change has been made to scope of system administrator activity.

Audit:

Run the following commands:

```
# grep scope /etc/audit/rules.d/*.rules
# auditctl -l | grep scope
```

Verify output of both matches:

```
-w /etc/sudoers -p wa -k scope
-w /etc/sudoers.d/ -p wa -k scope
```

Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-w /etc/sudoers -p wa -k scope
-w /etc/sudoers.d/ -p wa -k scope
```

Notes:

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

5.4 <u>Log Administrative User Addition And Removal</u>

Configure systems to issue a log entry and alert when an account is added to or removed from a domain administrators' group, or when a new local administrator account is added on a system.

Version 7

4.8 Log and Alert on Changes to Administrative Group Membership

Configure systems to issue a log entry and alert when an account is added to or removed from any group assigned administrative privileges.

4.1.17 Ensure system administrator actions (sudolog) are collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor the sudo log file. If the system has been properly configured to disable the use of the su command and force all administrators to have to log in first and then use sudo to execute privileged commands, then all administrator commands will be logged to $\label{eq:command} $$ \langle var/log/sudo.log. Any time a command is executed, an audit event will be triggered as the $$ \langle var/log/sudo.log file will be opened for write and the executed administration command will be written to the log.$

Rationale:

Changes in /var/log/sudo.log indicate that an administrator has executed a command or the log file itself has been tampered with. Administrators will want to correlate the events written to the audit trail with the records written to /var/log/sudo.log to verify if unauthorized commands have been executed.

Audit:

Run the following commands:

```
# grep actions /etc/audit/rules.d/*.rules
# auditctl -l | grep actions
```

Verify output of both matches:

```
-w /var/log/sudo.log -p wa -k actions
```

Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

-w /var/log/sudo.log -p wa -k actions

Notes:

The system must be configured with sudisabled (See Item 5.6 Ensure access to the su command is restricted) to force all command execution through sudo. This will not be effective on the console, as administrators can log in as root.

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

5.5 Log Failed Administrative Login Attempts

Configure systems to issue a log entry and alert on any unsuccessful login to an administrative account.

Version 7

4.9 Log and Alert on Unsuccessful Administrative Account Login

Configure systems to issue a log entry and alert on unsuccessful logins to an administrative account.

4.1.18 Ensure kernel module loading and unloading is collected (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Monitor the loading and unloading of kernel modules. The programs <code>insmod</code> (install a kernel module), <code>rmmod</code> (remove a kernel module), and <code>modprobe</code> (a more sophisticated program to load and unload modules, as well as some other features) control loading and unloading of modules. The <code>init_module</code> (load a module) and <code>delete_module</code> (delete a module) system calls control loading and unloading of modules. Any execution of the loading and unloading module programs and system calls will trigger an audit record with an identifier of "modules".

Rationale:

Monitoring the use of insmod, rmmod and modprobe could provide system administrators with evidence that an unauthorized user loaded or unloaded a kernel module, possibly compromising the security of the system. Monitoring of the init_module and delete_module system calls would reflect an unauthorized user attempting to use a different program to load and unload modules.

Audit:

On a 32 bit system run the following commands:

```
# grep modules /etc/audit/rules.d/*.rules
# auditctl -l | grep modules
```

Verify output of both matches:

```
-w /sbin/insmod -p x -k modules
-w /sbin/rmmod -p x -k modules
-w /sbin/modprobe -p x -k modules
-a always,exit -F arch=b32 -S init_module -S delete_module -k modules
```

On a 64 bit system run the following commands:

```
# grep modules /etc/audit/rules.d/*.rules
# auditctl -l | grep modules
```

Verify output of both matches:

```
-w /sbin/insmod -p x -k modules
-w /sbin/rmmod -p x -k modules
-w /sbin/modprobe -p x -k modules
-a always,exit -F arch=b64 -S init_module -S delete_module -k modules
```

For 32 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-w /sbin/insmod -p x -k modules
-w /sbin/rmmod -p x -k modules
-w /sbin/modprobe -p x -k modules
-a always,exit -F arch=b32 -S init module -S delete module -k modules
```

For 64 bit systems Edit or create a file in the /etc/audit/rules.d/ directory ending in .rules

Example: vi /etc/audit/rules.d/audit.rules and add the following lines:

```
-w /sbin/insmod -p x -k modules
-w /sbin/rmmod -p x -k modules
-w /sbin/modprobe -p x -k modules
-a always,exit -F arch=b64 -S init module -S delete module -k modules
```

Notes:

Reloading the auditd config to set active settings may require a system reboot.

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers</u>

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

4.1.19 Ensure the audit configuration is immutable (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

Set system audit so that audit rules cannot be modified with auditctl. Setting the flag "-e 2" forces audit to be put in immutable mode. Audit changes can only be made on system reboot.

Rationale:

In immutable mode, unauthorized users cannot execute changes to the audit system to potentially hide malicious activity and then put the audit rules back. Users would most likely notice a system reboot and that could alert administrators of an attempt to make unauthorized audit changes.

Audit:

Run the following command and verify output matches:

```
# grep "^\s*[^#]" /etc/audit/rules.d/*.rules | tail -1
-e 2
```

Edit or create the file /etc/audit/rules.d/99-finalize.rules and add the line

-e 2

at the end of the file

Notes:

This setting will ensure reloading the auditd config to set active settings requires a system reboot.

CIS Controls:

Version 6

3 <u>Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers</u>

Secure Configurations for Hardware and Software on Mobile Devices, Laptops, Workstations, and Servers

6 <u>Maintenance, Monitoring, and Analysis of Audit Logs</u> Maintenance, Monitoring, and Analysis of Audit Logs

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

4.2 Configure Logging

Logging services should be configured to prevent information leaks and to aggregate logs on a remote server so that they can be reviewed in the event of a system compromise and ease log analysis.

4.2.1 Configure rsyslog

The rsyslog software is recommended as a replacement for the syslogd daemon and provides improvements over syslogd, such as connection-oriented (i.e. TCP) transmission of logs, the option to log to database formats, and the encryption of log data en route to a central logging server. **Note:** This section only applies if rsyslog is installed on the system.

4.2.1.1 Ensure rsyslog is installed (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The rsyslog software is a recommended replacement to the original syslogd daemon which provide improvements over syslogd, such as connection-oriented (i.e. TCP) transmission of logs, the option to log to database formats, and the encryption of log data en route to a central logging server.

Rationale:

The security enhancements of rsyslog such as connection-oriented (i.e. TCP) transmission of logs, the option to log to database formats, and the encryption of log data en route to a central logging server) justify installing and configuring the package.

Audit:

Verify either rsyslog or syslog-ng is installed. Depending on the package management in use one of the following command groups may provide the needed information:

```
# rpm -q rsyslog
# dpkg -s rsyslog
```

Install rsyslog or using the appropriate package manager or manual installation:

```
# yum install rsyslog
# apt-get install rsyslog
# zypper install rsyslog
```

CIS Controls:

Version 6

6.2 Ensure Audit Log Settings Support Appropriate Log Entry Formatting

Validate audit log settings for each hardware device and the software installed on it, ensuring that logs include a date, timestamp, source addresses, destination addresses, and various other useful elements of each packet and/or transaction. Systems should record logs in a standardized format such as syslog entries or those outlined by the Common Event Expression initiative. If systems cannot generate logs in a standardized format, log normalization tools can be deployed to convert logs into such a format.

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

4.2.1.2 Ensure rsyslog Service is enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Once the rsyslog package is installed it needs to be activated.

Rationale:

If the rsyslog service is not activated the system may default to the syslogd service or lack logging instead.

Audit:

Run one of the following commands to verify rsyslog is enabled:

```
# chkconfig --list rsyslog
rsyslog 0:off 1:off 2:on 3:on 4:on 5:on 6:off
```

Verify runlevels 2 through 5 are "on".

```
# systemctl is-enabled rsyslog
enabled
```

Verify result is "enabled".

```
# ls /etc/rc*.d | grep rsyslog
```

Verify S* lines are returned for runlevels 2 through 5.

Run one of the following commands to enable rsyslog:

```
# chkconfig rsyslog on

# systemctl enable rsyslog

# update-rc.d rsyslog enable
```

Notes:

Additional methods of enabling a service exist. Consult your distribution documentation for appropriate methods.

Some distributions may configure syslog daemon selection via a setting in a configuration file such as /etc/sysconfig/syslog and a centralized init script.

CIS Controls:

Version 6

6.2 Ensure Audit Log Settings Support Appropriate Log Entry Formatting

Validate audit log settings for each hardware device and the software installed on it, ensuring that logs include a date, timestamp, source addresses, destination addresses, and various other useful elements of each packet and/or transaction. Systems should record logs in a standardized format such as syslog entries or those outlined by the Common Event Expression initiative. If systems cannot generate logs in a standardized format, log normalization tools can be deployed to convert logs into such a format.

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

4.2.1.3 Ensure logging is configured (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/rsyslog.conf and /etc/rsyslog.d/*.conf files specifies rules for logging and which files are to be used to log certain classes of messages.

Rationale:

A great deal of important security-related information is sent via rsyslog (e.g., successful and failed su attempts, failed login attempts, root login attempts, etc.).

Audit:

Review the contents of the /etc/rsyslog.conf and /etc/rsyslog.d/*.conf files to ensure appropriate logging is set. In addition, run the following command and verify that the log files are logging information:

ls -l /var/log/

Edit the following lines in the /etc/rsyslog.conf and /etc/rsyslog.d/*.conf files as appropriate for your environment:

```
*.emerg
                                          :omusrmsq:*
mail.*
                                         -/var/log/mail
mail.info
                                         -/var/log/mail.info
mail.warning
                                         -/var/log/mail.warn
                                          /var/log/mail.err
mail.err
news.crit
                                         -/var/log/news/news.crit
                                         -/var/log/news/news.err
news.err
news.notice
                                         -/var/log/news/news.notice
*.=warning; *.=err
                                         -/var/log/warn
                                          /var/log/warn
*.crit
                                         -/var/log/messages
*.*; mail.none; news.none
                                         -/var/log/localmessages
local0,local1.*
local2, local3.*
                                         -/var/log/localmessages
local4,local5.*
                                         -/var/log/localmessages
local6,local7.*
                                         -/var/log/localmessages
```

Run the following command to reload the rsyslogd configuration:

```
# pkill -HUP rsyslogd
```

References:

1. See the rsyslog.conf(5) man page for more information.

CIS Controls:

Version 6

6.2 Ensure Audit Log Settings Support Appropriate Log Entry Formatting

Validate audit log settings for each hardware device and the software installed on it, ensuring that logs include a date, timestamp, source addresses, destination addresses, and various other useful elements of each packet and/or transaction. Systems should record logs in a standardized format such as syslog entries or those outlined by the Common Event Expression initiative. If systems cannot generate logs in a standardized format, log normalization tools can be deployed to convert logs into such a format.

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

4.2.1.4 Ensure rsyslog default file permissions configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

rsyslog will create logfiles that do not already exist on the system. This setting controls what permissions will be applied to these newly created files.

Rationale:

It is important to ensure that log files have the correct permissions to ensure that sensitive data is archived and protected.

Audit:

Run the following command and verify that \$FileCreateMode is 0640 or more restrictive:

grep ^\\$FileCreateMode /etc/rsyslog.conf /etc/rsyslog.d/*.conf

Edit the /etc/rsyslog.conf and /etc/rsyslog.d/*.conf files and set \$FileCreateMode to 0640 or more restrictive:

\$FileCreateMode 0640

References:

1. See the rsyslog.conf(5) man page for more information.

Notes:

You should also ensure this is not overridden with less restrictive settings in any /etc/rsyslog.d/* conf file.

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

4.2.1.5 Ensure rsyslog is configured to send logs to a remote log host (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The rsyslog utility supports the ability to send logs it gathers to a remote log host running syslogd(8) or to receive messages from remote hosts, reducing administrative overhead.

Rationale:

Storing log data on a remote host protects log integrity from local attacks. If an attacker gains root access on the local system, they could tamper with or remove log data that is stored on the local system

Audit:

Review the /etc/rsyslog.conf and /etc/rsyslog.d/*.conf files and verify that logs are sent to a central host (where loghost.example.com is the name of your central log host):

```
# grep "^*.*[^I][^I]*@" /etc/rsyslog.conf /etc/rsyslog.d/*.conf
*.* @@loghost.example.com
```

Edit the /etc/rsyslog.conf and /etc/rsyslog.d/*.conf files and add the following line (where loghost.example.com is the name of your central log host).

. @@loghost.example.com

Run the following command to reload the rsyslogd configuration:

```
# pkill -HUP rsyslogd
```

References:

1. See the rsyslog.conf(5) man page for more information.

Notes:

The double "at" sign (@@) directs rsyslogto use TCP to send log messages to the server, which is a more reliable transport mechanism than the default UDP protocol.

CIS Controls:

Version 6

6.6 <u>Deploy A SIEM OR Log Analysis Tools For Aggregation And Correlation/Analysis</u>

Deploy a SIEM (Security Information and Event Management) or log analytic tools for log aggregation and consolidation from multiple machines and for log correlation and analysis. Using the SIEM tool, system administrators and security personnel should devise profiles of common events from given systems so that they can tune detection to focus on unusual activity, avoid false positives, more rapidly identify anomalies, and prevent overwhelming analysts with insignificant alerts.

Version 7

6.6 Deploy SIEM or Log Analytic tool

Deploy Security Information and Event Management (SIEM) or log analytic tool for log correlation and analysis.

6.8 Regularly Tune SIEM

On a regular basis, tune your SIEM system to better identify actionable events and decrease event noise.

4.2.1.6 Ensure remote rsyslog messages are only accepted on designated log hosts. (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

By default, rsyslog does not listen for log messages coming in from remote systems. The ModLoad tells rsyslog to load the imtcp.so module so it can listen over a network via TCP. The InputTCPServerRun option instructs rsyslogd to listen on the specified TCP port.

Rationale:

The guidance in the section ensures that remote log hosts are configured to only accept rsyslog data from hosts within the specified domain and that those systems that are not designed to be log hosts do not accept any remote rsyslog messages. This provides protection from spoofed log data and ensures that system administrators are reviewing reasonably complete syslog data in a central location.

Audit:

Run the following commands and verify the resulting lines are uncommented on designated log hosts and commented or removed on all others:

```
# grep '$ModLoad imtcp' /etc/rsyslog.conf /etc/rsyslog.d/*.conf
$ModLoad imtcp
# grep '$InputTCPServerRun' /etc/rsyslog.conf /etc/rsyslog.d/*.conf
$InputTCPServerRun 514
```

For hosts that are designated as log hosts, edit the /etc/rsyslog.conf file and uncomment or add the following lines:

```
$ModLoad imtcp
$InputTCPServerRun 514
```

For hosts that are not designated as log hosts, edit the /etc/rsyslog.conf file and comment or remove the following lines:

```
# $ModLoad imtcp
# $InputTCPServerRun 514
```

Run the following command to reload the rsyslogd configuration:

```
# pkill -HUP rsyslogd
```

References:

1. See the rsyslog(8) man page for more information.

Notes:

The \$MoadLoad imtcp line can have the .so extension added to the end of the module, or use the full path to the module.

CIS Controls:

Version 6

9.1 Limit Open Ports, Protocols, and Services

Ensure that only ports, protocols, and services with validated business needs are running on each system.

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running

Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

4.2.2 Configure journald

systemd-journald is a system service that collects and stores logging data. It creates and maintains structured, indexed journals based on logging information that is received from a variety of sources: Kernel log messages, via kmsg

Any changes made to the systemd-journald configuration will require a re-start of systemd-journald

4.2.2.1 Ensure journald is configured to send logs to rsyslog (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Data from journald may be stored in volatile memory or persisted locally on the server. Utilities exist to accept remote export of journald logs, however, use of the rsyslog service provides a consistent means of log collection and export.

Rationale:

Storing log data on a remote host protects log integrity from local attacks. If an attacker gains root access on the local system, they could tamper with or remove log data that is stored on the local system.

Audit:

Review /etc/systemd/journald.conf and verify that logs are forwarded to syslog

```
# grep -e ForwardToSyslog /etc/systemd/journald.conf
# ForwardToSyslog=yes
```

Remediation:

Edit the /etc/systemd/journald.conf file and add the following line:

ForwardToSyslog=yes

References:

1. https://github.com/konstruktoid/hardening/blob/master/systemd.adoc#etcsystemdjournaldconf

Notes:

This recommendation assumes that recommendation 4.2.1.5, "Ensure rsyslog is configured to send logs to a remote log host" has been implemented.

As noted in the journald man pages, journald logs may be exported to rsyslog either through the process mentioned here, or through a facility like <code>systemd-journald.service</code>. There are trade-offs involved in each implementation, where <code>ForwardToSyslog</code> will immediately capture all events (and forward to an external log server, if properly configured), but may not capture all boot-up activities. Mechanisms such as <code>systemd-journald.service</code>, on the other hand, will record bootup events, but may delay sending the information to rsyslog, leading to the potential for log manipulation prior to export. Be aware of the limitations of all tools employed to secure a system.

The main configuration file /etc/systemd/journald.conf is read before any of the custom *.conf files. If there are custom configs present, they override the main configuration parameters

CIS Controls:

Version 6

6.2 Ensure Audit Log Settings Support Appropriate Log Entry Formatting

Validate audit log settings for each hardware device and the software installed on it, ensuring that logs include a date, timestamp, source addresses, destination addresses, and various other useful elements of each packet and/or transaction. Systems should record logs in a standardized format such as syslog entries or those outlined by the Common Event Expression initiative. If systems cannot generate logs in a standardized format, log normalization tools can be deployed to convert logs into such a format.

Version 7

6.5 Central Log Management

Ensure that appropriate logs are being aggregated to a central log management system for analysis and review.

4.2.2.2 Ensure journald is configured to compress large log files (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The journald system includes the capability of compressing overly large files to avoid filling up the system with logs or making the logs unmanageably large.

Rationale:

Uncompressed large files may unexpectedly fill a filesystem leading to resource unavailability. Compressing logs prior to write can prevent sudden, unexpected filesystem impacts.

Audit:

Review /etc/systemd/journald.conf and verify that large files will be compressed:

grep -e Compress /etc/systemd/journald.conf
Compress=yes

Edit the /etc/systemd/journald.conf file and add the following line:

Compress=yes

References:

1. https://github.com/konstruktoid/hardening/blob/master/systemd.adoc#etcsystemdjournaldconf

Notes:

The main configuration file /etc/systemd/journald.conf is read before any of the custom *.conf files. If there are custom configs present, they override the main configuration parameters

CIS Controls:

Version 6

6.2 Ensure Audit Log Settings Support Appropriate Log Entry Formatting

Validate audit log settings for each hardware device and the software installed on it, ensuring that logs include a date, timestamp, source addresses, destination addresses, and various other useful elements of each packet and/or transaction. Systems should record logs in a standardized format such as syslog entries or those outlined by the Common Event Expression initiative. If systems cannot generate logs in a standardized format, log normalization tools can be deployed to convert logs into such a format.

Version 7

6.4 Ensure adequate storage for logs

Ensure that all systems that store logs have adequate storage space for the logs generated.

4.2.2.3 Ensure journald is configured to write logfiles to persistent disk (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Data from journald may be stored in volatile memory or persisted locally on the server. Logs in memory will be lost upon a system reboot. By persisting logs to local disk on the server they are protected from loss.

Rationale:

Writing log data to disk will provide the ability to forensically reconstruct events which may have impacted the operations or security of a system even after a system crash or reboot.

Audit:

Review /etc/systemd/journald.conf and verify that logs are persisted to disk:

grep -e Storage /etc/systemd/journald.conf
Storage=persistent

Edit the /etc/systemd/journald.conf file and add the following line:

Storage=persistent

References:

1. https://github.com/konstruktoid/hardening/blob/master/systemd.adoc#etcsystemdjournaldconf

Notes:

The main configuration file /etc/systemd/journald.conf is read before any of the custom *.conf files. If there are custom configs present, they override the main configuration parameters

CIS Controls:

Version 6

6.2 Ensure Audit Log Settings Support Appropriate Log Entry Formatting

Validate audit log settings for each hardware device and the software installed on it, ensuring that logs include a date, timestamp, source addresses, destination addresses, and various other useful elements of each packet and/or transaction. Systems should record logs in a standardized format such as syslog entries or those outlined by the Common Event Expression initiative. If systems cannot generate logs in a standardized format, log normalization tools can be deployed to convert logs into such a format.

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

4.2.3 Ensure permissions on all logfiles are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Log files stored in /var/log/ contain logged information from many services on the system, or on log hosts others as well.

Rationale:

It is important to ensure that log files have the correct permissions to ensure that sensitive data is archived and protected.

Audit:

Run the following command and verify that other has no permissions on any files and group does not have write or execute permissions on any files:

find /var/log -type f -ls

Run the following commands to set permissions on all existing log files:

```
find /var/log -type f -exec chmod g-wx,o-rwx "{}" + -o -type d -exec chmod g-w,o-rwx "{}" +
```

Notes:

You may also need to change the configuration for your logging software or services for any logs that had incorrect permissions.

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

4.3 Ensure logrotate is configured (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The system includes the capability of rotating log files regularly to avoid filling up the system with logs or making the logs unmanageably large. The file /etc/logrotate.d/syslog is the configuration file used to rotate log files created by syslog or rsyslog.

Rationale:

By keeping the log files smaller and more manageable, a system administrator can easily archive these files to another system and spend less time looking through inordinately large log files.

Audit:

Review /etc/logrotate.conf and /etc/logrotate.d/* and verify logs are rotated according to site policy.

Edit /etc/logrotate.conf and /etc/logrotate.d/* to ensure logs are rotated according to site policy.

Notes:

If no maxage setting is set for logrotate a situation can occur where logrotate is interrupted and fails to delete rotated logfiles. It is recommended to set this to a value greater than the longest any log file should exist on your system to ensure that any such logfile is removed but standard rotation settings are not overridden.

CIS Controls:

Version 6

6.3 Ensure Audit Logging Systems Are Not Subject To Loss (i.e. rotation/archive)
Ensure that all systems that store logs have adequate storage space for the logs
generated on a regular basis, so that log files will not fill up between log rotation intervals.
The logs must be archived and digitally signed on a periodic basis.

Version 7

6.4 Ensure adequate storage for logs

Ensure that all systems that store logs have adequate storage space for the logs generated.

5 Access, Authentication and Authorization			

5.1 Configure cron

5.1.1 Ensure cron daemon is enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The cron daemon is used to execute batch jobs on the system.

Rationale:

While there may not be user jobs that need to be run on the system, the system does have maintenance jobs that may include security monitoring that have to run, and cron is used to execute them.

Audit:

Based on your system configuration, run the appropriate one of the following commands to verify cron is enabled:

```
# chkconfig --list crond
crond 0:off 1:off 2:on 3:on 4:on 5:on 6:off
```

Verify runlevels 2 through 5 are "on".

```
# systemctl is-enabled crond
enabled
```

Verify result is "enabled".

```
# ls /etc/rc*.d | grep crond
```

Verify S* lines are returned for runlevels 2 through 5.

Based on your system configuration, run the appropriate one of the following commands to enable cron:

```
# chkconfig crond on
# systemctl enable crond
# update-rc.d crond enable
```

Notes:

Additional methods of enabling a service exist. Consult your distribution documentation for appropriate methods.

CIS Controls:

Version 6

6 <u>Maintenance, Monitoring, and Analysis of Audit Logs</u> Maintenance, Monitoring, and Analysis of Audit Logs

Version 7

5.1 Establish Secure Configurations

5.1.2 Ensure permissions on /etc/crontab are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/crontab file is used by cron to control its own jobs. The commands in this item make sure that root is the user and group owner of the file and that only the owner can access the file.

Rationale:

This file contains information on what system jobs are run by cron. Write access to these files could provide unprivileged users with the ability to elevate their privileges. Read access to these files could provide users with the ability to gain insight on system jobs that run on the system and could provide them a way to gain unauthorized privileged access.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access does not grant permissions to group or other:

```
# stat /etc/crontab
Access: (0600/-rw-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to set ownership and permissions on /etc/crontab:

```
# chown root:root /etc/crontab
# chmod og-rwx /etc/crontab
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

5.1.3 Ensure permissions on /etc/cron.hourly are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

This directory contains system <code>cron</code> jobs that need to run on an hourly basis. The files in this directory cannot be manipulated by the <code>crontab</code> command, but are instead edited by system administrators using a text editor. The commands below restrict read/write and search access to user and group root, preventing regular users from accessing this directory.

Rationale:

Granting write access to this directory for non-privileged users could provide them the means for gaining unauthorized elevated privileges. Granting read access to this directory could give an unprivileged user insight in how to gain elevated privileges or circumvent auditing controls.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access does not grant permissions to group or other:

```
# stat /etc/cron.hourly
Access: (0700/drwx-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to set ownership and permissions on /etc/cron.hourly:

- # chown root:root /etc/cron.hourly
- # chmod og-rwx /etc/cron.hourly

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

5.1.4 Ensure permissions on /etc/cron.daily are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/cron.daily directory contains system cron jobs that need to run on a daily basis. The files in this directory cannot be manipulated by the crontab command, but are instead edited by system administrators using a text editor. The commands below restrict read/write and search access to user and group root, preventing regular users from accessing this directory.

Rationale:

Granting write access to this directory for non-privileged users could provide them the means for gaining unauthorized elevated privileges. Granting read access to this directory could give an unprivileged user insight in how to gain elevated privileges or circumvent auditing controls.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access does not grant permissions to group or other:

```
# stat /etc/cron.daily

Access: (0700/drwx-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to set ownership and permissions on /etc/cron.daily:

```
# chown root:root /etc/cron.daily
# chmod og-rwx /etc/cron.daily
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

5.1.5 Ensure permissions on /etc/cron.weekly are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/cron.weekly directory contains system cron jobs that need to run on a weekly basis. The files in this directory cannot be manipulated by the crontab command, but are instead edited by system administrators using a text editor. The commands below restrict read/write and search access to user and group root, preventing regular users from accessing this directory.

Rationale:

Granting write access to this directory for non-privileged users could provide them the means for gaining unauthorized elevated privileges. Granting read access to this directory could give an unprivileged user insight in how to gain elevated privileges or circumvent auditing controls.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access does not grant permissions to group or other:

```
# stat /etc/cron.weekly
Access: (0700/drwx-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to set ownership and permissions on /etc/cron.weekly:

chown root:root /etc/cron.weekly
chmod og-rwx /etc/cron.weekly

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

5.1.6 Ensure permissions on /etc/cron.monthly are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The <code>/etc/cron.monthly</code> directory contains system cron jobs that need to run on a monthly basis. The files in this directory cannot be manipulated by the <code>crontab</code> command, but are instead edited by system administrators using a text editor. The commands below restrict read/write and search access to user and group root, preventing regular users from accessing this directory.

Rationale:

Granting write access to this directory for non-privileged users could provide them the means for gaining unauthorized elevated privileges. Granting read access to this directory could give an unprivileged user insight in how to gain elevated privileges or circumvent auditing controls.

Audit:

Run the following command and verify Uid and Gid are both O/root and Access does not grant permissions to group or other:

```
# stat /etc/cron.monthly
Access: (0700/drwx-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to set ownership and permissions on /etc/cron.monthly:

- # chown root:root /etc/cron.monthly
- # chmod og-rwx /etc/cron.monthly

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

5.1.7 Ensure permissions on /etc/cron.d are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/cron.d directory contains system cron jobs that need to run in a similar manner to the hourly, daily weekly and monthly jobs from /etc/crontab, but require more granular control as to when they run. The files in this directory cannot be manipulated by the crontab command, but are instead edited by system administrators using a text editor. The commands below restrict read/write and search access to user and group root, preventing regular users from accessing this directory.

Rationale:

Granting write access to this directory for non-privileged users could provide them the means for gaining unauthorized elevated privileges. Granting read access to this directory could give an unprivileged user insight in how to gain elevated privileges or circumvent auditing controls.

Audit:

Run the following command and verify uid and Gid are both 0/root and Access does not grant permissions to group or other:

```
# stat /etc/cron.d
Access: (0700/drwx-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to set ownership and permissions on /etc/cron.d:

chown root:root /etc/cron.d
chmod og-rwx /etc/cron.d

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

5.1.8 Ensure at/cron is restricted to authorized users (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Configure /etc/cron.allow and /etc/at.allow to allow specific users to use these services. If /etc/cron.allow or /etc/at.allow do not exist, then /etc/at.deny and /etc/cron.deny are checked. Any user not specifically defined in those files is allowed to use at and cron. By removing the files, only users in /etc/cron.allow and /etc/at.allow are allowed to use at and cron. Note that even though a given user is not listed in cron.allow, cron jobs can still be run as that user. The cron.allow file only controls administrative access to the crontab command for scheduling and modifying cron jobs.

Rationale:

On many systems, only the system administrator is authorized to schedule <code>cron</code> jobs. Using the <code>cron</code> allow file to control who can run <code>cron</code> jobs enforces this policy. It is easier to manage an allow list than a deny list. In a deny list, you could potentially add a user ID to the system and forget to add it to the deny files.

Audit:

Run the following commands and ensure /etc/cron.deny and /etc/at.deny do not exist:

```
# stat /etc/cron.deny
stat: cannot stat `/etc/cron.deny': No such file or directory

# stat /etc/at.deny
stat: cannot stat` /etc/at.deny': No such file or directory
```

Run the following command and verify Uid and Gid are both O/root and Access does not grant permissions to group or other for both /etc/cron.allow and /etc/at.allow:

```
# stat /etc/cron.allow
Access: (0600/-rw-----) Uid: ( 0/ root) Gid: ( 0/ root)

# stat /etc/at.allow
Access: (0600/-rw-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to remove /etc/cron.deny and /etc/at.deny and create and set permissions and ownership for /etc/cron.allow and /etc/at.allow:

```
# rm /etc/cron.deny
# rm /etc/at.deny

# touch /etc/cron.allow
# touch /etc/at.allow

# chmod og-rwx /etc/cron.allow
# chmod og-rwx /etc/at.allow

# chown root:root /etc/cron.allow
# chown root:root /etc/cron.allow
```

CIS Controls:

Version 6

16 <u>Account Monitoring and Control</u>
Account Monitoring and Control

Version 7

16 <u>Account Monitoring and Control</u> Account Monitoring and Control

5.2 SSH Server Configuration

SSH is a secure, encrypted replacement for common login services such as telnet, ftp, rlogin, rsh, and rcp. It is strongly recommended that sites abandon older clear-text login protocols and use SSH to prevent session hijacking and sniffing of sensitive data off the network.

Note: The recommendations in this section only apply if the SSH daemon is installed on the system, if remote access is not required the SSH daemon can be removed and this section skipped.

Note: Once all configuration changes have been made to /etc/ssh/sshd_config, the sshd configuration must be reloaded:

systemctl reload sshd

5.2.1 Ensure permissions on /etc/ssh/sshd_config are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/ssh/sshd_config file contains configuration specifications for sshd. The command below sets the owner and group of the file to root.

Rationale:

The /etc/ssh/sshd_config file needs to be protected from unauthorized changes by non-privileged users.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access does not grant permissions to group or other:

```
# stat /etc/ssh/sshd_config
Access: (0600/-rw-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following commands to set ownership and permissions on /etc/ssh/sshd config:

```
# chown root:root /etc/ssh/sshd_config
# chmod og-rwx /etc/ssh/sshd_config
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.2.2 Ensure permissions on SSH private host key files are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

An SSH private key is one of two files used in SSH public key authentication. In this authentication method, The possession of the private key is proof of identity. Only a private key that corresponds to a public key will be able to authenticate successfully. The private keys need to be stored and handled carefully, and no copies of the private key should be distributed.

Rationale:

If an unauthorized user obtains the private SSH host key file, the host could be impersonated

Audit:

Run the following command and verify Uid is 0/root and Gid is 0/root. Ensure group and other do not have permissions

```
# find /etc/ssh -xdev -type f -name 'ssh host * key' -exec stat {} \;
 File: '/etc/ssh/ssh host rsa key'
 Size: 1679
                                       IO Block: 4096
                                                     regular file
                     Blocks: 8
Device: ca01h/51713d
                    Inode: 8628138
                                       Links: 1
                                    root) Gid: ( 0/root)
Access: (0600/-rw-----) Uid: ( 0/
Access: 2018-10-22 18:24:56.861750616 +0000
Modify: 2018-10-22 18:24:56.861750616 +0000
Change: 2018-10-22 18:24:56.873750616 +0000
Birth: -
 File: '/etc/ssh/ssh host_ecdsa_key'
 Size: 227
                    Blocks: 8
                                       IO Block: 4096 regular file
Device: ca01h/51713d
                    Inode: 8631760
                                      Links: 1
Access: (0600/-rw-----) Uid: ( 0/
                                      root) Gid: ( 0/root)
Access: 2018-10-22 18:24:56.897750616 +0000
Modify: 2018-10-22 18:24:56.897750616 +0000
Change: 2018-10-22 18:24:56.905750616 +0000
Birth: -
 File: '/etc/ssh/ssh host ed25519 key'
                    Blocks: 8
 Size: 387
                                      IO Block: 4096 regular file
Device: ca01h/51713d
                    Inode: 8631762
Access: 2018-10-22 18:24:56.945750616 +0000
Modify: 2018-10-22 18:24:56.945750616 +0000
Change: 2018-10-22 18:24:56.957750616 +0000
Birth: -
```

Run the following commands to set ownership and permissions on the private SSH host key files

```
# find /etc/ssh -xdev -type f -name 'ssh_host_*_key' -exec chown root:root {}
\;
# find /etc/ssh -xdev -type f -name 'ssh_host_*_key' -exec chmod 0600 {} \;
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.2.3 Ensure permissions on SSH public host key files are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

An SSH public key is one of two files used in SSH public key authentication. In this authentication method, a public key is a key that can be used for verifying digital signatures generated using a corresponding private key. Only a public key that corresponds to a private key will be able to authenticate successfully.

Rationale:

If a public host key file is modified by an unauthorized user, the SSH service may be compromised.

Audit:

Run the following command and verify Access does not grant write or execute permissions to group or other for all returned files

```
# find /etc/ssh -xdev -type f -name 'ssh host * key.pub' -exec stat {} \;
 File: '/etc/ssh/ssh host rsa key.pub'
 Size: 382
                     Blocks: 8
                                       IO Block: 4096 regular file
Device: ca01h/51713d
                   Inode: 8631758
                                       Links: 1
Access: (0644/-rw-r--r--) Uid: ( 0/
                                      root) Gid: ( 0/ root)
Access: 2018-10-22 18:24:56.861750616 +0000
Modify: 2018-10-22 18:24:56.861750616 +0000
Change: 2018-10-22 18:24:56.881750616 +0000
Birth: -
 File: '/etc/ssh/ssh host_ecdsa_key.pub'
 Size: 162
                    Blocks: 8
                                       IO Block: 4096 regular file
Device: ca01h/51713d
                    Inode: 8631761
                                      Links: 1
Access: (0644/-rw-r--r-) Uid: ( 0/
                                      root) Gid: ( 0/ root)
Access: 2018-10-22 18:24:56.897750616 +0000
Modify: 2018-10-22 18:24:56.897750616 +0000
Change: 2018-10-22 18:24:56.917750616 +0000
Birth: -
 File: '/etc/ssh/ssh host ed25519 key.pub'
                     Blocks: 8
 Size: 82
                               IO Block: 4096 regular file
Device: ca01h/51713d
                    Inode: 8631763
                                                      0/
                                                            root)
Access: 2018-10-22 18:24:56.945750616 +0000
Modify: 2018-10-22 18:24:56.945750616 +0000
Change: 2018-10-22 18:24:56.961750616 +0000
Birth: -
```

Run the following commands to set permissions and ownership on the SSH host public key files

```
# find /etc/ssh -xdev -type f -name 'ssh_host_*_key.pub' -exec chmod 0644 {}
\;

#find /etc/ssh -xdev -type f -name 'ssh_host_*_key.pub' -exec chown root:root
{} \;
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.2.4 Ensure SSH Protocol is set to 2 (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Older versions of SSH support two different and incompatible protocols: SSH1 and SSH2. SSH1 was the original protocol and was subject to security issues. SSH2 is more advanced and secure.

Rationale:

SSH v1 suffers from insecurities that do not affect SSH v2.

Audit:

Run the following command and verify that output matches:

grep ^Protocol /etc/ssh/sshd_config
Protocol 2

Edit the /etc/ssh/sshd config file to set the parameter as follows:

Protocol 2

Notes:

This command not longer exists in newer versions of SSH. This check is still being included for systems that may be running an older version of SSH. As of openSSH version 7.4 this parameter will not cause an issue when included.

CIS Controls:

Version 6

3.4 <u>Use Only Secure Channels For Remote System Administration</u>

Perform all remote administration of servers, workstation, network devices, and similar equipment over secure channels. Protocols such as telnet, VNC, RDP, or others that do not actively support strong encryption should only be used if they are performed over a secondary encryption channel, such as SSL, TLS or IPSEC.

Version 7

4.5 <u>Use Multifactor Authentication For All Administrative Access</u>

Use multi-factor authentication and encrypted channels for all administrative account access.

14.4 Encrypt All Sensitive Information in Transit

Encrypt all sensitive information in transit.

5.2.5 Ensure SSH LogLevel is appropriate (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

INFO level is the basic level that only records login activity of SSH users. In many situations, such as Incident Response, it is important to determine when a particular user was active on a system. The logout record can eliminate those users who disconnected, which helps narrow the field.

VERBOSE level specifies that login and logout activity as well as the key fingerprint for any SSH key used for login will be logged. This information is important for SSH key management, especially in legacy environments.

Rationale:

SSH provides several logging levels with varying amounts of verbosity. Debug is specifically **not** recommended other than strictly for debugging SSH communications since it provides so much data that it is difficult to identify important security information.

Audit:

Run the following command and verify that output matches:

```
# sshd -T | grep loglevel

LogLevel VERBOSE

OR

loglevel INFO
```

Edit the /etc/ssh/sshd config file to set the parameter as follows:

LogLevel VERBOSE

OR

LogLevel INFO

Default Value:

LogLevel INFO

References:

1. https://www.ssh.com/ssh/sshd config/

CIS Controls:

Version 6

16 Account Monitoring and Control

Account Monitoring and Control

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6.3 Enable Detailed Logging

Enable system logging to include detailed information such as an event source, date, user, timestamp, source addresses, destination addresses, and other useful elements.

5.2.6 Ensure SSH X11 forwarding is disabled (Scored)

Profile Applicability:

- Level 1 Workstation
- Level 2 Server

Description:

The X11Forwarding parameter provides the ability to tunnel X11 traffic through the connection to enable remote graphic connections.

Rationale:

Disable X11 forwarding unless there is an operational requirement to use X11 applications directly. There is a small risk that the remote X11 servers of users who are logged in via SSH with X11 forwarding could be compromised by other users on the X11 server. Note that even if X11 forwarding is disabled, users can always install their own forwarders.

Audit:

Run the following command and verify that output matches:

```
# sshd -T | grep x11forwarding
X11Forwarding no
```

Remediation:

Edit the /etc/ssh/sshd config file to set the parameter as follows:

```
X11Forwarding no
```

CIS Controls:

Version 6

16 Account Monitoring and Control
Account Monitoring and Control

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

5.2.7 Ensure SSH MaxAuthTries is set to 4 or less (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The MaxAuthTries parameter specifies the maximum number of authentication attempts permitted per connection. When the login failure count reaches half the number, error messages will be written to the syslog file detailing the login failure.

Rationale:

Setting the MaxAuthTries parameter to a low number will minimize the risk of successful brute force attacks to the SSH server. While the recommended setting is 4, set the number based on site policy.

Audit:

Run the following command and verify that output MaxAuthTries is 4 or less:

```
# sshd -T | grep maxauthtries
MaxAuthTries 4
```

Edit the /etc/ssh/sshd_config file to set the parameter as follows:

MaxAuthTries 4

Default Value:

MaxAuthTries 6

CIS Controls:

Version 6

16 Account Monitoring and Control

Account Monitoring and Control

Version 7

16.13 Alert on Account Login Behavior Deviation

Alert when users deviate from normal login behavior, such as time-of-day, workstation location and duration.

5.2.8 Ensure SSH IgnoreRhosts is enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The IgnoreRhosts parameter specifies that .rhosts and .shosts files will not be used in RhostsRSAAuthentication or HostbasedAuthentication.

Rationale:

Setting this parameter forces users to enter a password when authenticating with ssh.

Audit:

Run the following command and verify that output matches:

```
# sshd -T | grep ignorerhosts

IgnoreRhosts yes
```

Remediation:

Edit the /etc/ssh/sshd config file to set the parameter as follows:

IgnoreRhosts yes

Default Value:

IgnoreRhosts yes

CIS Controls:

Version 6

9 <u>Limitation and Control of Network Ports, Protocols, and Services</u> Limitation and Control of Network Ports, Protocols, and Services

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

5.2.9 Ensure SSH HostbasedAuthentication is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The HostbasedAuthentication parameter specifies if authentication is allowed through trusted hosts via the user of .rhosts, or /etc/hosts.equiv, along with successful public key client host authentication. This option only applies to SSH Protocol Version 2.

Rationale:

Even though the .rhosts files are ineffective if support is disabled in /etc/pam.conf, disabling the ability to use .rhosts files in SSH provides an additional layer of protection.

Audit:

Run the following command and verify that output matches:

sshd -T | grep hostbasedauthentication
HostbasedAuthentication no

Edit the /etc/ssh/sshd config file to set the parameter as follows:

HostbasedAuthentication no

Default Value:

HostbasedAuthentication no

CIS Controls:

Version 6

9 <u>Limitation and Control of Network Ports, Protocols, and Services</u> Limitation and Control of Network Ports, Protocols, and Services

Version 7

16.3 Require Multi-factor Authentication

Require multi-factor authentication for all user accounts, on all systems, whether managed onsite or by a third-party provider.

5.2.10 Ensure SSH root login is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The PermitRootLogin parameter specifies if the root user can log in using ssh. The default is no.

Rationale:

Disallowing root logins over SSH requires system admins to authenticate using their own individual account, then escalating to root via <code>sudo</code> or <code>su</code>. This in turn limits opportunity for non-repudiation and provides a clear audit trail in the event of a security incident

Audit:

Run the following command and verify that output matches:

sshd -T | grep permitrootlogin
PermitRootLogin no

Edit the /etc/ssh/sshd config file to set the parameter as follows:

PermitRootLogin no

Default Value:

PermitRootLogin without-password

CIS Controls:

Version 6

5.8 Administrators Should Not Directly Log In To A System (i.e. use RunAs/sudo)

Administrators should be required to access a system using a fully logged and non-administrative account. Then, once logged on to the machine without administrative privileges, the administrator should transition to administrative privileges using tools such as Sudo on Linux/UNIX, RunAs on Windows, and other similar facilities for other types of systems.

Version 7

4.3 Ensure the Use of Dedicated Administrative Accounts

Ensure that all users with administrative account access use a dedicated or secondary account for elevated activities. This account should only be used for administrative activities and not internet browsing, email, or similar activities.

5.2.11 Ensure SSH PermitEmptyPasswords is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The PermitEmptyPasswords parameter specifies if the SSH server allows login to accounts with empty password strings.

Rationale:

Disallowing remote shell access to accounts that have an empty password reduces the probability of unauthorized access to the system

Audit:

Run the following command and verify that output matches:

sshd -T | grep permitemptypasswords
PermitEmptyPasswords no

Edit the /etc/ssh/sshd config file to set the parameter as follows:

PermitEmptyPasswords no

Default Value:

PermitEmptyPasswords no

CIS Controls:

Version 6

 $16\,\underline{Account\,Monitoring\,and\,Control}$

Account Monitoring and Control

Version 7

16.3 Require Multi-factor Authentication

Require multi-factor authentication for all user accounts, on all systems, whether managed onsite or by a third-party provider.

5.2.12 Ensure SSH PermitUserEnvironment is disabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The PermituserEnvironment option allows users to present environment options to the ssh daemon.

Rationale:

Permitting users the ability to set environment variables through the SSH daemon could potentially allow users to bypass security controls (e.g. setting an execution path that has ssh executing trojan'd programs)

Audit:

Run the following command and verify that output matches:

sshd -T | grep permituserenvironment

PermitUserEnvironment no

Edit the /etc/ssh/sshd config file to set the parameter as follows:

PermitUserEnvironment no

Default Value:

PermitUserEnvironment no

CIS Controls:

Version 6

16 Account Monitoring and Control

Account Monitoring and Control

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.2.13 Ensure only strong Ciphers are used (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

This variable limits the ciphers that SSH can use during communication.

Rationale:

Weak ciphers that are used for authentication to the cryptographic module cannot be relied upon to provide confidentiality or integrity, and system data may be compromised

The DES, Triple DES, and Blowfish ciphers, as used in SSH, have a birthday bound of approximately four billion blocks, which makes it easier for remote attackers to obtain cleartext data via a birthday attack against a long-duration encrypted session, aka a "Sweet32" attack

The RC4 algorithm, as used in the TLS protocol and SSL protocol, does not properly combine state data with key data during the initialization phase, which makes it easier for remote attackers to conduct plaintext-recovery attacks against the initial bytes of a stream by sniffing network traffic that occasionally relies on keys affected by the Invariance Weakness, and then using a brute-force approach involving LSB values, aka the "Bar Mitzvah" issue

The passwords used during an SSH session encrypted with RC4 can be recovered by an attacker who is able to capture and replay the session

Error handling in the SSH protocol; Client and Server, when using a block cipher algorithm in Cipher Block Chaining (CBC) mode, makes it easier for remote attackers to recover certain plaintext data from an arbitrary block of ciphertext in an SSH session via unknown vectors

The mm_newkeys_from_blob function in monitor_wrap.c, when an AES-GCM cipher is used, does not properly initialize memory for a MAC context data structure, which allows remote authenticated users to bypass intended ForceCommand and login-shell restrictions via packet data that provides a crafted callback address

Audit:

Run the following command and verify that output does not contain any of the listed weak ciphers

```
# sshd -T | grep ciphers
```

Weak Ciphers:

```
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

Remediation:

Edit the /etc/ssh/sshd_config file add/modify the Ciphers line to contain a comma separated list of the site approved ciphers

Example:

```
Ciphers chacha20-poly1305@openssh.com,aes256-gcm@openssh.com,aes128-gcm@openssh.com,aes256-ctr,aes192-ctr,aes128-ctr
```

Default Value:

Ciphers chacha20-poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openssh.com,aes256-gcm@openssh.com,aes128-cbc,aes192-cbc,aes256-cbc,blowfish-cbc,cast128-cbc,3des-cbc

References:

- 1. https://nvd.nist.gov/vuln/detail/CVE-2016-2183
- 2. https://nvd.nist.gov/vuln/detail/CVE-2015-2808
- 3. https://www.kb.cert.org/vuls/id/565052
- 4. https://www.openssh.com/txt/cbc.adv
- 5. https://nvd.nist.gov/vuln/detail/CVE-2008-5161
- 6. https://nvd.nist.gov/vuln/detail/CVE-2013-4548
- 7. https://www.kb.cert.org/vuls/id/565052
- 8. https://www.openssh.com/txt/cbc.adv
- 9. SSHD_CONFIG(5)

Notes:

Some organizations may have stricter requirements for approved ciphers. Ensure that ciphers used are in compliance with site policy.

The only "strong" ciphers currently FIPS 140-2 compliant are: aes256-ctr,aes192-ctr,aes128-ctr

CVE-2013-4548 referenced above applies to OpenSSH versions 6.2 and 6.3. If running these versions of Open SSH, Please upgrade to version 6.4 or later to fix the vulnerability, or disable AES-GCM in the server configuration.

The Following are the supported ciphers in openSSH:

```
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
aes128-ctr
aes192-ctr
aes256-ctr
aes128-gcm@openssh.com
aes256-gcm@openssh.com
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
chacha20-poly1305@openssh.com
```

CIS Controls:

Version 6

3.4 <u>Use Only Secure Channels For Remote System Administration</u>

Perform all remote administration of servers, workstation, network devices, and similar equipment over secure channels. Protocols such as telnet, VNC, RDP, or others that do not actively support strong encryption should only be used if they are performed over a secondary encryption channel, such as SSL, TLS or IPSEC.

Version 7

14.4 Encrypt All Sensitive Information in Transit Encrypt all sensitive information in transit.

5.2.14 Ensure only strong MAC algorithms are used (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

This variable limits the types of MAC algorithms that SSH can use during communication.

Rationale:

MD5 and 96-bit MAC algorithms are considered weak and have been shown to increase exploitability in SSH downgrade attacks. Weak algorithms continue to have a great deal of attention as a weak spot that can be exploited with expanded computing power. An attacker that breaks the algorithm could take advantage of a MiTM position to decrypt the SSH tunnel and capture credentials and information

Audit:

Run the following command and verify that output does not contain any of the listed weak MAC algorithms:

```
# sshd -T | grep -i "MACs"
```

Weak MAC algorithms:

```
hmac-md5
hmac-ripemd160
hmac-sha1
hmac-sha1-96
umac-64@openssh.com
umac-128@openssh.com
hmac-md5-etm@openssh.com
hmac-md5-etm@openssh.com
hmac-ripemd160-etm@openssh.com
hmac-sha1-etm@openssh.com
hmac-sha1-etm@openssh.com
umac-64-etm@openssh.com
umac-128-etm@openssh.com
```

Edit the /etc/ssh/sshd_config file and add/modify the MACs line to contain a comma separated list of the site approved MACs Example:

MACs hmac-sha2-512-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512,hmac-sha2-256

Default Value:

MACs umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1,hmac-sha1-etm@openssh.com

References:

- 1. More information on SSH downgrade attacks can be found here: http://www.mitls.org/pages/attacks/SLOTH
- 2. SSHD_CONFIG(5)

Notes:

Some organizations may have stricter requirements for approved MACs. Ensure that MACs used are in compliance with site policy.

The only "strong" MACs currently FIPS 140-2 approved are hmac-sha2-256 and hmac-sha2-512

The Supported MACs are:

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-sha1
hmac-shal-96
hmac-sha2-256
hmac-sha2-512
umac-64@openssh.com
umac-128@openssh.com
hmac-md5-etm@openssh.com
hmac-md5-96-etm@openssh.com
hmac-ripemd160-etm@openssh.com
hmac-shal-etm@openssh.com
hmac-shal-96-etm@openssh.com
hmac-sha2-256-etm@openssh.com
hmac-sha2-512-etm@openssh.com
umac-64-etm@openssh.com
umac-128-etm@openssh.com
```

CIS Controls:

Version 6

3.4 <u>Use Only Secure Channels For Remote System Administration</u>

Perform all remote administration of servers, workstation, network devices, and similar equipment over secure channels. Protocols such as telnet, VNC, RDP, or others that do not actively support strong encryption should only be used if they are performed over a secondary encryption channel, such as SSL, TLS or IPSEC.

Version 7

14.4 Encrypt All Sensitive Information in Transit

Encrypt all sensitive information in transit.

16.5 Encrypt Transmittal of Username and Authentication Credentials

Ensure that all account usernames and authentication credentials are transmitted across networks using encrypted channels.

5.2.15 Ensure only strong Key Exchange algorithms are used (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Key exchange is any method in cryptography by which cryptographic keys are exchanged between two parties, allowing use of a cryptographic algorithm. If the sender and receiver wish to exchange encrypted messages, each must be equipped to encrypt messages to be sent and decrypt messages received

Rationale:

Key exchange methods that are considered weak should be removed. A key exchange method may be weak because too few bits are used, or the hashing algorithm is considered too weak. Using weak algorithms could expose connections to man-in-the-middle attacks

Audit:

Run the following command and verify that output does not contain any of the listed weak Key Exchange algorithms

```
# sshd -T | grep kexalgorithms
```

Weak Key Exchange Algorithms:

```
diffie-hellman-group1-shal
diffie-hellman-group14-shal
diffie-hellman-group-exchange-shal
```

Edit the /etc/ssh/sshd_config file add/modify the KexAlgorithms line to contain a comma separated list of the site approved key exchange algorithms

Example:

KexAlgorithms curve25519-sha256,curve25519-sha256@libssh.org,diffie-hellman-group14-sha256,diffie-hellman-group16-sha512,diffie-hellman-group18-sha512,ecdh-sha2-nistp521,ecdh-sha2-nistp384,ecdh-sha2-nistp256,diffie-hellman-group-exchange-sha256

Default Value:

KexAlgorithms curve 25519-sha 256, curve 25519-sha 256@libssh.org, ecdh-sha 2-nistp 256, ecdh-sha 2-nistp 384, ecdh-sha 2-nistp 521, diffie-hellman-group-exchange-sha 256, diffie-hellman-group 14-sha 1, diffie-hellman-group 1-sha 1

Notes:

Kex algorithms have a higher preference the earlier they appear in the list

Some organizations may have stricter requirements for approved Key exchange algorithms. Ensure that Key exchange algorithms used are in compliance with site policy.

The only Key Exchange Algorithms currently FIPS 140-2 approved are: ecdh-sha2-nistp256,ecdh-sha2-nistp384,ecdh-sha2-nistp521,diffie-hellman-group-exchange-sha256,diffie-hellman-group16-sha512,diffie-hellman-group18-sha512,diffie-hellman-group14-sha256

The Key Exchange algorithms supported by OpenSSH 7 are:

```
curve25519-sha256@libssh.org
diffie-hellman-group1-sha1
diffie-hellman-group14-sha1
diffie-hellman-group-exchange-sha1
diffie-hellman-group-exchange-sha256
ecdh-sha2-nistp256
ecdh-sha2-nistp384
ecdh-sha2-nistp521
```

CIS Controls:

Version 6

3.4 <u>Use Only Secure Channels For Remote System Administration</u>

Perform all remote administration of servers, workstation, network devices, and similar equipment over secure channels. Protocols such as telnet, VNC, RDP, or others that do not actively support strong encryption should only be used if they are performed over a secondary encryption channel, such as SSL, TLS or IPSEC.

Version 7

14.4 Encrypt All Sensitive Information in Transit Encrypt all sensitive information in transit.

5.2.16 Ensure SSH Idle Timeout Interval is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The two options <code>ClientAliveInterval</code> and <code>ClientAliveCountMax</code> control the timeout of ssh sessions. When the <code>ClientAliveInterval</code> variable is set, ssh sessions that have no activity for the specified length of time are terminated. When the <code>ClientAliveCountMax</code> variable is set, <code>sshd</code> will send client alive messages at every <code>ClientAliveInterval</code> interval. When the number of consecutive client alive messages are sent with no response from the client, the <code>ssh</code> session is terminated. For example, if the <code>ClientAliveInterval</code> is set to 15 seconds and the <code>ClientAliveCountMax</code> is set to 3, the client <code>ssh</code> session will be terminated after 45 seconds of idle time.

Rationale:

Having no timeout value associated with a connection could allow an unauthorized user access to another user's ssh session (e.g. user walks away from their computer and doesn't lock the screen). Setting a timeout value at least reduces the risk of this happening.

While the recommended setting is 300 seconds (5 minutes), set this timeout value based on site policy. The recommended setting for ClientAliveCountMax is 0. In this case, the client session will be terminated after 5 minutes of idle time and no keepalive messages will be sent.

Audit:

Run the following commands and verify ClientAliveInterval is between 1 and 300 and ClientAliveCountMax is 3 or less:

```
# sshd -T | grep clientaliveinterval
ClientAliveInterval 300
# sshd -T | grep clientalivecountmax
ClientAliveCountMax 0
```

Edit the /etc/ssh/sshd config file to set the parameters according to site policy:

ClientAliveInterval 300

ClientAliveCountMax 0

Default Value:

ClientAliveInterval 300

ClientAliveCountMax 0

CIS Controls:

Version 6

16.4 Automatically Log Off Users After Standard Period Of Inactivity

Regularly monitor the use of all accounts, automatically logging off users after a standard period of inactivity.

Version 7

16.11 Lock Workstation Sessions After Inactivity

Automatically lock workstation sessions after a standard period of inactivity.

5.2.17 Ensure SSH LoginGraceTime is set to one minute or less (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The LoginGraceTime parameter specifies the time allowed for successful authentication to the SSH server. The longer the Grace period is the more open unauthenticated connections can exist. Like other session controls in this session the Grace Period should be limited to appropriate organizational limits to ensure the service is available for needed access.

Rationale:

Setting the LoginGraceTime parameter to a low number will minimize the risk of successful brute force attacks to the SSH server. It will also limit the number of concurrent unauthenticated connections While the recommended setting is 60 seconds (1 Minute), set the number based on site policy.

Audit:

Run the following command and verify that output LoginGraceTime is between 1 and 60:

```
# sshd -T | grep logingracetime
LoginGraceTime 60
```

Edit the /etc/ssh/sshd config file to set the parameter as follows:

LoginGraceTime 60

Default Value:

LoginGraceTime 120

CIS Controls:

Version 6

16 Account Monitoring and Control

Account Monitoring and Control

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.2.18 Ensure SSH access is limited (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

There are several options available to limit which users and group can access the system via SSH. It is recommended that at least one of the following options be leveraged:

AllowUsers

The AllowUsers variable gives the system administrator the option of allowing specific users to ssh into the system. The list consists of space separated user names. Numeric user IDs are not recognized with this variable. If a system administrator wants to restrict user access further by only allowing the allowed users to log in from a particular host, the entry can be specified in the form of user@host.

AllowGroups

The AllowGroups variable gives the system administrator the option of allowing specific groups of users to ssh into the system. The list consists of space separated group names. Numeric group IDs are not recognized with this variable.

DenyUsers

The <code>DenyUsers</code> variable gives the system administrator the option of denying specific users to <code>ssh</code> into the system. The list consists of space separated user names. Numeric user IDs are not recognized with this variable. If a system administrator wants to restrict user access further by specifically denying a user's access from a particular host, the entry can be specified in the form of user@host.

DenyGroups

The DenyGroups variable gives the system administrator the option of denying specific groups of users to ssh into the system. The list consists of space separated group names. Numeric group IDs are not recognized with this variable.

Rationale:

Restricting which users can remotely access the system via SSH will help ensure that only authorized users access the system.

Audit:

Run the following commands and verify that output matches for at least one:

```
# sshd -T | grep allowusers
AllowUsers <userlist>
# sshd -T | grep allowgroups
AllowGroups <grouplist>
# sshd -T | grep denyusers
DenyUsers <userlist>
# sshd -T | grep denygroups
DenyGroups <grouplist>
```

Edit the /etc/ssh/sshd config file to set one or more of the parameter as follows:

```
AllowUsers <userlist>
AllowGroups <grouplist>
DenyUsers <userlist>
DenyGroups <grouplist>
```

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

5.8 Administrators Should Not Directly Log In To A System (i.e. use RunAs/sudo)

Administrators should be required to access a system using a fully logged and non-administrative account. Then, once logged on to the machine without administrative privileges, the administrator should transition to administrative privileges using tools such as Sudo on Linux/UNIX, RunAs on Windows, and other similar facilities for other types of systems.

Version 7

4.3 Ensure the Use of Dedicated Administrative Accounts

Ensure that all users with administrative account access use a dedicated or secondary account for elevated activities. This account should only be used for administrative activities and not internet browsing, email, or similar activities.

5.2.19 Ensure SSH warning banner is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The Banner parameter specifies a file whose contents must be sent to the remote user before authentication is permitted. By default, no banner is displayed.

Rationale:

Banners are used to warn connecting users of the particular site's policy regarding connection. Presenting a warning message prior to the normal user login may assist the prosecution of trespassers on the computer system.

Audit:

Run the following command and verify that output matches:

```
# sshd -T | grep banner
Banner /etc/issue.net
```

Edit the /etc/ssh/sshd config file to set the parameter as follows:

Banner /etc/issue.net

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.2.20 Ensure SSH PAM is enabled (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

UsePAM Enables the Pluggable Authentication Module interface. If set to "yes" this will enable PAM authentication using ChallengeResponseAuthentication and PasswordAuthentication in addition to PAM account and session module processing for all authentication types

Rationale:

When usePAM is set to yes, PAM runs through account and session types properly. This is important if you want to restrict access to services based off of IP, time or other factors of the account. Additionally, you can make sure users inherit certain environment variables on login or disallow access to the server

Audit:

Run the following command and verify that output matches:

```
# sshd -T | grep -i usepam
usepam yes
```

Edit the /etc/ssh/sshd_config file to set the parameter as follows:

UsePAM yes

Impact:

If UsePAM is enabled, you will not be able to run sshd(8) as a non-root user.

Default Value:

usePAM yes

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 <u>Establish Secure Configurations</u>

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.2.21 Ensure SSH AllowTcpForwarding is disabled (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

SSH port forwarding is a mechanism in SSH for tunneling application ports from the client to the server, or servers to clients. It can be used for adding encryption to legacy applications, going through firewalls, and some system administrators and IT professionals use it for opening backdoors into the internal network from their home machines

Rationale:

Leaving port forwarding enabled can expose the organization to security risks and backdoors.

SSH connections are protected with strong encryption. This makes their contents invisible to most deployed network monitoring and traffic filtering solutions. This invisibility carries considerable risk potential if it is used for malicious purposes such as data exfiltration. Cybercriminals or malware could exploit SSH to hide their unauthorized communications, or to exfiltrate stolen data from the target network

Audit:

Run the following command and verify that output matches:

```
# sshd -T | grep -i allowtcpforwarding

AllowTcpForwarding no
```

Edit the /etc/ssh/sshd_config file to set the parameter as follows:

AllowTcpForwarding no

Impact:

SSH tunnels are widely used in many corporate environments that employ mainframe systems as their application backends. In those environments the applications themselves may have very limited native support for security. By utilizing tunneling, compliance with SOX, HIPAA, PCI-DSS, and other standards can be achieved without having to modify the applications.

Default Value:

AllowTcpForwarding yes

References:

1. https://www.ssh.com/ssh/tunneling/example

CIS Controls:

Version 6

16 Account Monitoring and Control
Account Monitoring and Control

Version 7

9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.

5.2.22 Ensure SSH MaxStartups is configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The MaxStartups parameter specifies the maximum number of concurrent unauthenticated connections to the SSH daemon.

Rationale:

To protect a system from denial of service due to a large number of pending authentication connection attempts, use the rate limiting function of MaxStartups to protect availability of sshd logins and prevent overwhelming the daemon.

Audit:

Run the following command and verify that output MaxStartups is 10:30:60 or matches site policy:

```
# sshd -T | grep -i maxstartups
# maxstartups 10:30:60
```

Edit the /etc/ssh/sshd config file to set the parameter as follows:

maxstartups 10:30:60

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.2.23 Ensure SSH MaxSessions is set to 4 or less (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The ${\tt MaxSessions}$ parameter specifies the maximum number of open sessions permitted from a given connection.

Rationale:

To protect a system from denial of service due to a large number of concurrent sessions, use the rate limiting function of MaxSessions to protect availability of sshd logins and prevent overwhelming the daemon.

Audit:

Run the following command and verify that output MaxSessions is 4 or less, or matches site policy:

```
# sshd -T | grep -i maxsessions
# maxsessions 4
```

Edit the /etc/ssh/sshd config file to set the parameter as follows:

MaxSessions 4

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.3 Configure PAM

PAM (Pluggable Authentication Modules) is a service that implements modular authentication modules on UNIX systems. PAM is implemented as a set of shared objects that are loaded and executed when a program needs to authenticate a user. Files for PAM are typically located in the /etc/pam.d directory. PAM must be carefully configured to secure system authentication. While this section covers some of PAM, please consult other PAM resources to fully understand the configuration capabilities.

5.3.1 Ensure password creation requirements are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The pam_cracklib.so module checks the strength of passwords. It performs checks such as making sure a password is not a dictionary word, it is a certain length, contains a mix of characters (e.g. alphabet, numeric, other) and more. The following are definitions of the pam cracklib.so options.

- try_first_pass retrieve the password from a previous stacked PAM module. If not available, then prompt the user for a password.
- retry=3 Allow 3 tries before sending back a failure.
- minlen=14 password must be 14 characters or more
- dcredit=-1 provide at least one digit
- ucredit=-1 provide at least one uppercase character
- ocredit=-1 provide at least one special character
- lcredit=-1 provide at least one lowercase character

The pam_pwquality.so module functions similarly but the minlen, dcredit, ucredit, ocredit, and lcredit parameters are stored in the /etc/security/pwquality.conf file.

The settings shown above are one possible policy. Alter these values to conform to your own organization's password policies.

Rationale:

Strong passwords protect systems from being hacked through brute force methods.

Audit:

Verify password creation requirements conform to organization policy and minlen is 14 or more. This setting is commonly configured with the pam cracklib.so or

 $\label{lem:pam_pwquality.so} \begin{center} pam_pwquality.so \begin{center} options found in /etc/pam.d/common-password or /etc/pam.d/system-auth. Examples: \end{center}$

```
password required pam_cracklib.so try_first_pass retry=3 minlen=14 dcredit=-1
ucredit=-1 ocredit=-1 lcredit=-1
password requisite pam_pwquality.so try_first_pass retry=3
```

 $If \verb|pam_pwquality.so| is in use also verify settings in /etc/security/pwquality.conf|:$

```
minlen = 14
dcredit = -1
ucredit = -1
ocredit = -1
lcredit = -1
```

Set password creation requirements to conform to site policy. Many distributions provide tools for updating PAM configuration, consult your documentation for details. If no tooling is provided edit the appropriate /etc/pam.d/ configuration file and add or modify the pam cracklib.so or pam pwquality.so lines to include the required options:

```
password required pam_cracklib.so try_first_pass retry=3 minlen=14 dcredit=-1
ucredit=-1 ocredit=-1 lcredit=-1
password requisite pam_pwquality.so try_first_pass retry=3
```

If pam pwquality.so is in use also configure settings in /etc/security/pwquality.conf:

```
minlen = 14
dcredit = -1
ucredit = -1
ocredit = -1
lcredit = -1
```

Notes:

Consult your documentation for the appropriate PAM file and module.

Additional module options may be set, recommendation requirements only cover including try first pass and minlen set to 14 or more.

Settings in /etc/security/pwquality.conf must use spaces around the = symbol.

CIS Controls:

Version 6

5.7 User Accounts Shall Use Long Passwords

Where multi-factor authentication is not supported, user accounts shall be required to use long passwords on the system (longer than 14 characters).

16.12 Use Long Passwords For All User Accounts

Where multi-factor authentication is not supported, user accounts shall be required to use long passwords on the system (longer than 14 characters).

Version 7

4.4 Use Unique Passwords

Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.

5.3.2 Ensure lockout for failed password attempts is configured (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Lock out users after *n* unsuccessful consecutive login attempts. The first sets of changes are made to the PAM configuration files. The second set of changes are applied to the program specific PAM configuration file. The second set of changes must be applied to each program that will lock out users. Check the documentation for each secondary program for instructions on how to configure them to work with PAM.

Set the lockout number to the policy in effect at your site.

Rationale:

Locking out user IDs after *n* unsuccessful consecutive login attempts mitigates brute force password attacks against your systems.

Audit:

Verify password lockouts are configured. These settings are commonly configured with the pam_tally2.so and pam_failock.so modules found in /etc/pam.d/common-auth or /etc/pam.d/system-auth and /etc/pam.d/password-auth. Examples:

```
auth required pam_tally2.so onerr=fail audit silent deny=5 unlock_time=900

auth required pam_faillock.so preauth audit silent deny=5 unlock_time=900

auth sufficient pam_unix.so

auth [default=die] pam_faillock.so authfail audit deny=5 unlock_time=900

auth sufficient pam faillock.so authsucc audit deny=5 unlock time=900
```

The pam faillock.so lines should surround a pam unix.so line as listed here.

Set password lockouts to conform to site policy. Many distributions provide tools for updating PAM configuration, consult your documentation for details. If no tooling is provided edit the appropriate /etc/pam.d/ configuration file and add or modify the pam tally2.so or pam faillock.so lines as appropriate:

```
auth required pam_tally2.so onerr=fail audit silent deny=5 unlock_time=900

auth required pam_faillock.so preauth audit silent deny=5 unlock_time=900

auth sufficient pam_unix.so

auth [default=die] pam_faillock.so authfail audit deny=5 unlock_time=900

auth sufficient pam faillock.so authsucc audit deny=5 unlock time=900
```

Notes:

Consult your documentation for the appropriate PAM file and module.

Additional module options may be set, recommendation only covers those listed here.

If a user has been locked out because they have reached the maximum consecutive failure count defined by deny= in the pam_tally2.so or pam_faillock.so module, the user can be unlocked by issuing the command pam_tally2 -u <username> --reset or faillock -u --reset respectively. This command sets the failed count to 0, effectively unlocking the user.

Use of the "audit" keyword may log credentials in the case of user error during authentication. This risk should be evaluated in the context of the site policies of your organization.

CIS Controls:

Version 6

16.7 Configure Account Lockouts

Use and configure account lockouts such that after a set number of failed login attempts the account is locked for a standard period of time.

Version 7

16.7 Establish Process for Revoking Access

Establish and follow an automated process for revoking system access by disabling accounts immediately upon termination or change of responsibilities of an employee or contractor . Disabling these accounts, instead of deleting accounts, allows preservation of audit trails.

5.3.3 Ensure password reuse is limited (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/security/opasswd file stores the users' old passwords and can be checked to ensure that users are not recycling recent passwords.

Rationale:

Forcing users not to reuse their past 5 passwords make it less likely that an attacker will be able to guess the password.

Note that these change only apply to accounts configured on the local system.

Audit:

Verify remembered password history is 5 or more. This setting is commonly configured with the pam_unix.so or pam_pwhistory.so remember options found in /etc/pam.d/common-password or /etc/pam.d/system-auth. Examples:

password required pam_pwhistory.so remember=5
password sufficient pam unix.so remember=5

Set remembered password history to conform to site policy. Many distributions provide tools for updating PAM configuration, consult your documentation for details. If no tooling is provided edit the appropriate /etc/pam.d/ configuration file and add or modify the pam pwhistory.so or pam unix.so lines to include the remember option:

```
password required pam_pwhistory.so remember=5
password sufficient pam_unix.so remember=5
```

Notes:

Consult your documentation for the appropriate PAM file and module.

Additional module options may be set, recommendation only covers those listed here.

CIS Controls:

Version 6

16 Account Monitoring and Control
Account Monitoring and Control

Version 7

16 Account Monitoring and Control
Account Monitoring and Control

5.3.4 Ensure password hashing algorithm is SHA-512 (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The commands below change password encryption from md5 to sha512 (a much stronger hashing algorithm). All existing accounts will need to perform a password change to upgrade the stored hashes to the new algorithm.

Rationale:

The SHA-512 algorithm provides much stronger hashing than MD5, thus providing additional protection to the system by increasing the level of effort for an attacker to successfully determine passwords.

Note that these change only apply to accounts configured on the local system.

Audit:

Verify password hashing algorithm is sha512. This setting is commonly configured with the pam_unix.so sha512 option found in /etc/pam.d/common-password or /etc/pam.d/system-auth and /etc/pam.d/password-auth. Example:

password sufficient pam unix.so sha512

Set password hashing algorithm to sha512. Many distributions provide tools for updating PAM configuration, consult your documentation for details. If no tooling is provided edit the appropriate /etc/pam.d/ configuration file and add or modify the pam_unix.so lines to include the sha512 option:

```
password sufficient pam unix.so sha512
```

Notes:

Consult your documentation for the appropriate PAM file and module.

Additional module options may be set, recommendation only covers those listed here.

If it is determined that the password algorithm being used is not SHA-512, once it is changed, it is recommended that all user ID's be immediately expired and forced to change their passwords on next login. To accomplish that, the following commands can be used. Any system accounts that need to be expired should be carefully done separately by the system administrator to prevent any potential problems.

```
# cat /etc/passwd | awk -F: '( $3 >= 500 && $1 != "nfsnobody" ) { print $1 }'
| xargs -n 1 chage -d 0
```

This command assumes a system UID split at 500. Some distributions split at UID 1000 instead, consult your documentation and/or the UID_MIN setting in /etc/login.defs to determine which is appropriate for you.

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

5.4 User Accounts and Environment

This section provides guidance on setting up secure defaults for system and user accounts and their environment.

5.4.1 Set Shadow Password Suite Parameters

While a majority of the password control parameters have been moved to PAM, some parameters are still available through the shadow password suite. Any changes made to /etc/login.defswill only be applied if the usermodcommand is used. If user IDs are added a different way, use the chagecommand to effect changes to individual user IDs.

5.4.1.1 Ensure password expiration is 365 days or less (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The PASS_MAX_DAYS parameter in /etc/login.defs allows an administrator to force passwords to expire once they reach a defined age. It is recommended that the PASS MAX DAYS parameter be set to less than or equal to 365 days.

Rationale:

The window of opportunity for an attacker to leverage compromised credentials or successfully compromise credentials via an online brute force attack is limited by the age of the password. Therefore, reducing the maximum age of a password also reduces an attacker's window of opportunity.

Audit:

Run the following command and verify PASS_MAX_DAYS conforms to site policy (no more than 365 days):

```
# grep PASS_MAX_DAYS /etc/login.defs
PASS_MAX_DAYS 365
```

Run the following command and Review list of users and PASS_MAX_DAYS to verify that all users' PASS_MAX_DAYS conforms to site policy (no more than 365 days):

```
# grep -E '^[^:]+:[^!*]' /etc/shadow | cut -d: -f1,5
<user>:<PASS_MAX_DAYS>
```

Set the PASS MAX DAYS parameter to conform to site policy in /etc/login.defs:

PASS MAX DAYS 365

Modify user parameters for all users with a password set to match:

chage --maxdays 365 <user>

Notes:

You can also check this setting in /etc/shadow directly. The 5th field should be 365 or less for all users with a password.

Note: A value of -1 will disable password expiration. Additionally the password expiration must be greater than the minimum days between password changes or users will be unable to change their password.

CIS Controls:

Version 6

16 Account Monitoring and Control

Account Monitoring and Control

Version 7

4.4 <u>Use Unique Passwords</u>

Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.

5.4.1.2 Ensure minimum days between password changes is 7 or more (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The PASS_MIN_DAYS parameter in /etc/login.defs allows an administrator to prevent users from changing their password until a minimum number of days have passed since the last time the user changed their password. It is recommended that PASS_MIN_DAYS parameter be set to 7 or more days.

Rationale:

By restricting the frequency of password changes, an administrator can prevent users from repeatedly changing their password in an attempt to circumvent password reuse controls.

Audit:

Run the following command and verify PASS_MIN_DAYS conforms to site policy (no less than 7 days):

```
# grep PASS_MIN_DAYS /etc/login.defs
PASS_MIN_DAYS 7
```

Run the following command and Review list of users and PAS_MIN_DAYS to Verify that all users' PAS_MIN_DAYS conform s to site policy (no less than 7 days):

```
# grep -E ^[^:]+:[^\!*] /etc/shadow | cut -d: -f1,4
<user>:<PASS_MIN_DAYS>
```

Set the PASS_MIN_DAYS parameter to $7 \ in \ / \text{etc/login.defs}$:

PASS MIN DAYS 7

Modify user parameters for all users with a password set to match:

chage --mindays 7 <user>

Notes:

You can also check this setting in /etc/shadow directly. The 4th field should be 7 or more for all users with a password.

CIS Controls:

Version 6

16 Account Monitoring and Control

Account Monitoring and Control

Version 7

4.4 <u>Use Unique Passwords</u>

Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.

5.4.1.3 Ensure password expiration warning days is 7 or more (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The PASS_WARN_AGE parameter in /etc/login.defs allows an administrator to notify users that their password will expire in a defined number of days. It is recommended that the PASS WARN AGE parameter be set to 7 or more days.

Rationale:

Providing an advance warning that a password will be expiring gives users time to think of a secure password. Users caught unaware may choose a simple password or write it down where it may be discovered.

Audit:

Run the following command and verify PASS_WARN_AGE conforms to site policy (No less than 7 days):

```
# grep PASS_WARN_AGE /etc/login.defs
PASS_WARN_AGE 7
```

Verify all users with a password have their number of days of warning before password expires set to 7 or more:

Run the following command and Review list of users and PASS_WARN_AGE to verify that all users' PASS_WARN_AGE conforms to site policy (No less than 7 days):

```
# grep -E ^[^:]+:[^\!*] /etc/shadow | cut -d: -f1,6

<user>:<PASS_WARN_AGE>
```

Set the PASS WARN AGE parameter to 7 in /etc/login.defs:

PASS WARN AGE 7

Modify user parameters for all users with a password set to match:

chage --warndays 7 <user>

Notes:

You can also check this setting in /etc/shadow directly. The 6th field should be 7 or more for all users with a password.

CIS Controls:

Version 6

16 Account Monitoring and Control

Account Monitoring and Control

Version 7

4.4 <u>Use Unique Passwords</u>

Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.

5.4.1.4 Ensure inactive password lock is 30 days or less (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

User accounts that have been inactive for over a given period of time can be automatically disabled. It is recommended that accounts that are inactive for 30 days after password expiration be disabled.

Rationale:

Inactive accounts pose a threat to system security since the users are not logging in to notice failed login attempts or other anomalies.

Audit:

Run the following command and verify INACTIVE conforms to sire policy (no more than 30 days):

```
# useradd -D | grep INACTIVE
INACTIVE=30
```

Verify all users with a password have Password inactive no more than 30 days after password expires:

Run the following command and Review list of users and INACTIVE to verify that all users' INACTIVE conforms to site policy (no more than 30 days):

```
# grep -E ^[^:]+:[^\!*] /etc/shadow | cut -d: -f1,7
<user>:<INACTIVE>
```

Run the following command to set the default password inactivity period to 30 days:

```
# useradd -D -f 30
```

Modify user parameters for all users with a password set to match:

```
# chage --inactive 30 <user>
```

Notes:

You can also check this setting in /etc/shadow directly. The 7th field should be 30 or less for all users with a password.

Note: A value of -1 would disable this setting.

CIS Controls:

Version 6

16 Account Monitoring and Control

Account Monitoring and Control

Version 7

4.4 <u>Use Unique Passwords</u>

Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.

5.4.1.5 Ensure all users last password change date is in the past (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

All users should have a password change date in the past.

Rationale:

If a users recorded password change date is in the future then they could bypass any set password expiration.

Audit:

Run the following command and verify nothing is returned

```
# for usr in $(cut -d: -f1 /etc/shadow); do [[ $(chage --list $usr | grep
'^Last password change' | cut -d: -f2) > $(date) ]] && echo "$usr :$(chage --
list $usr | grep '^Last password change' | cut -d: -f2)"; done
```

Remediation:

Investigate any users with a password change date in the future and correct them. Locking the account, expiring the password, or resetting the password manually may be appropriate.

CIS Controls:

Version 6

16 Account Monitoring and Control
Account Monitoring and Control

Version 7

4.4 <u>Use Unique Passwords</u>

Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.

5.4.2 Ensure system accounts are secured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

There are a number of accounts provided with most distributions that are used to manage applications and are not intended to provide an interactive shell.

Rationale:

It is important to make sure that accounts that are not being used by regular users are prevented from being used to provide an interactive shell. By default, most distributions set the password field for these accounts to an invalid string, but it is also recommended that the shell field in the password file be set to the nologin shell. This prevents the account from potentially being used to run any commands.

Audit:

Run the following commands and verify no results are returned:

```
awk -F: '($1!="root" && $1!="sync" && $1!="shutdown" && $1!="halt" && $1!~/^\+/ && $3<'"$(awk '/^\s*UID_MIN/{print $2}' /etc/login.defs)"' && $7!="'"$(which nologin)"'" && $7!="/bin/false") {print}' /etc/passwd

awk -F: '($1!="root" && $1!~/^\+/ && $3<'"$(awk '/^\s*UID_MIN/{print $2}' /etc/login.defs)"') {print $1}' /etc/passwd | xargs -I '{}' passwd -S '{}' | awk '($2!="L" && $2!="LK") {print $1}'
```

Run the commands appropriate for your distribution: Set the shell for any accounts returned by the audit to nologin:

```
# usermod -s $(which nologin) <user>
```

Lock any non root accounts returned by the audit:

```
# usermod -L <user>
```

The following command will set all system accounts to a non login shell:

```
awk -F: '($1!="root" && $1!="sync" && $1!="shutdown" && $1!="halt" &&
$1!~/^\+/ && $3<'"$(awk '/^\s*UID_MIN/{print $2}' /etc/login.defs)"' &&
$7!="'"$(which nologin)"'" && $7!="/bin/false") {print $1}' /etc/passwd |
while read user do usermod -s $(which nologin) $user done</pre>
```

The following command will automatically lock not root system accounts:

```
awk -F: '($1!="root" && $1!~/^\+/ && $3<'"$(awk '/^\s*UID MIN/{print $2}' /etc/login.defs)"') {print $1}' /etc/passwd | xargs -I '{}' passwd -S '{}' | awk '($2!="L" && $2!="LK") {print $1}' | while read user do usermod -L $user done
```

Notes:

The root, sync, shutdown, and halt users are exempted from requiring a non-login shell.

CIS Controls:

Version 6

16 Account Monitoring and Control
Account Monitoring and Control

Version 7

16 Account Monitoring and Control
Account Monitoring and Control

5.4.3 Ensure default group for the root account is GID 0 (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The usermod command can be used to specify which group the root user belongs to. This affects permissions of files that are created by the root user.

Rationale:

Using GID 0 for the root account helps prevent root -owned files from accidentally becoming accessible to non-privileged users.

Audit:

Run the following command and verify the result is 0:

```
# grep "^root:" /etc/passwd | cut -f4 -d:
0
```

Remediation:

Run the following command to set the root user default group to GID 0:

```
# usermod -g 0 root
```

CIS Controls:

Version 6

5 <u>Controlled Use of Administration Privileges</u> Controlled Use of Administration Privileges

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.4.4 Ensure default user umask is 027 or more restrictive (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The default <code>umask</code> determines the permissions of files created by users. The user creating the file has the discretion of making their files and directories readable by others via the chmod command. Users who wish to allow their files and directories to be readable by others by default may choose a different default umask by inserting the <code>umask</code> command into the standard shell configuration files (<code>.profile</code>, <code>.bashrc</code>, etc.) in their home directories.

Rationale:

Setting a very secure default value for <code>umask</code> ensures that users make a conscious choice about their file permissions. A default <code>umask</code> setting of <code>077</code> causes files and directories created by users to not be readable by any other user on the system. A <code>umask</code> of <code>027</code> would make files and directories readable by users in the same Unix group, while a <code>umask</code> of <code>022</code> would make files readable by every user on the system.

Audit:

Run the following commands and verify all umask lines returned are 027 or more restrictive.

```
# grep "umask" /etc/bashrc
umask 027
# grep "umask" /etc/profile /etc/profile.d/*.sh
umask 027
```

Edit the /etc/bashrc, /etc/profile and /etc/profile.d/*.sh files (and the appropriate files for any other shell supported on your system) and add or edit any umask parameters as follows:

umask 027

Notes:

The audit and remediation in this recommendation apply to bash and shell. If other shells are supported on the system, it is recommended that their configuration files also are checked.

Other methods of setting a default user umask exist however the shell configuration files are the last run and will override other settings if they exist therefor our recommendation is to configure in the shell configuration files. If other methods are in use in your environment they should be audited and the shell configs should be verified to not override.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

13 <u>Data Protection</u> Data Protection

5.4.5 Ensure default user shell timeout is 900 seconds or less (Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The default $\verb"tmout"$ determines the shell timeout for users. The TMOUT value is measured in seconds.

Rationale:

Having no timeout value associated with a shell could allow an unauthorized user access to another user's shell session (e.g. user walks away from their computer and doesn't lock the screen). Setting a timeout value at least reduces the risk of this happening.

Audit:

Run the following commands and verify all TMOUT lines returned are 900 or less and at least one exists in each file.

```
# grep "^TMOUT" /etc/bashrc
TMOUT=900

# grep "^TMOUT" /etc/profile
TMOUT=900
```

Edit the /etc/bashrc and /etc/profile files (and the appropriate files for any other shell supported on your system) and add or edit any umask parameters as follows:

TMOUT=900

Notes:

The audit and remediation in this recommendation apply to bash and shell. If other shells are supported on the system, it is recommended that their configuration files also are checked. Other methods of setting a timeout exist for other shells not covered here.

Ensure that the timeout conforms to your local policy.

CIS Controls:

Version 6

16.4 Automatically Log Off Users After Standard Period Of Inactivity

Regularly monitor the use of all accounts, automatically logging off users after a standard period of inactivity.

Version 7

16.11 Lock Workstation Sessions After Inactivity

Automatically lock workstation sessions after a standard period of inactivity.

5.5 Ensure root login is restricted to system console (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The file /etc/securetty contains a list of valid terminals that may be logged in directly as root.

Rationale:

Since the system console has special properties to handle emergency situations, it is important to ensure that the console is in a physically secure location and that unauthorized consoles have not been defined.

Audit:

cat /etc/securetty

Remediation:

Remove entries for any consoles that are not in a physically secure location.

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

5.6 Ensure access to the su command is restricted (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The \mathtt{su} command allows a user to run a command or shell as another user. The program has been superseded by \mathtt{sudo} , which allows for more granular control over privileged access. Normally, the \mathtt{su} command can be executed by any user. By uncommenting the $\mathtt{pam_wheel.so}$ statement in $/\mathtt{etc/pam.d/su}$, the \mathtt{su} command will only allow users in the wheel group to execute \mathtt{su} .

Rationale:

Restricting the use of \mathtt{su} , and using \mathtt{sudo} in its place, provides system administrators better control of the escalation of user privileges to execute privileged commands. The sudo utility also provides a better logging and audit mechanism, as it can log each command executed via \mathtt{sudo} , whereas \mathtt{su} can only record that a user executed the \mathtt{su} program.

Audit:

Run the following command and verify output includes matching line:

```
# grep pam_wheel.so /etc/pam.d/su
auth required pam_wheel.so use_uid
```

Run the following command and verify users in wheel group match site policy:

```
# grep wheel /etc/group
wheel:x:10:root,<user list>
```

Add the following line to the /etc/pam.d/su file:

auth required pam wheel.so use uid

Create a comma separated list of users in the wheel statement in the /etc/group file:

wheel:x:10:root,<user list>

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 <u>Establish Secure Configurations</u>

Maintain documented, standard security configuration standards for all authorized operating systems and software.

6 System Maintenance

Recommendations in this section are intended as maintenance and are intended to be checked on a frequent basis to ensure system stability. Many recommendations do not have quick remediations and require investigation into the cause and best fix available and may indicate an attempted breach of system security.

6.1 System File Permissions

This section provides guidance on securing aspects of system files and directories.

6.1.1 Audit system file permissions (Not Scored)

Profile Applicability:

- Level 2 Server
- Level 2 Workstation

Description:

The RPM and Debian package managers have a number of useful options. One of these, the <code>--verify</code> (or <code>-v</code> for RPM) option, can be used to verify that system packages are correctly installed. The <code>--verify</code> option can be used to verify a particular package or to verify all system packages. If no output is returned, the package is installed correctly. The following table describes the meaning of output from the verify option:

```
Code
       Meaning
S
       File size differs.
       File mode differs (includes permissions and file type).
Μ
5
       The MD5 checksum differs.
       The major and minor version numbers differ on a device file.
D
       A mismatch occurs in a link.
L
U
       The file ownership differs.
G
       The file group owner differs.
       The file time (mtime) differs.
```

The ${\tt rpm}$ -qf or dpkg -s command can be used to determine which package a particular file belongs to. For example the following commands determines which package the /bin/bash file belongs to:

```
# rpm -qf /bin/bash
bash-4.1.2-29.el6.x86_64
# dpkg -S /bin/bash
bash: /bin/bash
```

To verify the settings for the package that controls the /bin/bash file, run the following:

```
# rpm -V bash-4.1.2-29.el6.x86_64
.M..... /bin/bash
# dpkg --verify bash
??5?????? c /etc/bash.bashrc
```

Note that you can feed the output of the rpm -qf command to the rpm -v command:

```
# rpm -V `rpm -qf /etc/passwd`
.M..... c /etc/passwd
S.5....T c /etc/printcap
```

Rationale:

It is important to confirm that packaged system files and directories are maintained with the permissions they were intended to have from the OS vendor.

Audit:

Run one of the following commands to review all installed packages. Note that this may be very time consuming and may be best scheduled via the <code>cron</code> utility. It is recommended that the output of this command be redirected to a file that can be reviewed later.

```
# rpm -Va --nomtime --nosize --nomd5 --nolinkto > <filename>
# dpkg --verify > <filename>
```

Correct any discrepancies found and rerun the audit until output is clean or risk is mitigated or accepted.

References:

1. http://docs.fedoraproject.org/en-US/Fedora Draft Documentation/0.1/html/RPM Guide/index.html

Notes:

Since packages and important files may change with new updates and releases, it is recommended to verify everything, not just a finite list of files. This can be a time consuming task and results may depend on site policy therefore it is not a scorable benchmark item, but is provided for those interested in additional security measures.

Some of the recommendations of this benchmark alter the state of files audited by this recommendation. The audit command will alert for all changes to a file permissions even if the new state is more secure than the default.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

6.1.2 Ensure permissions on /etc/passwd are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/passwd file contains user account information that is used by many system utilities and therefore must be readable for these utilities to operate.

Rationale:

It is critical to ensure that the /etc/passwd file is protected from unauthorized write access. Although it is protected by default, the file permissions could be changed either inadvertently or through malicious actions.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access is 644:

```
# stat /etc/passwd
Access: (0644/-rw-r--r--) Uid: ( 0/ root) Gid: ( 0/ root)
```

Remediation:

Run the following command to set permissions on /etc/passwd:

```
# chown root:root /etc/passwd
# chmod 644 /etc/passwd
```

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

6.1.3 Ensure permissions on /etc/shadow are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/shadow file is used to store the information about user accounts that is critical to the security of those accounts, such as the hashed password and other security information.

Rationale:

If attackers can gain read access to the /etc/shadow file, they can easily run a password cracking program against the hashed password to break it. Other security information that is stored in the /etc/shadow file (such as expiration) could also be useful to subvert the user accounts.

Audit:

Run the following command and verify verify Uid is 0/root, Gid is 0/root or <gid>/shadow, and Access is 640 or more restrictive:

```
# stat /etc/shadow
Access: (0640/-rw-r----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the one of the following chown commands as appropriate and the chmod to set permissions on /etc/shadow:

```
# chown root:root /etc/shadow
# chown root:shadow /etc/shadow
# chmod o-rwx,g-wx /etc/shadow
```

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

6.1.4 Ensure permissions on /etc/group are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/group file contains a list of all the valid groups defined in the system. The command below allows read/write access for root and read access for everyone else.

Rationale:

The /etc/group file needs to be protected from unauthorized changes by non-privileged users, but needs to be readable as this information is used with many non-privileged programs.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access is 644:

```
# stat /etc/group
Access: (0644/-rw-r--r--) Uid: ( 0/ root) Gid: ( 0/ root)
```

Remediation:

Run the following command to set permissions on /etc/group:

```
# chown root:root /etc/group
# chmod 644 /etc/group
```

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

6.1.5 Ensure permissions on /etc/gshadow are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/gshadow file is used to store the information about groups that is critical to the security of those accounts, such as the hashed password and other security information.

Rationale:

If attackers can gain read access to the /etc/gshadow file, they can easily run a password cracking program against the hashed password to break it. Other security information that is stored in the /etc/gshadow file (such as group administrators) could also be useful to subvert the group.

Audit:

Run the following command and verify Uid is 0/root, Gid is 0/root or <gid>/shadow, and Access is 640 or more restrictive:

```
# stat /etc/gshadow
Access: (0640/-rw-r----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the one of the following chown commands as appropriate and the chmod to set permissions on /etc/gshadow:

```
# chown root:root /etc/gshadow
# chown root:shadow /etc/gshadow
# chmod o-rwx,g-rw /etc/gshadow
```

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

6.1.6 Ensure permissions on /etc/passwd- are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/passwd- file contains backup user account information.

Rationale:

It is critical to ensure that the /etc/passwd- file is protected from unauthorized access. Although it is protected by default, the file permissions could be changed either inadvertently or through malicious actions.

Audit:

Run the following command and verify Uid and Gid are both 0/root and Access is 600 or more restrictive:

```
# stat /etc/passwd-
Access: (0600/-rw-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the following command to set permissions on /etc/passwd-:

```
# chown root:root /etc/passwd-
# chmod u-x,go-rwx /etc/passwd-
```

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials
Encrypt or hash with a salt all authentication credentials when stored.

6.1.7 Ensure permissions on /etc/shadow- are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/shadow- file is used to store backup information about user accounts that is critical to the security of those accounts, such as the hashed password and other security information.

Rationale:

It is critical to ensure that the /etc/shadow- file is protected from unauthorized access. Although it is protected by default, the file permissions could be changed either inadvertently or through malicious actions.

Audit:

Run the following command and verify verify Uid is 0/root, Gid is 0/root or <qid>/shadow, and Access is 640 or more restrictive:

```
# stat /etc/shadow-
Access: (0640/-rw-r----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the one of the following chown commands as appropriate and the chmod to set permissions on /etc/shadow-:

```
# chown root:root /etc/shadow-
# chown root:shadow /etc/shadow-
# chmod o-rwx,g-rw /etc/shadow-
```

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

6.1.8 Ensure permissions on /etc/group- are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/group- file contains a backup list of all the valid groups defined in the system.

Rationale:

It is critical to ensure that the /etc/group- file is protected from unauthorized access. Although it is protected by default, the file permissions could be changed either inadvertently or through malicious actions.

Audit:

Run the following command and verify Uid and Gid are both O/root and Access is 644 or more restrictive:

```
# stat /etc/group-
Access: (0644/-rw-----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Remediation:

Run the following command to set permissions on /etc/group-:

```
# chown root:root /etc/group-
# chmod u-x,go-wx /etc/group-
```

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

6.1.9 Ensure permissions on /etc/gshadow- are configured (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The /etc/gshadow- file is used to store backup information about groups that is critical to the security of those accounts, such as the hashed password and other security information.

Rationale:

It is critical to ensure that the /etc/gshadow- file is protected from unauthorized access. Although it is protected by default, the file permissions could be changed either inadvertently or through malicious actions.

Audit:

Run the following command and verify verify Uid is 0/root, Gid is 0/root or <gid>/shadow, and Access is 640 or more restrictive:

```
# stat /etc/gshadow-
Access: (0640/-rw-r----) Uid: ( 0/ root) Gid: ( 0/ root)
```

Run the one of the following chown commands as appropriate and the chmod to set permissions on /etc/gshadow-:

```
# chown root:root /etc/gshadow-
# chown root:shadow /etc/gshadow-
# chmod o-rwx,g-rw /etc/gshadow-
```

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

6.1.10 Ensure no world writable files exist (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Unix-based systems support variable settings to control access to files. World writable files are the least secure. See the chmod (2) man page for more information.

Rationale:

Data in world-writable files can be modified and compromised by any user on the system. World writable files may also indicate an incorrectly written script or program that could potentially be the cause of a larger compromise to the system's integrity.

Audit:

Run the following command and verify no files are returned:

```
# df --local -P | awk '{if (NR!=1) print $6}' | xargs -I '{}' find '{}' -xdev -type f -perm -0002
```

The command above only searches local filesystems, there may still be compromised items on network mounted partitions. Additionally the --local option to df is not universal to all versions, it can be omitted to search all filesystems on a system including network mounted filesystems or the following command can be run manually for each partition:

```
# find <partition> -xdev -type f -perm -0002
```

Removing write access for the "other" category (chmod o-w < filename>) is advisable, but always consult relevant vendor documentation to avoid breaking any application dependencies on a given file.

CIS Controls:

Version 6

14 <u>Controlled Access Based on the Need to Know</u> Controlled Access Based on the Need to Know

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

13 <u>Data Protection</u> Data Protection

6.1.11 Ensure no unowned files or directories exist (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Sometimes when administrators delete users from the password file they neglect to remove all files owned by those users from the system.

Rationale:

A new user who is assigned the deleted user's user ID or group ID may then end up "owning" these files, and thus have more access on the system than was intended.

Audit:

Run the following command and verify no files are returned:

```
# df --local -P | awk {'if (NR!=1) print $6'} | xargs -I '{}' find '{}' -xdev -nouser
```

The command above only searches local filesystems, there may still be compromised items on network mounted partitions. Additionally the --local option to df is not universal to all versions, it can be omitted to search all filesystems on a system including network mounted filesystems or the following command can be run manually for each partition:

```
# find <partition> -xdev -nouser
```

Locate files that are owned by users or groups not listed in the system configuration files, and reset the ownership of these files to some active user on the system as appropriate.

CIS Controls:

Version 6

14 <u>Controlled Access Based on the Need to Know</u> Controlled Access Based on the Need to Know

Version 7

13.2 Remove Sensitive Data or Systems Not Regularly Accessed by Organization Remove sensitive data or systems not regularly accessed by the organization from the network. These systems shall only be used as stand alone systems (disconnected from the network) by the business unit needing to occasionally use the system or completely virtualized and powered off until needed.

6.1.12 Ensure no ungrouped files or directories exist (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Sometimes when administrators delete users or groups from the system they neglect to remove all files owned by those users or groups.

Rationale:

A new user who is assigned the deleted user's user ID or group ID may then end up "owning" these files, and thus have more access on the system than was intended.

Audit:

Run the following command and verify no files are returned:

```
# df --local -P | awk '{if (NR!=1) print $6}' | xargs -I '{}' find '{}' -xdev -nogroup
```

The command above only searches local filesystems, there may still be compromised items on network mounted partitions. Additionally the --local option to df is not universal to all versions, it can be omitted to search all filesystems on a system including network mounted filesystems or the following command can be run manually for each partition:

```
# find <partition> -xdev -nogroup
```

Locate files that are owned by users or groups not listed in the system configuration files, and reset the ownership of these files to some active user on the system as appropriate.

CIS Controls:

Version 6

14 <u>Controlled Access Based on the Need to Know</u> Controlled Access Based on the Need to Know

Version 7

13.2 Remove Sensitive Data or Systems Not Regularly Accessed by Organization Remove sensitive data or systems not regularly accessed by the organization from the network. These systems shall only be used as stand alone systems (disconnected from the network) by the business unit needing to occasionally use the system or completely virtualized and powered off until needed.

6.1.13 Audit SUID executables (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The owner of a file can set the file's permissions to run with the owner's or group's permissions, even if the user running the program is not the owner or a member of the group. The most common reason for a SUID program is to enable users to perform functions (such as changing their password) that require root privileges.

Rationale:

There are valid reasons for SUID programs, but it is important to identify and review such programs to ensure they are legitimate.

Audit:

Run the following command to list SUID files:

```
# df --local -P | awk '{if (NR!=1) print $6}' | xargs -I '{}' find '{}' -xdev -type f -perm -4000
```

The command above only searches local filesystems, there may still be compromised items on network mounted partitions. Additionally the --local option to df is not universal to all versions, it can be omitted to search all filesystems on a system including network mounted filesystems or the following command can be run manually for each partition:

```
# find <partition> -xdev -type f -perm -4000
```

Ensure that no rogue SUID programs have been introduced into the system. Review the files returned by the action in the Audit section and confirm the integrity of these binaries.

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

6.1.14 Audit SGID executables (Not Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The owner of a file can set the file's permissions to run with the owner's or group's permissions, even if the user running the program is not the owner or a member of the group. The most common reason for a SGID program is to enable users to perform functions (such as changing their password) that require root privileges.

Rationale:

There are valid reasons for SGID programs, but it is important to identify and review such programs to ensure they are legitimate. Review the files returned by the action in the audit section and check to see if system binaries have a different md5 checksum than what from the package. This is an indication that the binary may have been replaced.

Audit:

Run the following command to list SGID files:

```
# df --local -P | awk '{if (NR!=1) print $6}' | xargs -I '{}' find '{}' -xdev -type f -perm -2000
```

The command above only searches local filesystems, there may still be compromised items on network mounted partitions. Additionally the --local option to df is not universal to all versions, it can be omitted to search all filesystems on a system including network mounted filesystems or the following command can be run manually for each partition:

```
# find <partition> -xdev -type f -perm -2000
```

Ensure that no rogue SGID programs have been introduced into the system. Review the files returned by the action in the Audit section and confirm the integrity of these binaries.

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

6.2 User and Group Settings

This section provides guidance on securing aspects of the users and groups.

Note: The recommendations in this section check local users and groups. Any users or groups from other sources such as LDAP will not be audited. In a domain environment similar checks should be performed against domain users and groups.

6.2.1 Ensure password fields are not empty (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

An account with an empty password field means that anybody may log in as that user without providing a password.

Rationale:

All accounts must have passwords or be locked to prevent the account from being used by an unauthorized user.

Audit:

Run the following command and verify that no output is returned:

```
\# awk -F: '($2 == "" ) { print $1 " does not have a password "}' /etc/shadow
```

Remediation:

If any accounts in the /etc/shadow file do not have a password, run the following command to lock the account until it can be determined why it does not have a password:

```
# passwd -l <username>
```

Also, check to see if the account is logged in and investigate what it is being used for to determine if it needs to be forced off.

CIS Controls:

Version 6

16 Account Monitoring and Control

Account Monitoring and Control

Version 7

4.4 <u>Use Unique Passwords</u>

Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.

6.2.2 Ensure no legacy "+" entries exist in /etc/passwd (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The character + in various files used to be markers for systems to insert data from NIS maps at a certain point in a system configuration file. These entries are no longer required on most systems, but may exist in files that have been imported from other platforms.

Rationale:

These entries may provide an avenue for attackers to gain privileged access on the system.

Audit:

Run the following command and verify that no output is returned:

grep '^\+:' /etc/passwd

Remediation:

Remove any legacy '+' entries from /etc/passwd if they exist.

CIS Controls:

Version 6

16.9 Configure Account Access Centrally

Configure access for all accounts through a centralized point of authentication, for example Active Directory or LDAP. Configure network and security devices for centralized authentication as well.

Version 7

16.2 Configure Centralized Point of Authentication

Configure access for all accounts through as few centralized points of authentication as possible, including network, security, and cloud systems.

6.2.3 Ensure no legacy "+" entries exist in /etc/shadow (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The character + in various files used to be markers for systems to insert data from NIS maps at a certain point in a system configuration file. These entries are no longer required on most systems, but may exist in files that have been imported from other platforms.

Rationale:

These entries may provide an avenue for attackers to gain privileged access on the system.

Audit:

Run the following command and verify that no output is returned:

grep '^\+:' /etc/shadow

Remediation:

Remove any legacy '+' entries from /etc/shadow if they exist.

CIS Controls:

Version 6

16.9 Configure Account Access Centrally

Configure access for all accounts through a centralized point of authentication, for example Active Directory or LDAP. Configure network and security devices for centralized authentication as well.

Version 7

16.2 Configure Centralized Point of Authentication

Configure access for all accounts through as few centralized points of authentication as possible, including network, security, and cloud systems.

6.2.4 Ensure no legacy "+" entries exist in /etc/group (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The character + in various files used to be markers for systems to insert data from NIS maps at a certain point in a system configuration file. These entries are no longer required on most systems, but may exist in files that have been imported from other platforms.

Rationale:

These entries may provide an avenue for attackers to gain privileged access on the system.

Audit:

Run the following command and verify that no output is returned:

grep '^\+:' /etc/group

Remediation:

Remove any legacy '+' entries from /etc/group if they exist.

CIS Controls:

Version 6

16.9 Configure Account Access Centrally

Configure access for all accounts through a centralized point of authentication, for example Active Directory or LDAP. Configure network and security devices for centralized authentication as well.

Version 7

16.2 Configure Centralized Point of Authentication

Configure access for all accounts through as few centralized points of authentication as possible, including network, security, and cloud systems.

6.2.5 Ensure root is the only UID 0 account (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Any account with UID 0 has superuser privileges on the system.

Rationale:

This access must be limited to only the default root account and only from the system console. Administrative access must be through an unprivileged account using an approved mechanism as noted in Item 5.6 Ensure access to the su command is restricted.

Audit:

Run the following command and verify that only "root" is returned:

```
# awk -F: '($3 == 0) { print $1 }' /etc/passwd root
```

Remediation:

Remove any users other than root with UID 0 or assign them a new UID if appropriate.

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

6.2.6 Ensure root PATH Integrity (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The root user can execute any command on the system and could be fooled into executing programs unintentionally if the PATH is not set correctly.

Rationale:

Including the current working directory (.) or other writable directory in root 's executable path makes it likely that an attacker can gain superuser access by forcing an administrator operating as root to execute a Trojan horse program.

Audit:

```
#!/bin/bash
if [ "$(echo "$PATH" | grep ::)" != "" ]; then
 echo "Empty Directory in PATH (::)"
if [ "$(echo "$PATH" | grep :$)" != "" ]; then
 echo "Trailing : in PATH"
fi
p=$(echo "$PATH" | sed -e 's/::/:/ -e 's/:$//' -e 's/:/ /g')
set -- $p
while [ "$1" != "" ]; do
  if [ "$1" = "." ]; then
    shift
  continue
 fi
  if [ -d "$1" ]; then
    dirperm=$(ls -ldH "$1" | cut -f1 -d" ")
    if [ "$(echo "$dirperm" | cut -c6)" != "-" ]; then
     echo "Group Write permission set on directory $1"
   if [ "$(echo "$dirperm" | cut -c9)" != "-" ]; then
    echo "Other Write permission set on directory $1"
   dirown=$(ls -ldH "$1" | awk '{print $3}')
    if [ "$dirown" != "root" ] ; then
      echo "$1 is not owned by root"
  else
    echo "$1 is not a directory"
  fi
  shift
done
```

Correct or justify any items discovered in the Audit step.

CIS Controls:

Version 6

5.1 <u>Minimize And Sparingly Use Administrative Privileges</u>

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

6.2.7 Ensure all users' home directories exist (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Users can be defined in /etc/passwd without a home directory or with a home directory that does not actually exist.

Rationale:

If the user's home directory does not exist or is unassigned, the user will be placed in "/" and will not be able to write any files or have local environment variables set.

Audit:

If any users' home directories do not exist, create them and make sure the respective user owns the directory. Users without an assigned home directory should be removed or assigned a home directory as appropriate.

Notes:

The audit script checks all users UID 500 and above except nfsnobody. Some distributions split at UID 1000 instead, consult your documentation and/or the UID_MIN setting in /etc/login.defs to determine which is appropriate for you.

On some distributions the /sbin/nologin should be replaced with /usr/sbin/nologin.

CIS Controls:

Version 6

13 <u>Data Protection</u> Data Protection

Version 7

5.1 <u>Establish Secure Configurations</u>

Maintain documented, standard security configuration standards for all authorized operating systems and software.

6.2.8 Ensure users' home directories permissions are 750 or more restrictive (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

While the system administrator can establish secure permissions for users' home directories, the users can easily override these.

Rationale:

Group or world-writable user home directories may enable malicious users to steal or modify other users' data or to gain another user's system privileges.

Audit:

```
#!/bin/bash
grep -E -v '^(halt|sync|shutdown)' /etc/passwd | awk -F: '($7 != "'"$(which
nologin)"'" && $7 != "/bin/false") { print $1 " " $6 }' | while read user
dir; do
  if [ ! -d "$dir" ]; then
    echo "The home directory ($dir) of user $user does not exist."
    dirperm=$(ls -ld $dir | cut -f1 -d" ")
    if [ $(echo $dirperm | cut -c6) != "-" ]; then
     echo "Group Write permission set on the home directory ($dir) of user
$user"
    if [ $(echo $dirperm | cut -c8) != "-" ]; then
     echo "Other Read permission set on the home directory ($dir) of user
$user"
    if [ $(echo $dirperm | cut -c9) != "-" ]; then
      echo "Other Write permission set on the home directory ($dir) of user
$user"
    if [ $(echo $dirperm | cut -c10) != "-" ]; then
     echo "Other Execute permission set on the home directory ($dir) of user
$user"
    fi
  fi
done
```

Making global modifications to user home directories without alerting the user community can result in unexpected outages and unhappy users. Therefore, it is recommended that a monitoring policy be established to report user file permissions and determine the action to be taken in accordance with site policy.

Notes:

On some distributions the /sbin/nologin should be replaced with /usr/sbin/nologin.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

6.2.9 Ensure users own their home directories (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The user home directory is space defined for the particular user to set local environment variables and to store personal files.

Rationale:

Since the user is accountable for files stored in the user home directory, the user must be the owner of the directory.

Audit:

```
#!/bin/bash
grep -E -v '^(halt|sync|shutdown)' /etc/passwd | awk -F: '($7 != "'"$(which nologin)"'" && $7 != "/bin/false") { print $1 " " $6 }' | while read user dir; do
  if [ ! -d "$dir" ]; then
    echo "The home directory ($dir) of user $user does not exist."
  else
    owner=$(stat -L -c "%U" "$dir")
    if [ "$owner" != "$user" ]; then
       echo "The home directory ($dir) of user $user is owned by $owner."
  fi
  fi
  done
```

Change the ownership of any home directories that are not owned by the defined user to the correct user.

Notes:

On some distributions the /sbin/nologin should be replaced with /usr/sbin/nologin.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

6.2.10 Ensure users' dot files are not group or world writable (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

While the system administrator can establish secure permissions for users' "dot" files, the users can easily override these.

Rationale:

Group or world-writable user configuration files may enable malicious users to steal or modify other users' data or to gain another user's system privileges.

Audit:

```
#!/bin/bash
grep -E -v '^(halt|sync|shutdown)' /etc/passwd | awk -F: '($7 != "'"$(which
nologin)"'" && $7 != "/bin/false") { print $1 " " $6 }' | while read user
  if [ ! -d "$dir" ]; then
    echo "The home directory ($dir) of user $user does not exist."
  else
    for file in $dir/.[A-Za-z0-9]*; do
     if [ ! -h "$file" -a -f "$file" ]; then
        fileperm=$(ls -ld $file | cut -f1 -d" ")
        if [ $(echo $fileperm | cut -c6) != "-" ]; then
         echo "Group Write permission set on file $file"
       fi
       if [ $(echo $fileperm | cut -c9) != "-" ]; then
         echo "Other Write permission set on file $file"
      fi
    done
  fi
done
```

Making global modifications to users' files without alerting the user community can result in unexpected outages and unhappy users. Therefore, it is recommended that a monitoring policy be established to report user dot file permissions and determine the action to be taken in accordance with site policy.

Notes:

On some distributions the /sbin/nologin should be replaced with /usr/sbin/nologin.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

6.2.11 Ensure no users have .forward files (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The .forward file specifies an email address to forward the user's mail to.

Rationale:

Use of the .forward file poses a security risk in that sensitive data may be inadvertently transferred outside the organization. The .forward file also poses a risk as it can be used to execute commands that may perform unintended actions.

Audit:

```
#!/bin/bash
grep -E -v '^(root|halt|sync|shutdown)' /etc/passwd | awk -F: '($7 !=
"'"$(which nologin)"'" && $7 != "/bin/false") { print $1 " " $6 }' | while
read user dir; do
  if [ ! -d "$dir" ]; then
    echo "The home directory ($dir) of user $user does not exist."
  else
    if [ ! -h "$dir/.forward" -a -f "$dir/.forward" ]; then
       echo ".forward file $dir/.forward exists"
    fi
  fi
  done
```

Making global modifications to users' files without alerting the user community can result in unexpected outages and unhappy users. Therefore, it is recommended that a monitoring policy be established to report user . forward files and determine the action to be taken in accordance with site policy.

Notes:

On some distributions the /sbin/nologin should be replaced with /usr/sbin/nologin.

CIS Controls:

Version 6

7 Email and Web Browser Protections
Email and Web Browser Protections

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

6.2.12 Ensure no users have .netrc files (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The .netrc file contains data for logging into a remote host for file transfers via FTP.

Rationale:

The .netrc file presents a significant security risk since it stores passwords in unencrypted form. Even if FTP is disabled, user accounts may have brought over .netrc files from other systems which could pose a risk to those systems.

Audit:

```
#!/bin/bash
grep -E -v '^(root|halt|sync|shutdown)' /etc/passwd | awk -F: '($7 !=
"'"$(which nologin)"'" && $7 != "/bin/false") { print $1 " " $6 }' | while
read user dir; do
  if [ ! -d "$dir" ]; then
    echo "The home directory ($dir) of user $user does not exist."
  else
    if [ ! -h "$dir/.netrc" -a -f "$dir/.netrc" ]; then
       echo ".netrc file $dir/.netrc exists"
    fi
  fi
  done
```

Making global modifications to users' files without alerting the user community can result in unexpected outages and unhappy users. Therefore, it is recommended that a monitoring policy be established to report user <code>.netrc</code> files and determine the action to be taken in accordance with site policy.

Notes:

On some distributions the /sbin/nologin should be replaced with /usr/sbin/nologin.

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

6.2.13 Ensure users' .netrc Files are not group or world accessible (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

While the system administrator can establish secure permissions for users' .netrc files, the users can easily override these.

Rationale:

.netrofiles may contain unencrypted passwords that may be used to attack other systems.

Audit:

```
#!/bin/bash
grep -E -v '^(root|halt|sync|shutdown)' /etc/passwd | awk -F: '($7 !=
"'"$(which nologin)"'" && $7 != "/bin/false") { print $1 " " $6 }' | while
read user dir; do
 if [ ! -d "$dir" ]; then
   echo "The home directory ($dir) of user $user does not exist."
  else
   for file in $dir/.netrc; do
      if [ ! -h "$file" -a -f "$file" ]; then
        fileperm=$(ls -ld $file | cut -f1 -d" ")
                                         != "-" ]; then
       if [ $(echo $fileperm | cut -c5)
          echo "Group Read set on $file"
        if [ $(echo $fileperm | cut -c6)
                                         != "-" ]; then
         echo "Group Write set on $file"
        if [ $(echo $fileperm | cut -c7) != "-" ]; then
         echo "Group Execute set on $file"
       if [ $(echo $fileperm | cut -c8) != "-" ]; then
         echo "Other Read set on $file"
       if [ $(echo $fileperm | cut -c9) != "-" ]; then
         echo "Other Write set on $file"
        if [ $(echo $fileperm | cut -c10) != "-" ]; then
          echo "Other Execute set on $file"
      fi
    done
  fi
done
```

Making global modifications to users' files without alerting the user community can result in unexpected outages and unhappy users. Therefore, it is recommended that a monitoring policy be established to report user <code>.netrc</code> file permissions and determine the action to be taken in accordance with site policy.

Notes:

While the complete removal of .netrc files is recommended if any are required on the system secure permissions must be applied.

On some distributions the /sbin/nologin should be replaced with /usr/sbin/nologin.

CIS Controls:

Version 6

14.4 Protect Information With Access Control Lists

All information stored on systems shall be protected with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

Version 7

14.6 Protect Information through Access Control Lists

Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.

6.2.14 Ensure no users have .rhosts files (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

While no .rhosts files are shipped by default, users can easily create them.

Rationale:

This action is only meaningful if .rhosts support is permitted in the file /etc/pam.conf . Even though the .rhosts files are ineffective if support is disabled in /etc/pam.conf , they may have been brought over from other systems and could contain information useful to an attacker for those other systems.

Audit:

```
#!/bin/bash
grep -E -v '^(root|halt|sync|shutdown)' /etc/passwd | awk -F: '($7 !=
"'"$(which nologin)"'" && $7 != "/bin/false") { print $1 " " $6 }' | while
read user dir; do
  if [ ! -d "$dir" ]; then
    echo "The home directory ($dir) of user $user does not exist."
  else
    for file in $dir/.rhosts; do
       if [ ! -h "$file" -a -f "$file" ]; then
        echo ".rhosts file in $dir"
       fi
       done
    fi
    done
```

Making global modifications to users' files without alerting the user community can result in unexpected outages and unhappy users. Therefore, it is recommended that a monitoring policy be established to report user .rhosts files and determine the action to be taken in accordance with site policy.

Notes:

On some distributions the /sbin/nologin should be replaced with /usr/sbin/nologin.

CIS Controls:

Version 6

16.14 Encrypt/Hash All Authentication Files And Monitor Their Access

Verify that all authentication files are encrypted or hashed and that these files cannot be accessed without root or administrator privileges. Audit all access to password files in the system.

Version 7

16.4 Encrypt or Hash all Authentication Credentials

Encrypt or hash with a salt all authentication credentials when stored.

6.2.15 Ensure all groups in /etc/passwd exist in /etc/group (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Over time, system administration errors and changes can lead to groups being defined in /etc/passwd but not in /etc/group.

Rationale:

Groups defined in the /etc/passwd file but not in the /etc/group file pose a threat to system security since group permissions are not properly managed.

Audit:

```
#!/bin/bash

for i in $(cut -s -d: -f4 /etc/passwd | sort -u ); do
  grep -q -P "^.*?:[^:]*:$i:" /etc/group
  if [ $? -ne 0 ]; then
    echo "Group $i is referenced by /etc/passwd but does not exist in
/etc/group"
  fi
done
```

Analyze the output of the Audit step above and perform the appropriate action to correct any discrepancies found.

CIS Controls:

Version 6

16 <u>Account Monitoring and Control</u> Account Monitoring and Control

Version 7

16 <u>Account Monitoring and Control</u> Account Monitoring and Control

6.2.16 Ensure no duplicate UIDs exist (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Although the useradd program will not let you create a duplicate User ID (UID), it is possible for an administrator to manually edit the /etc/passwd file and change the UID field.

Rationale:

Users must be assigned unique UIDs for accountability and to ensure appropriate access protections.

Audit:

```
#!/bin/bash

cut -f3 -d":" /etc/passwd | sort -n | uniq -c | while read x ; do
  [ -z "$x" ] && break
  set - $x
  if [ $1 -gt 1 ]; then
    users=$(awk -F: '($3 == n) { print $1 }' n=$2 /etc/passwd | xargs)
    echo "Duplicate UID ($2): $users"
  fi
done
```

Based on the results of the audit script, establish unique UIDs and review all files owned by the shared UIDs to determine which UID they are supposed to belong to.

CIS Controls:

Version 6

16 <u>Account Monitoring and Control</u> Account Monitoring and Control

Version 7

16 <u>Account Monitoring and Control</u> Account Monitoring and Control

6.2.17 Ensure no duplicate GIDs exist (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Although the groupadd program will not let you create a duplicate Group ID (GID), it is possible for an administrator to manually edit the /etc/group file and change the GID field.

Rationale:

User groups must be assigned unique GIDs for accountability and to ensure appropriate access protections.

Audit:

```
#!/bin/bash

cut -f3 -d":" /etc/group | sort -n | uniq -c | while read x ; do
  [ -z "$x" ] && break
  set - $x
  if [ $1 -gt 1 ]; then
     groups=$(awk -F: '($3 == n) { print $1 }' n=$2 /etc/group | xargs)
     echo "Duplicate GID ($2): $groups"
  fi
done
```

Based on the results of the audit script, establish unique GIDs and review all files owned by the shared GID to determine which group they are supposed to belong to.

Notes:

You can also use the grpck command to check for other inconsistencies in the /etc/group file.

CIS Controls:

Version 6

16 <u>Account Monitoring and Control</u>
Account Monitoring and Control

Version 7

16 Account Monitoring and Control
Account Monitoring and Control

6.2.18 Ensure no duplicate user names exist (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Although the useradd program will not let you create a duplicate user name, it is possible for an administrator to manually edit the /etc/passwd file and change the user name.

Rationale:

If a user is assigned a duplicate user name, it will create and have access to files with the first UID for that username in /etc/passwd. For example, if "test4" has a UID of 1000 and a subsequent "test4" entry has a UID of 2000, logging in as "test4" will use UID 1000. Effectively, the UID is shared, which is a security problem.

Audit:

Run the following script and verify no results are returned:

```
#!/bin/bash

cut -f1 -d":" /etc/passwd | sort -n | uniq -c | while read x ; do
  [ -z "$x" ] && break
  set - $x
  if [ $1 -gt 1 ]; then
    uids=$(awk -F: '($1 == n) { print $3 }' n=$2 /etc/passwd | xargs)
    echo "Duplicate User Name ($2): $uids"
  fi
done
```

Based on the results of the audit script, establish unique user names for the users. File ownerships will automatically reflect the change as long as the users have unique UIDs.

CIS Controls:

Version 6

16 <u>Account Monitoring and Control</u> Account Monitoring and Control

Version 7

16 <u>Account Monitoring and Control</u>
Account Monitoring and Control

6.2.19 Ensure no duplicate group names exist (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

Although the groupadd program will not let you create a duplicate group name, it is possible for an administrator to manually edit the /etc/group file and change the group name.

Rationale:

If a group is assigned a duplicate group name, it will create and have access to files with the first GID for that group in /etc/group. Effectively, the GID is shared, which is a security problem.

Audit:

Run the following script and verify no results are returned:

```
#!/bin/bash

cut -f1 -d":" /etc/group | sort -n | uniq -c | while read x ; do
  [ -z "$x" ] && break
  set - $x
  if [ $1 -gt 1 ]; then
     gids=$(gawk -F: '($1 == n) { print $3 }' n=$2 /etc/group | xargs)
     echo "Duplicate Group Name ($2): $gids"
  fi
done
```

Based on the results of the audit script, establish unique names for the user groups. File group ownerships will automatically reflect the change as long as the groups have unique GIDs.

CIS Controls:

Version 6

16 <u>Account Monitoring and Control</u> Account Monitoring and Control

Version 7

16 <u>Account Monitoring and Control</u>
Account Monitoring and Control

6.2.20 Ensure shadow group is empty (Scored)

Profile Applicability:

- Level 1 Server
- Level 1 Workstation

Description:

The shadow group allows system programs which require access the ability to read the /etc/shadow file. No users should be assigned to the shadow group.

Rationale:

Any users assigned to the shadow group would be granted read access to the /etc/shadow file. If attackers can gain read access to the /etc/shadow file, they can easily run a password cracking program against the hashed passwords to break them. Other security information that is stored in the /etc/shadow file (such as expiration) could also be useful to subvert additional user accounts.

Audit:

Run the following commands and verify no results are returned:

```
# grep ^shadow:[^:]*:[^:]*:[^:]+ /etc/group
# awk -F: '($4 == "<shadow-gid>") { print }' /etc/passwd
```

Remove all users from the shadow group, and change the primary group of any users with shadow as their primary group.

CIS Controls:

Version 6

5.1 Minimize And Sparingly Use Administrative Privileges

Minimize administrative privileges and only use administrative accounts when they are required. Implement focused auditing on the use of administrative privileged functions and monitor for anomalous behavior.

Version 7

5.1 Establish Secure Configurations

Maintain documented, standard security configuration standards for all authorized operating systems and software.

Appendix: Summary Table

Control			et
			ectly
		Yes	No
1	Initial Setup		
1.1	Filesystem Configuration		
1.1.1	Disable unused filesystems		
1.1.1.1	Ensure mounting of cramfs filesystems is disabled (Scored)		
1.1.1.2	Ensure mounting of freevxfs filesystems is disabled (Scored)		
1.1.1.3	Ensure mounting of jffs2 filesystems is disabled (Scored)		
1.1.1.4	Ensure mounting of hfs filesystems is disabled (Scored)		
1.1.1.5	Ensure mounting of hfsplus filesystems is disabled (Scored)		
1.1.1.6	Ensure mounting of squashfs filesystems is disabled (Scored)		
1.1.1.7	Ensure mounting of udf filesystems is disabled (Scored)		
1.1.1.8	Ensure mounting of FAT filesystems is limited (Not Scored)		
1.1.2	Ensure /tmp is configured (Scored)		
1.1.3	Ensure nodev option set on /tmp partition (Scored)		
1.1.4	Ensure nosuid option set on /tmp partition (Scored)		
1.1.5	Ensure noexec option set on /tmp partition (Scored)		
1.1.6	Ensure separate partition exists for /var (Scored)		
1.1.7	Ensure separate partition exists for /var/tmp (Scored)		
1.1.8	Ensure nodev option set on /var/tmp partition (Scored)		
1.1.9	Ensure nosuid option set on /var/tmp partition (Scored)		
1.1.10	Ensure noexec option set on /var/tmp partition (Scored)		
1.1.11	Ensure separate partition exists for /var/log (Scored)		
1.1.12	Ensure separate partition exists for /var/log/audit (Scored)		
1.1.13	Ensure separate partition exists for /home (Scored)		
1.1.14	Ensure nodev option set on /home partition (Scored)		
1.1.15	Ensure nodev option set on /dev/shm partition (Scored)		
1.1.16	Ensure nosuid option set on /dev/shm partition (Scored)		
1.1.17	Ensure noexec option set on /dev/shm partition (Scored)		
1.1.18	Ensure nodev option set on removable media partitions (Not Scored)		
1.1.19	Ensure nosuid option set on removable media partitions (Not Scored)		
1.1.20	Ensure noexec option set on removable media partitions (Not Scored)		
1.1.21	Ensure sticky bit is set on all world-writable directories (Scored)		
1.1.22	Disable Automounting (Scored)		

1.1.23	Disable USB Storage (Scored)	П	П
1.2	Configure Software Updates		
1.2.1	Ensure package manager repositories are configured (Not Scored)		
1.2.2	Ensure GPG keys are configured (Not Scored)		
1.3	Filesystem Integrity Checking	•	
1.3.1	Ensure AIDE is installed (Scored)		
1.3.2	Ensure filesystem integrity is regularly checked (Scored)		
1.4	Secure Boot Settings		
1.4.1	Ensure permissions on bootloader config are configured (Scored)		
1.4.2	Ensure bootloader password is set (Scored)		
1.4.3	Ensure authentication required for single user mode (Scored)		
1.4.4	Ensure interactive boot is not enabled (Not Scored)		
1.5	Additional Process Hardening		
1.5.1	Ensure core dumps are restricted (Scored)		
1.5.2	Ensure XD/NX support is enabled (Scored)		
1.5.3	Ensure address space layout randomization (ASLR) is enabled (Scored)		
1.5.4	Ensure prelink is disabled (Scored)		
1.6	Mandatory Access Control		
1.6.1	Ensure Mandatory Access Control Software is Installed		
1.6.1.1	Ensure SELinux or AppArmor are installed (Scored)		
1.6.2	Configure SELinux		
1.6.2.1	Ensure SELinux is not disabled in bootloader configuration (Scored)		
1.6.2.2	Ensure the SELinux state is enforcing (Scored)		
1.6.2.3	Ensure SELinux policy is configured (Scored)		
1.6.2.4	Ensure SETroubleshoot is not installed (Scored)		
1.6.2.5	Ensure the MCS Translation Service (mcstrans) is not installed (Scored)		
1.6.2.6	Ensure no unconfined daemons exist (Scored)		
1.6.3	Configure AppArmor		
1.6.3.1	Ensure AppArmor is not disabled in bootloader configuration (Scored)		
1.6.3.2	Ensure all AppArmor Profiles are enforcing (Scored)		
1.7	Warning Banners		
1.7.1	Command Line Warning Banners		
1.7.1.1	Ensure message of the day is configured properly (Scored)		
1.7.1.2	Ensure local login warning banner is configured properly (Scored)		

1.7.1.3 Ensure remote login warning banner is configured properly (Scored) □				
1.7.1.4 Ensure permissions on /etc/motd are configured (Scored) 1.7.1.5 Ensure permissions on /etc/issue are configured (Scored) 1.7.1.6 Ensure permissions on /etc/issue.net are configured (Scored) 1.7.2 Ensure GDM login banner is configured (Scored) 1.8 Ensure updates, patches, and additional security software are installed (Not Scored) 2 Services 2.1 inetd Services 2.1.1 Ensure chargen services are not enabled (Scored) 2.1.2 Ensure daytime services are not enabled (Scored) 2.1.3 Ensure discard services are not enabled (Scored) 2.1.4 Ensure echo services are not enabled (Scored) 2.1.5 Ensure time services are not enabled (Scored) 2.1.6 Ensure rsh server is not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.1.5 Ensure Nortonization is in use (Not Scored) 2.2.1.6 Ensure Synchronization is not installed (Scored) 2.2.1.7 Ensure time synchronization is not installed (Scored) 2.2.1.8 Ensure htp is configured (Scored) 2.2.1.9 Ensure Systemd-timesyncd is configured (Scored) 2.2.1.1 Ensure time synchronization is not installed (Scored) 2.2.2.2 Ensure DAP server is not enabled (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure DAP server is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure DAP server is not enabled (Scored) 2.2.7 Ensure FTP Server is not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored)	1.7.1.3			
1.7.1.5 Ensure permissions on /etc/issue are configured (Scored) 1.7.1.6 Ensure permissions on /etc/issue.net are configured (Scored) 1.7.2 Ensure GDM login banner is configured (Scored) 1.8 Ensure updates, patches, and additional security software are installed (Not Scored) 2 Services 2.1 inetd Services 2.1.1 Ensure chargen services are not enabled (Scored) 2.1.2 Ensure daytime services are not enabled (Scored) 2.1.3 Ensure discard services are not enabled (Scored) 2.1.4 Ensure discard services are not enabled (Scored) 2.1.5 Ensure time services are not enabled (Scored) 2.1.6 Ensure time services are not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tflp server is not enabled (Scored) 2.1.10 Ensure since the services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.2 Special Purpose Services 2.2.1 Ensure to configured (Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure thine synchronization is in use (Not Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2.5 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure Avahi Server is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored)	1.7.1.4			
1.7.1.6 Ensure permissions on /etc/issue.net are configured (Scored) 1.7.2 Ensure GDM login banner is configured (Scored) 1.8 Ensure updates, patches, and additional security software are installed (Not Scored) 2 Services 2.1 inetd Services 2.1.1 Ensure chargen services are not enabled (Scored) 2.1.2 Ensure daytime services are not enabled (Scored) 2.1.3 Ensure discard services are not enabled (Scored) 2.1.4 Ensure echo services are not enabled (Scored) 2.1.5 Ensure time services are not enabled (Scored) 2.1.6 Ensure rsh server is not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure intp is configured (Scored) 2.2.1.3 Ensure time synchronization is in use (Not Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.1.5 Ensure thony is configured (Scored) 2.2.1.6 Ensure Systemd-timesyncd is configured (Scored) 2.2.1.7 Ensure time synchronization is in use (Not Scored) 2.2.1.8 Ensure other is not enabled (Scored) 2.2.1.9 Ensure other is not enabled (Scored) 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure other is not enabled (Scored) 2.2.2.3 Ensure DNC PServer is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure DNS Server is not enabled (Scored) 2.2.7 Ensure DNS Server is not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure HTTP Server is not enabled (Scored)	1.7.1.5			
1.7.2 Ensure GDM login banner is configured (Scored)				
Ensure updates, patches, and additional security software are installed (Not Scored)		(Scored)	Ш	Ц
are installed (Not Scored) 2	1.7.2	Ensure GDM login banner is configured (Scored)		
are installed (Not Scored) 2	1.8	Ensure updates, patches, and additional security software	٦	
2.1.1 Ensure chargen services are not enabled (Scored) 2.1.2 Ensure daytime services are not enabled (Scored) 2.1.3 Ensure discard services are not enabled (Scored) 2.1.4 Ensure echo services are not enabled (Scored) 2.1.5 Ensure time services are not enabled (Scored) 2.1.6 Ensure rsh server is not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) □ 2.2.10 Ensure HTTP server is not enabled (Scored)		are installed (Not Scored)		
2.1.1 Ensure chargen services are not enabled (Scored) 2.1.2 Ensure daytime services are not enabled (Scored) 2.1.3 Ensure discard services are not enabled (Scored) 2.1.4 Ensure echo services are not enabled (Scored) 2.1.5 Ensure time services are not enabled (Scored) 2.1.6 Ensure rsh server is not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2.1 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2.5 Ensure X Window System is not installed (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) □ 2.2.10 Ensure HTTP server is not enabled (Scored)	2	Services		
2.1.2 Ensure daytime services are not enabled (Scored) 2.1.3 Ensure discard services are not enabled (Scored) 2.1.4 Ensure echo services are not enabled (Scored) 2.1.5 Ensure time services are not enabled (Scored) 2.1.6 Ensure rsh server is not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2. Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure FTP Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) □ 2.2.10 Ensure HTTP server is not enabled (Scored)	2.1	inetd Services		
2.1.3 Ensure discard services are not enabled (Scored) 2.1.4 Ensure echo services are not enabled (Scored) 2.1.5 Ensure time services are not enabled (Scored) 2.1.6 Ensure rsh server is not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure FTP Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) □ 2.2.10 Ensure HTTP server is not enabled (Scored)		Ensure chargen services are not enabled (Scored)		
2.1.4 Ensure echo services are not enabled (Scored) 2.1.5 Ensure time services are not enabled (Scored) 2.1.6 Ensure rsh server is not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.2.2 Ensure ntp is configured (Scored) 2.2.1.2 Ensure chrony is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) Candot Provided Hamber of the services are not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored)	2.1.2	Ensure daytime services are not enabled (Scored)		
2.1.5 Ensure time services are not enabled (Scored) 2.1.6 Ensure rsh server is not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) 2.2.10 Ensure HTTP server is not enabled (Scored)	2.1.3	Ensure discard services are not enabled (Scored)		
2.1.6 Ensure rsh server is not enabled (Scored) 2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) □ 2.2.10 Ensure HTTP server is not enabled (Scored) □ □ □ □	2.1.4	Ensure echo services are not enabled (Scored)		
2.1.7 Ensure talk server is not enabled (Scored) 2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2. Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) □ 2.2.10 Ensure HTTP server is not enabled (Scored)	2.1.5	Ensure time services are not enabled (Scored)		
2.1.8 Ensure telnet server is not enabled (Scored) 2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) □	2.1.6	Ensure rsh server is not enabled (Scored)		
2.1.9 Ensure tftp server is not enabled (Scored) 2.1.10 Ensure xinetd is not enabled (Scored) 2.2 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.2 Ensure time synchronization is in use (Not Scored) 2.2.1.3 Ensure of configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure DNS Server is not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure HTTP Server is not enabled (Scored) □ □ □ □ □ □ □ □ □ □ □ □ □	2.1.7	Ensure talk server is not enabled (Scored)		
2.1.10 Ensure xinetd is not enabled (Scored) 2.2 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) □ □ □ □ □ □ □ □ □ □ □ □ □	2.1.8	Ensure telnet server is not enabled (Scored)		
2.2 Special Purpose Services 2.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) 2.2.10 Ensure HTTP server is not enabled (Scored)	2.1.9	Ensure tftp server is not enabled (Scored)		
Z.2.1 Time Synchronization 2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) 2.2.10 Ensure HTTP server is not enabled (Scored)	2.1.10	Ensure xinetd is not enabled (Scored)		
2.2.1.1 Ensure time synchronization is in use (Not Scored) 2.2.1.2 Ensure ntp is configured (Scored) 2.2.1.3 Ensure chrony is configured (Scored) 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) 2.2.10 Ensure HTTP server is not enabled (Scored)	2.2	Special Purpose Services		
2.2.1.2 Ensure ntp is configured (Scored) □ 2.2.1.3 Ensure chrony is configured (Scored) □ 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) □ 2.2.2 Ensure X Window System is not installed (Scored) □ 2.2.3 Ensure Avahi Server is not enabled (Scored) □ 2.2.4 Ensure CUPS is not enabled (Scored) □ 2.2.5 Ensure DHCP Server is not enabled (Scored) □ 2.2.6 Ensure LDAP server is not enabled (Scored) □ 2.2.7 Ensure NFS and RPC are not enabled (Scored) □ 2.2.8 Ensure DNS Server is not enabled (Scored) □ 2.2.9 Ensure FTP Server is not enabled (Scored) □ 2.2.10 Ensure HTTP server is not enabled (Scored) □	2.2.1	Time Synchronization		
2.2.1.3 Ensure chrony is configured (Scored) □ 2.2.1.4 Ensure systemd-timesyncd is configured (Scored) □ 2.2.2 Ensure X Window System is not installed (Scored) □ 2.2.3 Ensure Avahi Server is not enabled (Scored) □ 2.2.4 Ensure CUPS is not enabled (Scored) □ 2.2.5 Ensure DHCP Server is not enabled (Scored) □ 2.2.6 Ensure LDAP server is not enabled (Scored) □ 2.2.7 Ensure NFS and RPC are not enabled (Scored) □ 2.2.8 Ensure DNS Server is not enabled (Scored) □ 2.2.9 Ensure FTP Server is not enabled (Scored) □ 2.2.10 Ensure HTTP server is not enabled (Scored) □	2.2.1.1	Ensure time synchronization is in use (Not Scored)		
2.2.1.4 Ensure systemd-timesyncd is configured (Scored) 2.2.2 Ensure X Window System is not installed (Scored) 2.2.3 Ensure Avahi Server is not enabled (Scored) 2.2.4 Ensure CUPS is not enabled (Scored) 2.2.5 Ensure DHCP Server is not enabled (Scored) 2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) 2.2.10 Ensure HTTP server is not enabled (Scored)	2.2.1.2	Ensure ntp is configured (Scored)		
2.2.2Ensure X Window System is not installed (Scored)□2.2.3Ensure Avahi Server is not enabled (Scored)□2.2.4Ensure CUPS is not enabled (Scored)□2.2.5Ensure DHCP Server is not enabled (Scored)□2.2.6Ensure LDAP server is not enabled (Scored)□2.2.7Ensure NFS and RPC are not enabled (Scored)□2.2.8Ensure DNS Server is not enabled (Scored)□2.2.9Ensure FTP Server is not enabled (Scored)□2.2.10Ensure HTTP server is not enabled (Scored)□	2.2.1.3	Ensure chrony is configured (Scored)		
2.2.3 Ensure Avahi Server is not enabled (Scored) □ 2.2.4 Ensure CUPS is not enabled (Scored) □ 2.2.5 Ensure DHCP Server is not enabled (Scored) □ 2.2.6 Ensure LDAP server is not enabled (Scored) □ 2.2.7 Ensure NFS and RPC are not enabled (Scored) □ 2.2.8 Ensure DNS Server is not enabled (Scored) □ 2.2.9 Ensure FTP Server is not enabled (Scored) □ 2.2.10 Ensure HTTP server is not enabled (Scored) □	2.2.1.4	Ensure systemd-timesyncd is configured (Scored)		
2.2.4Ensure CUPS is not enabled (Scored)□2.2.5Ensure DHCP Server is not enabled (Scored)□2.2.6Ensure LDAP server is not enabled (Scored)□2.2.7Ensure NFS and RPC are not enabled (Scored)□2.2.8Ensure DNS Server is not enabled (Scored)□2.2.9Ensure FTP Server is not enabled (Scored)□2.2.10Ensure HTTP server is not enabled (Scored)□	2.2.2	Ensure X Window System is not installed (Scored)		
2.2.5Ensure DHCP Server is not enabled (Scored)□2.2.6Ensure LDAP server is not enabled (Scored)□2.2.7Ensure NFS and RPC are not enabled (Scored)□2.2.8Ensure DNS Server is not enabled (Scored)□2.2.9Ensure FTP Server is not enabled (Scored)□2.2.10Ensure HTTP server is not enabled (Scored)□	2.2.3	Ensure Avahi Server is not enabled (Scored)		
2.2.6 Ensure LDAP server is not enabled (Scored) 2.2.7 Ensure NFS and RPC are not enabled (Scored) 2.2.8 Ensure DNS Server is not enabled (Scored) 2.2.9 Ensure FTP Server is not enabled (Scored) 2.2.10 Ensure HTTP server is not enabled (Scored) □	2.2.4	Ensure CUPS is not enabled (Scored)		
2.2.7Ensure NFS and RPC are not enabled (Scored)□2.2.8Ensure DNS Server is not enabled (Scored)□2.2.9Ensure FTP Server is not enabled (Scored)□2.2.10Ensure HTTP server is not enabled (Scored)□	2.2.5	Ensure DHCP Server is not enabled (Scored)		
2.2.8Ensure DNS Server is not enabled (Scored)□2.2.9Ensure FTP Server is not enabled (Scored)□2.2.10Ensure HTTP server is not enabled (Scored)□	2.2.6	Ensure LDAP server is not enabled (Scored)		
2.2.9Ensure FTP Server is not enabled (Scored)□2.2.10Ensure HTTP server is not enabled (Scored)□	2.2.7	Ensure NFS and RPC are not enabled (Scored)		
2.2.10 Ensure HTTP server is not enabled (Scored)	2.2.8	Ensure DNS Server is not enabled (Scored)		
	2.2.9	Ensure FTP Server is not enabled (Scored)		
	2.2.10	Ensure HTTP server is not enabled (Scored)		
2.2.11 Ensure IMAP and POP3 server is not enabled (Scored)	2.2.11	Ensure IMAP and POP3 server is not enabled (Scored)		
2.2.12 Ensure Samba is not enabled (Scored)	2.2.12	Ensure Samba is not enabled (Scored)		
2.2.13 Ensure HTTP Proxy Server is not enabled (Scored)	2.2.13	Ensure HTTP Proxy Server is not enabled (Scored)		
2.2.14 Ensure SNMP Server is not enabled (Scored)	2.2.14	Ensure SNMP Server is not enabled (Scored)		
2.2.15 Ensure mail transfer agent is configured for local-only mode (Scored)	2.2.15			
	2.2.16	Ensure rsync service is not enabled (Scored)		

2.2.17	Ensure NIS Server is not enabled (Scored)		
2.3	Service Clients		
2.3.1	Ensure NIS Client is not installed (Scored)		
2.3.2	Ensure rsh client is not installed (Scored)		
2.3.3	Ensure talk client is not installed (Scored)		
2.3.4	Ensure telnet client is not installed (Scored)		
2.3.5	Ensure LDAP client is not installed (Scored)		
3	Network Configuration	-	
3.1	Network Parameters (Host Only)		
3.1.1	Ensure IP forwarding is disabled (Scored)		
3.1.2	Ensure packet redirect sending is disabled (Scored)		
3.2	Network Parameters (Host and Router)	-	
3.2.1	Ensure source routed packets are not accepted (Scored)		
3.2.2	Ensure ICMP redirects are not accepted (Scored)		
3.2.3	Ensure secure ICMP redirects are not accepted (Scored)		
3.2.4	Ensure suspicious packets are logged (Scored)		
3.2.5	Ensure broadcast ICMP requests are ignored (Scored)		
3.2.6	Ensure bogus ICMP responses are ignored (Scored)		
3.2.7	Ensure Reverse Path Filtering is enabled (Scored)		
3.2.8	Ensure TCP SYN Cookies is enabled (Scored)		
3.2.9	Ensure IPv6 router advertisements are not accepted		
	(Scored)		
3.3	TCP Wrappers		
3.3.1	Ensure TCP Wrappers is installed (Not Scored)		
3.3.2	Ensure /etc/hosts.allow is configured (Not Scored)		
3.3.3	Ensure /etc/hosts.deny is configured (Not Scored)		
3.3.4	Ensure permissions on /etc/hosts.allow are configured		
	(Scored)		Ш
3.3.5	Ensure permissions on /etc/hosts.deny are configured		
	(Scored)		
3.4	Uncommon Network Protocols		
3.4.1	Ensure DCCP is disabled (Scored)		
3.4.2	Ensure SCTP is disabled (Scored)		
3.4.3	Ensure RDS is disabled (Scored)		
3.4.4	Ensure TIPC is disabled (Scored)		
3.5	Firewall Configuration		
3.5.1	Configure IPv6 ip6tables		
3.5.1.1	Ensure IPv6 default deny firewall policy (Scored)		
3.5.1.2	Ensure IPv6 loopback traffic is configured (Scored)		
3.5.1.3	Ensure IPv6 outbound and established connections are		
	configured (Not Scored)		
3.5.1.4	Ensure IPv6 firewall rules exist for all open ports (Not		
	Scored)		J

3.5.2	Configure IPv4 iptables		
3.5.2.1	Ensure default deny firewall policy (Scored)		
3.5.2.2	Ensure loopback traffic is configured (Scored)		
3.5.2.3	Ensure outbound and established connections are		
	configured (Not Scored)	ם	
3.5.2.4	Ensure firewall rules exist for all open ports (Scored)		
3.5.3	Ensure iptables is installed (Scored)		
3.6	Ensure wireless interfaces are disabled (Not Scored)		
3.7	Disable IPv6 (Not Scored)		
4	Logging and Auditing		
4.1	Configure System Accounting (auditd)		
4.1.1	Configure Data Retention		
4.1.1.1	Ensure audit log storage size is configured (Scored)		
4.1.1.2	Ensure system is disabled when audit logs are full (Scored)		
4.1.1.3	Ensure audit logs are not automatically deleted (Scored)		
4.1.2	Ensure auditd is installed (Scored)		
4.1.3	Ensure auditd service is enabled (Scored)		
4.1.4	Ensure auditing for processes that start prior to auditd is		
	enabled (Scored)		
4.1.5	Ensure events that modify date and time information are]	
	collected (Scored)		
4.1.6	Ensure events that modify user/group information are]	
	collected (Scored)		ш
4.1.7	Ensure events that modify the system's network		
	environment are collected (Scored)		
4.1.8	Ensure events that modify the system's Mandatory Access		
	Controls are collected (Scored)		
4.1.9	Ensure login and logout events are collected (Scored)		
4.1.10	Ensure session initiation information is collected (Scored)		
4.1.11	Ensure discretionary access control permission		
	modification events are collected (Scored)		ш
4.1.12	Ensure unsuccessful unauthorized file access attempts are		
	collected (Scored)		
4.1.13	Ensure use of privileged commands is collected (Scored)		
4.1.14	Ensure successful file system mounts are collected (Scored)		
4.1.15	Ensure file deletion events by users are collected (Scored)		
4.1.16	Ensure changes to system administration scope (sudoers) is collected (Scored)		
4.1.17	Ensure system administrator actions (sudolog) are collected (Scored)		
4.1.18	Ensure kernel module loading and unloading is collected		
4.1.10	(Scored)		
4.1.19	Ensure the audit configuration is immutable (Scored)		

4.2	Configure Logging		
4.2.1	Configure rsyslog		
4.2.1.1	Ensure rsyslog is installed (Scored)		
4.2.1.2	Ensure rsyslog Service is enabled (Scored)		
4.2.1.3	Ensure logging is configured (Not Scored)		
4.2.1.4	Ensure rsyslog default file permissions configured (Scored)		
4.2.1.5	Ensure rsyslog is configured to send logs to a remote log host (Scored)		
4.2.1.6	Ensure remote rsyslog messages are only accepted on designated log hosts. (Not Scored)		
4.2.2	Configure journald	•	
4.2.2.1	Ensure journald is configured to send logs to rsyslog (Scored)		
4.2.2.2	Ensure journald is configured to compress large log files (Scored)		
4.2.2.3	Ensure journald is configured to write logfiles to persistent disk (Scored)		
4.2.3	Ensure permissions on all logfiles are configured (Scored)		
4.3	Ensure logrotate is configured (Not Scored)		
5	Access, Authentication and Authorization		
5.1	Configure cron		
5.1.1	Ensure cron daemon is enabled (Scored)		
5.1.2	Ensure permissions on /etc/crontab are configured (Scored)		
5.1.3	Ensure permissions on /etc/cron.hourly are configured (Scored)		
5.1.4	Ensure permissions on /etc/cron.daily are configured (Scored)		
5.1.5	Ensure permissions on /etc/cron.weekly are configured (Scored)		
5.1.6	Ensure permissions on /etc/cron.monthly are configured (Scored)		
5.1.7	Ensure permissions on /etc/cron.d are configured (Scored)		
5.1.8	Ensure at/cron is restricted to authorized users (Scored)		
5.2	SSH Server Configuration		
5.2.1	Ensure permissions on /etc/ssh/sshd_config are configured (Scored)		
5.2.2	Ensure permissions on SSH private host key files are configured (Scored)		
5.2.3	Ensure permissions on SSH public host key files are configured (Scored)		
5.2.4	Ensure SSH Protocol is set to 2 (Scored)		
5.2.5	Ensure SSH LogLevel is appropriate (Scored)		

5.2.6 5.2.7 5.2.8 5.2.9 5.2.10	Ensure SSH X11 forwarding is disabled (Scored) Ensure SSH MaxAuthTries is set to 4 or less (Scored) Ensure SSH IgnoreRhosts is enabled (Scored)		
5.2.8 5.2.9 5.2.10		L□	1
5.2.9 5.2.10	Ensure SSH IgnoreRhosts is enabled (Scored)]	
5.2.10	D 007777 1 14 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
	Ensure SSH HostbasedAuthentication is disabled (Scored)		
	Ensure SSH root login is disabled (Scored)		
5.2.11	Ensure SSH PermitEmptyPasswords is disabled (Scored)		
5.2.12	Ensure SSH PermitUserEnvironment is disabled (Scored)		
5.2.13	Ensure only strong Ciphers are used (Scored)		
5.2.14	Ensure only strong MAC algorithms are used (Scored)		
5.2.15	Ensure only strong Key Exchange algorithms are used (Scored)		
5.2.16	Ensure SSH Idle Timeout Interval is configured (Scored)		
5.2.17	Ensure SSH LoginGraceTime is set to one minute or less (Scored)		
5.2.18	Ensure SSH access is limited (Scored)		
5.2.19	Ensure SSH warning banner is configured (Scored)		
5.2.20	Ensure SSH PAM is enabled (Scored)		
5.2.21	Ensure SSH AllowTcpForwarding is disabled (Scored)		
5.2.22	Ensure SSH MaxStartups is configured (Scored)		
5.2.23	Ensure SSH MaxSessions is set to 4 or less (Scored)		
5.3	Configure PAM		
5.3.1	Ensure password creation requirements are configured (Scored)		
5.3.2	Ensure lockout for failed password attempts is configured (Not Scored)		
5.3.3	Ensure password reuse is limited (Not Scored)		
5.3.4	Ensure password hashing algorithm is SHA-512 (Not Scored)		
5.4	User Accounts and Environment		
5.4.1	Set Shadow Password Suite Parameters		
5.4.1.1	Ensure password expiration is 365 days or less (Scored)		
5.4.1.2	Ensure minimum days between password changes is 7 or		
0.1.1.2	more (Scored)		
5.4.1.3	Ensure password expiration warning days is 7 or more		
	(Scored)		
5.4.1.4	Ensure inactive password lock is 30 days or less (Scored)		
5.4.1.5	Ensure all users last password change date is in the past (Scored)		
5.4.2	Ensure system accounts are secured (Scored)		
5.4.3	Ensure default group for the root account is GID 0 (Scored)		
5.4.4	Ensure default user umask is 027 or more restrictive (Scored)		

5.4.5	Ensure default user shell timeout is 900 seconds or less (Scored)		
5.5	Ensure root login is restricted to system console (Not Scored)		
5.6	Ensure access to the su command is restricted (Scored)		
6	System Maintenance		
6.1	System File Permissions		
6.1.1	Audit system file permissions (Not Scored)		
6.1.2	Ensure permissions on /etc/passwd are configured (Scored)		
6.1.3	Ensure permissions on /etc/shadow are configured (Scored)		
6.1.4	Ensure permissions on /etc/group are configured (Scored)		
6.1.5	Ensure permissions on /etc/gshadow are configured (Scored)		
6.1.6	Ensure permissions on /etc/passwd- are configured (Scored)		
6.1.7	Ensure permissions on /etc/shadow- are configured (Scored)		
6.1.8	Ensure permissions on /etc/group- are configured (Scored)		
6.1.9	Ensure permissions on /etc/gshadow- are configured (Scored)		
6.1.10	Ensure no world writable files exist (Scored)		
6.1.11	Ensure no unowned files or directories exist (Scored)		
6.1.12	Ensure no ungrouped files or directories exist (Scored)		
6.1.13	Audit SUID executables (Not Scored)		
6.1.14	Audit SGID executables (Not Scored)		
6.2	User and Group Settings		
6.2.1	Ensure password fields are not empty (Scored)		
6.2.2	Ensure no legacy "+" entries exist in /etc/passwd (Scored)		
6.2.3	Ensure no legacy "+" entries exist in /etc/shadow (Scored)		
6.2.4	Ensure no legacy "+" entries exist in /etc/group (Scored)		
6.2.5	Ensure root is the only UID 0 account (Scored)		
6.2.6	Ensure root PATH Integrity (Scored)		
6.2.7	Ensure all users' home directories exist (Scored)		
6.2.8	Ensure users' home directories permissions are 750 or more restrictive (Scored)		
6.2.9	Ensure users own their home directories (Scored)		
6.2.10	Ensure users' dot files are not group or world writable (Scored)		
6.2.11	Ensure no users have .forward files (Scored)		
6.2.12	Ensure no users have .netrc files (Scored)		

6.2.13	Ensure users' .netrc Files are not group or world accessible (Scored)	
6.2.14	Ensure no users have .rhosts files (Scored)	
6.2.15	Ensure all groups in /etc/passwd exist in /etc/group (Scored)	
6.2.16	Ensure no duplicate UIDs exist (Scored)	
6.2.17	Ensure no duplicate GIDs exist (Scored)	
6.2.18	Ensure no duplicate user names exist (Scored)	
6.2.19	Ensure no duplicate group names exist (Scored)	
6.2.20	Ensure shadow group is empty (Scored)	

Appendix: Change History

Date	Version	Changes for this version
Apr 1, 2016	1.0.0	Initial Release
Jan 31, 2017	1.0.1	CIS Controls Mapping
Dec 26, 2017	1.1.0	1.1.1.* - Expanded remediation to match audit (Ticket 86)
Dec 26, 2017	1.1.0	1.1.1.8 - Moved to Level 2 for all use cases (Ticket 5719)
Dec 26, 2017	1.1.0	1.1.25 - Fixed audit and remediation commands (Ticket 5015)
Dec 26, 2017	1.1.0	1.1.3-1.1.5 - Removed notes (Ticket 1332)
Dec 26, 2017	1.1.0	1.1.6 - Fixed typo in audit command (Ticket 59)
Dec 26, 2017	1.1.0	1.1.7 - Updated command output example in audit (Ticket 77)
Dec 26, 2017	1.1.0	1.5.1, 1.5.3, 3.1.*, 3.2.*, 3.3.1, 3.3.2 - Expanded audit and updated remediation (Tickets 78, 84)
Dec 26, 2017	1.1.0	1.7.1.1-1.7.1.3 - Removed erroneous command references (Ticket 67)
Dec 26, 2017	1.1.0	1.7.2 - Expanded audit check (Ticket 66)
Dec 26, 2017	1.1.0	2.1.1 - Removed extraneous controls mapping (Ticket 4788)
Dec 26, 2017	1.1.0	2.1.10 - Fixed typo in Remediation prose (Ticket 81)
Dec 26, 2017	1.1.0	2.2.1.2 - Expanded audit and remediation (Ticket 5624)
Dec 26, 2017	1.1.0	2.2.1.2, 2.2.1.3 - Expanded audit and remediation options (Ticket 805)
Dec 26, 2017	1.1.0	2.2.10 - Fixed typo in audit (Ticket 5283)
Dec 26, 2017	1.1.0	2.2.14 - Clarified Rationale (Ticket 74)
Dec 26, 2017	1.1.0	2.2.15 - Updated remediation settings (Ticket 80)
Dec 26, 2017	1.1.0	2.2.15, 5.2 - Updated commands to include systemd style (Ticket 76)

Dec 26, 2017	1.1.0	2.2.3 - Fixed reversed prose in Audit and Remediation (Ticket 82)
Dec 26, 2017	1.1.0	2.2.3-2.2.14, 2.2.16-2.2.17 - Fixed error in audits (Ticket 5284)
Dec 26, 2017	1.1.0	2.2.5 - Fixed prose in Audit (Ticket 83)
Dec 26, 2017	1.1.0	3.3.1, 3.3.2 - Fixed audit and remediation output examples (Ticket 88)
Dec 26, 2017	1.1.0	3.3.3 - Aligned audit and remediation to all distributions (Ticket 1338)
Dec 26, 2017	1.1.0	3.4.5 - Corrected title (Ticket 1303)
Dec 26, 2017	1.1.0	3.6.5 - Fixed typo in audit commands (ticket 75)
Dec 26, 2017	1.1.0	4.1.17 - Fixed typo in audit and remediation (Ticket 58)
Dec 26, 2017	1.1.0	4.1.4-4.1.17 - Expanded audit (Ticket 71)
Dec 26, 2017	1.1.0	4.1.7 - Expanded audit and remediation (Ticket 72)
Dec 26, 2017	1.1.0	4.1.9 - Updated audit and remediation (Ticket 5429)
Dec 26, 2017	1.1.0	4.2.1.2, 4.2.1.4, 4.2.1.5, 4.2.2.2, 4.2.2.4, 4.2.2.5 - Updated remediation prose (Ticket 1893)
Dec 26, 2017	1.1.0	4.2.1.2-4.1.2.5 - Updated audit and remediation (Ticket 804)
Dec 26, 2017	1.1.0	4.2.1.4 - Fixed discrepancy in audit (Ticket 64)
Dec 26, 2017	1.1.0	4.2.1.4 - Fixed inconsistency in audit text (Ticket 64)
Dec 26, 2017	1.1.0	4.2.2.1 - Fixed error in remediation commands (ticket 68)
Dec 26, 2017	1.1.0	4.2.2.4 - 4.2.2.5 - Fixed reference (Ticket 63)
Dec 26, 2017	1.1.0	4.2.2.4 - Fixed inconsistency in references and scoring status (Ticket 63)
Dec 26, 2017	1.1.0	4.2.2.5 - Fixed incorrect service name in remediation (Ticket 62)
Dec 26, 2017	1.1.0	4.3 - Added note (Ticket 89)
Dec 26, 2017	1.1.0	5.1.3-5.1.7 - Fixed typo in audit command output example (Ticket 4716)
Dec 26, 2017	1.1.0	5.2.1 - Updated rationale (Ticket 4775)

Dec 26, 2017	1.1.0	5.2.11 - Fixed Typo in Rationale (Ticket 4873)
Dec 26, 2017	1.1.0	5.2.11 - Removed Recommendation (Ticket 1848)
Dec 26, 2017	1.1.0	5.2.12 - Updated audit (Ticket 5069)
Dec 26, 2017	1.1.0	5.2.13 - Updated audit (Ticket 5071)
Dec 26, 2017	1.1.0	5.3.1 - Removed requirements in audit (Ticket 5692)
Dec 26, 2017	1.1.0	5.3.1 - Updated audit and remediation, and added note (Ticket 5553)
Dec 26, 2017	1.1.0	5.3.2 - Added note regarding audit flag (Ticket 1990)
Dec 26, 2017	1.1.0	5.4.1.1 - Added note (Ticket 5082)
Dec 26, 2017	1.1.0	5.4.1.1 - Reduced requirements in audit and remediation (Ticket 5692)
Dec 26, 2017	1.1.0	5.4.1.2 - Fixed typo in notes (Ticket 5192)
Dec 26, 2017	1.1.0	5.4.1.4 - Added note (Ticket 5084)
Dec 26, 2017	1.1.0	5.4.1.4 - Fixed typo in audit (Ticket 5093)
Dec 26, 2017	1.1.0	5.4.1.5 - Added recommendation (Ticket 70)
Dec 26, 2017	1.1.0	5.4.4 - Expanded audit and remediation (Ticket 4777)
Dec 26, 2017	1.1.0	5.4.4 - Updated audit command (Ticket 5245)
Dec 26, 2017	1.1.0	5.4.5 - Added recommendation (Ticket 73)
Dec 26, 2017	1.1.0	6.1.10-6.1.14 - Corrected audit command (Ticket 5122)
Dec 26, 2017	1.1.0	6.1.3 - Fixed typo in remediation command (Ticket 87)
Dec 26, 2017	1.1.0	6.1.6, 6.1.8 - Updated audit and remediation (Ticket 5346)
Dec 26, 2017	1.1.0	6.1.6-6.1.9 - Aligned recommendations to match non-backup files (Ticket 5218)
Dec 26, 2017	1.1.0	6.2 - Added note (Ticket 5479)
Dec 26, 2017	1.1.0	6.2.2-6.2.4 - Fixed regex in audit (Ticket 1320)

Dec 26, 2017	1.1.0	6.2.20 - Updated audit command (Ticket 85)
Dec 26, 2017	1.1.0	6.2.7-6.2.14 - Updated audit procedure (Ticket 5534)
Dec 29, 2017	1.1.0	Published
Jul 1, 2019	2.0.0	DELETE - Duplicated recommendations deleted - (Ticket 5890)
Jul 1, 2019	2.0.0	UPDATE - sections 1.1.1.1 - 1.1.1.7 - change from a single cis.conf file to a single or individual .conf file(s) (Ticket 6912) (Ticket 6761)
Jul 1, 2019	2.0.0	DELETE - Duplicate Recommendations 1.1.11, 1.1.12, 1.1.13, 1.1.14 (Ticket 7090)
Jul 1, 2019	2.0.0	UPDATE - Ensure only approved MAC algorithms are used - Changed to Ensure only strong MAC algorithms are used (Ticket 795)
Jul 1, 2019	2.0.0	UPDATE - Ensure events that modify date and time information are collected (Ticket 8363) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure default user shell timeout is 900 seconds or less - Update Audit and Remediation to reflect the text of the audit Procedure (Ticket 8392)
Jul 1, 2019	2.0.0	UPDATE - Ensure events that modify the system's Mandatory Access Controls are collected - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8371) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure session initiation information is collected - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8373) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure login and logout events are collected - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8372) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure discretionary access control permission modification events are collected - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8374) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure unsuccessful unauthorized file access attempts are collected - /etc/audit/audit.rules is overwritten when auditd is restarted (Ticket 8375) (Ticket 8087)

Jul 1, 2019	2.0.0	UPDATE - Ensure use of privileged commands is collected - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8376) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure successful file system mounts are collected - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8377) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure file deletion events by users are collected - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8378) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure changes to system administration scope (sudoers) is collected - /etc/audit/audit.rules is overwritten when auditd is restarted (Ticket 8379) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure system administrator actions (sudolog) are collected - /etc/audit/audit.rules is overwritten when auditd is restarted (Ticket 8380) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure the audit configuration is immutable - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8381) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure kernel module loading and unloading is collected - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8382) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure events that modify the system's network environment are collected - /etc/audit/audit.rules is overwritten when auditd is re-started (Ticket 8370) (Ticket 8078)
Jul 1, 2019	2.0.0	Update - Ensure events that modify user/group information are collected - /etc/audit/audit.rules is overwritten when auditd is restarted (Ticket 8369) (Ticket 8087)
Jul 1, 2019	2.0.0	UPDATE - Ensure permissions on all logfiles are configured - Remediation procedure also changes folder permissions (Ticket 8456)
Jul 1, 2019	2.0.0	UPDATE - Ensure SSH access is limited - The user names in the AllowUsers directive is space separated and NOT comma separated (Ticket 6452)

Jul 1, 2019	2.0.0	UPDATE - Ensure only approved MAC algorithms are used - "Ensure only strong MAC algorithms are used" - reviewed/modified algorithms (Ticket 60) (Ticket 6442)
Jul 1, 2019	2.0.0	UPDATE- Ensure password expiration is 90 days or less - changed to Ensure password expiration is 365 days or less - Audit and remediation updated (Ticket 6917)
Jul 1, 2019	2.0.0	DELETE - syslog-ng section has been removed (Ticket 8489)
Jul 1, 2019	2.0.0	UPDATE - Ensure only strong Ciphers are used - Added chacha20-poly1305@openssh.com to the recomended cipher list (Ticket 6972)
Jul 1, 2019	2.0.0	UPDATE - Ensure IMAP and POP3 server is not enabled - Notes section incorrectly refers to cyrus-imap as a web server (Ticket 6404)
Jul 1, 2019	2.0.0	ADD - IPv6 configuration to Network Parameters recommendations (Ticket 7035)
Jul 1, 2019	2.0.0	UPDATE - Ensure GDM login banner is configured - Update audit and remediation to ensure that OS name and/or version are not displayed (Ticket 8388)
Jul 1, 2019	2.0.0	UPDATE - Ensure GDM login banner is configured - modified to include GDM3 (Ticket 8389)
Jul 1, 2019	2.0.0	UPDATE - Ensure sticky bit is set on all world-writable directories - remediation is unable to handle if a filename has Special character (Ticket 8487)
Jul 1, 2019	2.0.0	UPDATE - Ensure message of the day is configured properly - Update audit and remediation to ensure that OS name and/or version are not displayed (Ticket 8385)
Jul 1, 2019	2.0.0	UPDATE - Ensure local login warning banner is configured properly - Update audit and remediation to ensure that OS name and/or version are not displayed (Ticket 8386)
Jul 1, 2019	2.0.0	UPDATE - Ensure remote login warning banner is configured properly - Update audit and remediation to ensure that OS name and/or version are not displayed (Ticket 8387)
Jul 1, 2019	2.0.0	ADD - Ensure systemd-timesyncd is configured

Jul 1, 2019	2.0.0	UPDATE - Ensure core dumps are restricted - If systemd-coredump is installed, limits has no effect (Ticket 8475) (Ticket 8476)
Jul 1, 2019	2.0.0	UPDATE - Ensure time synchronization is in use - Modify to include timesyncd (Ticket 8450)
Jul 1, 2019	2.0.0	UPDATE - Ensure auditing for processes that start prior to auditd is enabled - Update recommendation to account for Grub2 (Ticket 8367)
Jul 1, 2019	2.0.0	UPDATE - Ensure mail transfer agent is configured for local-only mode - netstat is deprecated - re-written to leverage ss (Ticket 8056) (Ticket 8569) (Ticket 8658)
Jul 1, 2019	2.0.0	UPDATE - Ensure permissions on bootloader config are configured - Corrected for grub2 configuration (Ticket 8549)
Jul 1, 2019	2.0.0	UPDATE - Ensure X Window System is not installed - adds an "Impact" statement summarizing the issue and potential workaround (Ticket 8548)
Jul 1, 2019	2.0.0	UPDATE - Ensure permissions on bootloader config are configured - Notes should reference same file as rest of recommendation (Ticket 8560)
Jul 1, 2019	2.0.0	UPDATE - Ensure no unconfined daemons exist - update egrep to grep -E (Ticket 8587)
Jul 1, 2019	2.0.0	UPDATE - Ensure message of the day is configured properly - change egrep to grep -E (Ticket 8588)
Jul 1, 2019	2.0.0	UPDATE - Ensure ntp is configured - replace egrep with grep -E (Ticket 8589)
Jul 1, 2019	2.0.0	UPDATE - Ensure IPv6 firewall rules exist for all open ports - Use ss - 6tln instead of ss -ta (Ticket 8575)
Jul 1, 2019	2.0.0	UPDATE - Ensure firewall rules exist for all open ports - Update audit command (Ticket 8606)
Jul 1, 2019	2.0.0	UPDATE - Ensure events that modify date and time information are collected - allow for any .rules file (Ticket 8604)

Jul 1, 2019	2.0.0	UPDATE - Ensure root is the only UID 0 account - remove cat command from audit (Ticket 8639)
Jul 1, 2019	2.0.0	UPDATE - Ensure password fields are not empty - Eliminate UUOC (Ticket 8625)
Jul 1, 2019	2.0.0	UPDATE - Ensure discretionary access control permission modification events are collected - Corrected Audit success criterion (Ticket 8458)
Jul 1, 2019	2.0.0	UPDATE - Ensure IPv6 loopback traffic is configured - Corrected audit command (Ticket 8566) (Ticket 8541)
Jul 1, 2019	2.0.0	UPDATE - Ensure root PATH Integrity - Removed legacy / deprecated commands (Ticket 8621)
Jul 1, 2019	2.0.0	UPDATE - Ensure all users' home directories exist - Removed legacy / deprecated commands (Ticket 8622) (Ticket 6829)
Jul 1, 2019	2.0.0	UPDATE - Ensure users' home directories permissions are 750 or more restrictive - Removed legacy / deprecated commands (Ticket 8623) (Ticket 6829)
Jul 1, 2019	2.0.0	UPDATE - Ensure users' home directories permissions are 750 or more restrictive - remove "root" account from exclusions (Ticket 8638)
Jul 1, 2019	2.0.0	UPDATE - Ensure users own their home directories - remove "root" account from exclusions - removed legacy / deprecated commands (Ticket 8640)
Jul 1, 2019	2.0.0	UPDATE - Ensure users' dot files are not group or world writable - removed legacy / deprecated commands (Ticket 8641)
Jul 1, 2019	2.0.0	UPDATE - Ensure no users have .forward files - removed legacy / deprecated commands (Ticket 8642)
Jul 1, 2019	2.0.0	UPDATE - Ensure no users have .netrc files - Update audit (Ticket 8647)
Jul 1, 2019	2.0.0	UPDATE - Ensure users' .netrc Files are not group or world accessible - update audit script (Ticket 8648)

Jul 1, 2019	2.0.0	UPDATE - Ensure no users have .rhosts files - update audit script (Ticket 8649)
Jul 1, 2019	2.0.0	UPDATE - Ensure no duplicate UIDs exist - update audit script (Ticket 8650)
Jul 1, 2019	2.0.0	UPDATE - Ensure no duplicate GIDs exist - update audit (Ticket 8651)
Jul 1, 2019	2.0.0	UPDATE - Ensure no duplicate user names exist - update audit (Ticket 8652)
Jul 1, 2019	2.0.0	UPDATE - Ensure no duplicate group names exist - update audit (Ticket 8653)
Jul 1, 2019	2.0.0	UPDATE - Ensure system accounts are non-login - change egrep to grep -E (Ticket 8598)
Jul 1, 2019	2.0.0	UPDATE - Ensure all users last password change date is in the past - Modify audit to simplify output (Ticket 8619)
Jul 1, 2019	2.0.0	UPDATE - Ensure inactive password lock is 30 days or less - update audit section (Ticket 8596)
Jul 1, 2019	2.0.0	UPDATE - Ensure inactive password lock is 30 days or less - change egrep to grep -E (Ticket 8597)
Jul 1, 2019	2.0.0	UPDATE - Ensure password expiration warning days is 7 or more - change egrep to grep -E (Ticket 8595)
Jul 1, 2019	2.0.0	UPDATE - Ensure password expiration warning days is 7 or more - Updated audit (Ticket 8594)
Jul 1, 2019	2.0.0	UPDATE - Ensure minimum days between password changes is 7 or more - Updated audit (Ticket 8592)
Jul 1, 2019	2.0.0	UPDATE - Ensure minimum days between password changes is 7 or more - change egrep to grep -E (Ticket 8593)
Jul 1, 2019	2.0.0	UPDATE - Ensure password expiration is 365 days or less - Updated audit (Ticket 8542) (Ticket 8533)
Jul 1, 2019	2.0.0	UPDATE - Ensure password expiration is 365 days or less - change egrep to grep -E (Ticket 8591)

Jul 1, 2019	2.0.0	UPDATE - Ensure kernel module loading and unloading is collected - Modified audit and remediation to allow for any .rules file (Ticket 8618) (Ticket 8454) (Ticket 8462)
Jul 1, 2019	2.0.0	UPDATE - Ensure events that modify user/group information are collected - Modified audit and remediation to allow for any .rules file (Ticket 8605) (Ticket 8454) (Ticket 8462)
Jul 1, 2019	2.0.0	UPDATE - Ensure events that modify the system's network environment are collected - Modified audit and remediation to allow for any .rules file (Ticket 8606) (Ticket 8454) (Ticket 8462)
Jul 1, 2019	2.0.0	UPDATE - Ensure events that modify the system's Mandatory Access Controls are collected - Modified audit and remediation to allow for any .rules file (Ticket 8607) (Ticket 8454) (Ticket 8462)
Jul 1, 2019	2.0.0	UPDATE - Ensure login and logout events are collected - Modified audit and remediation to allow for any .rules file (Ticket 8609) (Ticket 8454) (Ticket 8462)
Jul 1, 2019	2.0.0	UPDATE - Ensure session initiation information is collected - Modified audit and remediation to allow for any .rules file (Ticket 8610) (Ticket 8454) (Ticket 8462)
Jul 1, 2019	2.0.0	UPDATE - Ensure discretionary access control permission modification events are collected - Modified audit and remediation to allow for any .rules file (Ticket 8611) (Ticket 8454) (Ticket 8462)
Jul 1, 2019	2.0.0	UPDATE - Ensure unsuccessful unauthorized file access attempts are collected - Modified audit and remediation to allow for any .rules file (Ticket 8612) (Ticket 8454) (Ticket 8462)
Jul 2, 2019	2.0.0	UPDATE - Ensure use of privileged commands is collected - Modified audit and remediation to allow for any .rules file (Ticket 8613) (Ticket 8454) (Ticket 8462)
Jul 2, 2019	2.0.0	UPDATE - Ensure successful file system mounts are collected - Modified audit and remediation to allow for any .rules file (Ticket 8614) (Ticket 8454) (Ticket 8462)

Jul 2, 2019	2.0.0	UPDATE - Ensure file deletion events by users are collected - Modified audit and remediation to allow for any .rules file (Ticket 8615) (Ticket 8454) (Ticket 8462)
Jul 2, 2019	2.0.0	UPDATE - Ensure changes to system administration scope (sudoers) is collected - Modified audit and remediation to allow for any .rules file (Ticket 8616) (Ticket 8454) (Ticket 8462)
Jul 2, 2019	2.0.0	UPDATE - Ensure system administrator actions (sudolog) are collected - Modified audit and remediation to allow for any .rules file (Ticket 8617) (Ticket 8454) (Ticket 8462)
Jul 2, 2019	2.0.0	ADD - Disable USB Storage - Recommendation added
Jul 2, 2019	2.0.0	UPDATE - Disable USB Storage - Correct language in Description (Ticket 8574)
Jul 2, 2019	2.0.0	UPDATE - Updated audit and remediation commands and/or scripts to remove legacy/deprecated code and/or commands (Ticket 6829)
Jul 2, 2019	2.0.0	UPDATE - Ensure TCP Wrappers is installed - Updated Description to account for Distributions where TCP Wrappers is depricated - Changed to "Not Scored" (Ticket 8393)
Jul 2, 2019	2.0.0	ADD - Ensure that auditd is installed - Added Recommendation (Ticket 8086)
Jul 2, 2019	2.0.0	UPDATE - Ensure sticky bit is set on all world-writable directories - Updated remediation (Ticket 8455)
Jul 2, 2019	2.0.0	UPDATE - Ensure core dumps are restricted - Added audit and remediation guidance to cover systemd/coredump.conf (Ticket 6258) (Ticket 6259)
Jul 2, 2019	2.0.0	UPDATE - Ensure bootloader password is set - Audit and remediation updated (Ticket 8488)
Jul 2, 2019	2.0.0	UPDATE - Ensure DCCP is disabled - Changed from "Not Scored" to Level 2 Scored (Ticket 6846)
Jul 2, 2019	2.0.0	UPDATE - Ensure SCTP is disabled - Changed from "Not Scored" to Level 2 Scored (Ticket 6846)

Jul 2, 2019	2.0.0	UPDATE - Ensure RDS is disabled - Changed from "Not Scored" to Level 2 Scored (Ticket 6846)
Jul 2, 2019	2.0.0	UPDATE - Ensure TIPC is disabled - Changed from "Not Scored" to Level 2 Scored (Ticket 6846)
Jul 2, 2019	2.0.0	UPDATE - Ensure audit log storage size is configured - Changed from "Not Scored" to Level 2 Scored (Ticket 6847)
Jul 2, 2019	2.0.0	UPDATE - Ensure permissions on /etc/cron.monthly are configured - Corrected Typo in audit (Ticket 6933)
Jul 2, 2019	2.0.0	UPDATE - Ensure system accounts are non-login - Title changed to "Ensure system accounts are secured" (Ticket 8512)
Jul 2, 2019	2.0.0	UPDATE - Ensure system accounts are secured - Updated audit and remediation (Ticket 8512)
Jul 2, 2019	2.0.0	ADD - systemd-timesyncd subsection (Ticket 6698)
Jul 2, 2019	2.0.0	UPDATE - Ensure XD/NX support is enabled - Audit updated (Ticket 8452) (Ticket 8460)
Jul 2, 2019	2.0.0	UPDATE - Ensure default user shell timeout is 900 seconds or less - Changed from Level 2 to Level 1 (Ticket 8661) (Ticket 5691)
Jul 2, 2019	2.0.0	UPDATE - Ensure filesystem integrity is regularly checked - Updated audit and remediation (Ticket 8474) (Ticket 6257)
Jul 2, 2019	2.0.0	ADD - Ensure SSH allowtcpforwarding is disabled - Recommendation added (Ticket 2847)
Jul 2, 2019	2.0.0	UPDATE - Ensure IMAP and POP3 server is not enabled - Updated Notes section (Ticket 8669)
Jul 2, 2019	2.0.0	UPDATE - Ensure system accounts are secured - Updated audit and remediation (Ticket 8679) (Ticket 8683)
Jul 2, 2019	2.0.0	UPDATE - Ensure chrony is configured - Updated audit section (Ticket 8238)
Jul 2, 2019	2.0.0	ADD - Configure journald - Section added for journald (Ticket 8568)

Jul 2, 2019	2.0.0	ADD - Ensure SSH MaxStartups is configured - Recommendation added (Ticket 7115)
Jul 2, 2019	2.0.0	Add - Ensure SSH MaxSessions is set to 4 or less - Recommendation added (Ticket 7115)
Jul 2, 2019	2.0.0	UPDATED - Ensure mounting of FAT filesystems is limited - Corrected Impact Statement (Ticket 8681)
Jul 2, 2019	2.0.0	UPDATE - Ensure sticky bit is set on all world-writable directories - Updated audit and remediation (Ticket 8682)
Jul 2, 2019	2.0.0	ADD - Mappings to CIS Controls v7.0 - Mappings added (Ticket 8519)
Jul 2, 2019	2.0.0	UPDATE - Ensure no world writable files exist - Updated audit procedure (Ticket 8684)
Jul 2, 2019	2.0.0	UPDATE - Ensure no unowned files or directories exist - Updated audit procedure (Ticket 8685)
Jul 2, 2019	2.0.0	UPDATE - Ensure no ungrouped files or directories exist - Updated audit procedure (Ticket 8686)
Jul 2, 2019	2.0.0	UPDATE - Audit SUID executables - Updated audit procedure (Ticket 8687)
Jul 2, 2019	2.0.0	UPDATE - Audit SGID executables - Updated audit procedure (Ticket 8688)
Jul 2, 2019	2.0.0	UPDATE - Audit SGID executables - Corrected Description Section (Ticket 8451)
Jul 2, 2019	2.0.0	ADD - Ensure Mandatory Access Control Software is installed - Section added (Ticket 8477)
Jul 2, 2019	2.0.0	ADD - Ensure only strong Ciphers are used - Recommendation added (Ticket 7070)
Jul 2, 2019	2.0.0	ADD - Ensure only strong Key Exchange algorithms are used - Recommendation added (Ticket 7070)
Jul 2, 2019	2.0.0	ADD - Ensure only strong MAC algorithms are used - Recommendation added (Ticket 7070)

Jul 2, 2019	2.0.0	ADD - Configure IPv6 ip6tables - Section added for IPv6 Tables
Jul 2, 2019	2.0.0	ADD - Ensure IPv6 default deny firewall policy
Jul 2, 2019	2.0.0	ADD - Ensure IPv6 loopback traffic is configured
Jul 2, 2019	2.0.0	ADD - Ensure IPv6 outbound and established connections are configured
Jul 2, 2019	2.0.0	ADD - Ensure IPv6 firewall rules exist for all open ports
Jul 2, 2019	2.0.0	UPDATE - Ensure separate partition exists for /var - Added Notes (Ticket 8689)
Jul 2, 2019	2.0.0	UPDATE - Ensure separate partition exists for /var/log - Added Notes (Ticket 8689)
Jul 2, 2019	2.0.0	UPDATE - Ensure separate partition exists for /var/log/audit - Added Notes (Ticket 8689)
Jul 2, 2019	2.0.0	UPDATE - Ensure nodev option set on /tmp partition - Updated audit (Ticket 8690)
Jul 2, 2019	2.0.0	UPDATE - Ensure nosuid option set on /tmp partition - Updated audit (Ticket 8690)
Jul 2, 2019	2.0.0	UPDATE - Ensure noexec option set on /tmp partition - Updated audit (Ticket 8690)
Jul 2, 2019	2.0.0	UPDATE - Ensure nodev option set on /var/tmp partition - Updated audit (Ticket 8690)
Jul 2, 2019	2.0.0	UPDATE - Ensure nosuid option set on /var/tmp partition - Updated audit (Ticket 8690)
Jul 2, 2019	2.0.0	UPDATE - Ensure noexec option set on /var/tmp partition - Updated audit (Ticket 8690)
Jul 2, 2019	2.0.0	UPDATE - Ensure nodev option set on /home partition - Updated audit (Ticket 8690)
Jul 2, 2019	2.0.0	UPDATE - Ensure nodev option set on /dev/shm partition - Updated audit (Ticket 8690)

Jul 2, 2019	2.0.0	UPDATE - Ensure nosuid option set on /dev/shm partition - Updated audit (Ticket 8690)
Jul 2, 2019	2.0.0	UPDATE - Ensure noexec option set on /dev/shm partition - Updated audit (Ticket 8690)
Jul 2, 2019	2.0.0	Draft created for final review
Jul 3, 2019	2.0.0	UPDATE - Ensure /tmp is configured - Corrected error in audit script (Ticket 8698)
Jul 3, 2019	2.0.0	UPDATE - Ensure /tmp is configured - Corrected error in audit (Ticket 8700)
Jul 3, 2019	2.0.0	UPDATE - Ensure separate partition exists for /var - Corrected error in audit script (Ticket 8699)
Jul 3, 2019	2.0.0	UPDATE - Ensure SSH access is limited - Remove extra double quote from audit (Ticket 8701)
Jul 10, 2019	2.0.0	UPDATE - Ensure all users' home directories exist - Update audit (Ticket 8736)
Jul 10, 2019	2.0.0	UPDATE - Ensure users' home directories permissions are 750 or more restrictive - update audit (Ticket 8737)
Jul 10, 2019	2.0.0	UPDATE - Ensure users own their home directories - Update audit (Ticket 8738)
Jul 10, 2019	2.0.0	UPDATE - Ensure users' dot files are not group or world writable - Update audit (Ticket 8739)
Jul 10, 2019	2.0.0	UPDATE - Ensure no users have .forward files Accepted - Update audit (Ticket 8741)
Jul 10, 2019	2.0.0	UPDATE - Ensure no users have .netrc files - Update audit (Ticket 8742)
Jul 10, 2019	2.0.0	UPDATE - Ensure users' .netrc Files are not group or world accessible - Update audit (Ticket 8743)
Jul 10, 2019	2.0.0	UPDATE - Ensure no users have .rhosts files - Update audit (Ticket 8744)
Name and the same		

Jul 15, 2019	2.0.0	UPDATE - Ensure permissions on /etc/passwd- are configured - update audit (Ticket 8243) (Ticket 8750)
Jul 16, 2019	2.0.0	Published